MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1, HIGH ANGLE,
(155-AN-1), (P/N 11785434-47)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described herein shall consist of this docunent and the latest issue of Specification MIL-S-64045

ACCURACY DATA

		ICM 718/741		ICM 692/731		ICM 483A1	
Charge	Range (meters)	Elevation (mils)	Fuze Setting	Elevation (mils)	Fuze Setting	Elevation (mils)	Fuze Setting
3	3000	281±1	10.6±0.1	452±1	12.1±.1	318±1	11.33.1
	5500	624±1	27.0±0.1	770±1	31.2±0.1	615±1	27.3±0.1
4	4500	308±1	15.3±0.1	423±1	16.6±0.1	338±1	15.9±0.1
	7000	594±1	30.1±0.1	700±1	33.1±0.1	598±1	30.8±0.1
6	6000	220±1	15.9±0.1	317±1	16.5±0.1	264±1	16.19.1
	10000	458±1	32.8±0.1	520±1	34.1±0.1	487±1	33.4±0.1
8	10000	224±1	22.8±0.1	254±1	23.2±0.1	266±1	22.9±0.1
	17000	669±1	57.0±0.1	702±1	58.5±0.1	690±1	58.0±.01

Custodian:
ARMY-AR

Preparing Activity
ARMY-AR

Project No. 1220-A293/

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:14Z
Check the source to verify that this is the current version before use.