MIL-B-45081D(AL)
3 June 1983
SUPERSEDING
MIL-B-45081C(AL)
30 March 1979

MILITARY SPECIFICATION

BLAST CLEANING MACHINE: SELF-CONTAINED TUMBLE TYPE, WITH DUST COLLECTOR

This specification is approved for use by the US Army Armament Materiel Readiness Command, Department of the Army, and is available for use by all Departments and Agencies of The Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a self-contained tumble type blast cleaning machine, including dust collector, in which the abrasive is directed by centrifugal force on the objects being cleaned.

1.2 Classification. The blast cleaning machines covered by this specification shall be the following sizes, as specified (see 6.2):

Size 1-1 1/2 cubic feet minimum (covering 1-1/2 cu. ft. machines)
Size 2-3 cubic feet minimum (covering 3 to 5 cu. ft. machines)
Size 3-6 cubic feet minimum (covering 6 to 7 cu. ft. machines)
Size 4-12 cubic feet minimum (covering 12 to 14 cu. ft. machines)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Materiel Readiness Command, ATTN: DRSAR-LEE-S, Rock Island, IL 61299 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller)

MILITARY

MIL-S-12514 - Starters, Motor; Across-the-Line and Reduced Voltage Types, A-C Induction, 3/4 to 100 HP, Manual and Electric
MIL-M-18058 - Machinery, Metal and Wood-Working, Support Equipment and Associated Repair Parts; Preparation for Delivery of

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards For Federal Services

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-889 - Dissimilar Metals

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DOD adopted shall be the issue listed in the current DODISS and the supplement thereto, if applicable.

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

NEMA Electrical Standards

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish one complete blast cleaning machine for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The blast cleaning machine shall be new and of the latest standard commercial design meeting the performance requirements of this specification. The blast cleaning machine shall be a self-contained tumble type with a load capacity of not less than the minimum cubic feet shown for the size specified in Table I. The machine shall house an endless belt conveyor upon which the parts to be cleaned are loaded, tumbled while being cleaned, and unloaded. The machine, with the door closed, shall be dust and abrasive tight. The blast action shall be accomplished by a controlled centrifugal force acting upon the abrasive. An abrasive recovery and handling system shall be provided as an integral part of this unit. The dust collector shall be a separate cabinet with its own power source (motor). All parts subject to wear or replacement shall be accessible for adjustment and repair when using standard tools and maintenance equipment.

3.3 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the producing industry. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.3.1 Reclaimed materials. The contractor is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity, and intent of the materials originally selected or specified. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment.

3.4 Construction. The blast cleaning machine shall be complete, and shall be capable of operating in accordance with the requirements specified herein. All parts used in fabrication shall be new. There shall be no process used for reclaiming any parts of the blast cleaning machine. All surfaces of all parts shall be clean and free from extraneous materials. External surfaces shall be smooth and free of sharp edges. All screws, pins, bolts, and similar locking

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

parts shall be installed with a means for preventing loss of tightness. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked, or otherwise permanently deformed.

3.4.1 Interchangeability. All replaceable parts shall be manufactured to such standards as shall permit replacement or adjustment without modification of the parts or the blast cleaning machine.

3.4.2 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.4.3 Electrical connections. Connections of conductors and terminal parts shall be of the screw, pressure, or solder type. When soldered connections are used, the conductors and terminal parts shall be mechanically secured before soldering. Rosin base fluxes only shall be used in soldering operations. Connections to screw-type terminals shall be mechanically secured with a means to prevent loss of tightness.

3.4.4 Gears. All gears and pinions used in the machine and in its components and assemblies shall be constructed from a material suitable for the intended purpose. Gears and pinions shall be machined and heat treated. This process shall impart the hardness, toughness, and smoothness that shall enable the gear train to transmit the full rated torque of the drive motor without gear damage, failure, or premature deterioration and wear.

3.4.5 Lubrication. All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with standard means for lubrication. Oil holes, grease fittings, and filler caps shall be accessible. Lubrication reservoirs, if applicable, shall have means for checking levels.

3.4.6 Safety devices. Each blast cleaning machine shall have safety devices wherever parts could be hazardous to the operator. All moving parts located on the blast cleaning machine from floor level to a height of eight feet shall be enclosed to prevent injury. Protection against electric shock shall be provided. Special safety devices shall be provided when specified (see 6.2).

3.5 Performance and product characteristics.

3.5.1 Function of blast cleaning machine. The blast cleaning machine shall be capable of performing a predetermined blast cleaning cycle. This performance shall consist of tumbling and cleaning a work load while circulating a metallic abrasive. The work load shall be tumbled on an endless belt conveyor. The circulating rate of the metallic abrasive flow shall be accomplished through the combined facilities of an airless blasting unit, the endless belt conveyor, and an elevator. The minimum abrasive capacity of the cleaning machine shall be sufficient to maintain the minimum rate of flow.

3.5.2 Function of dust collector. The dust collector shall be capable of filtering dust particles from the air inside the cleaning cabinet so the exhaust air shall not contaminate the air in the building. A shaking device shall remove the dust from the tubes when the air flow through the dust collector is shut off.

3.6 Detail of components. The blast cleaning machine shall consist of, but not be limited to, the following component parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

3.6.1 Machine cabinet and frame. The machine cabinet and frame shall accommodate an endless belt conveyor, the drive mechanism, an airless blasting unit, the abrasive handling and reclaim system, and motors. The blast cleaning machine shall be mounted at floor level. The machine cabinet shall be fabricated from steel plates or panels not less than Manufacturers Standard Gage No. 14. These plates or panels shall be welded on a steel frame. The section surrounding the blast cleaning chamber shall be dust and abrasive tight. Inspection doors or plates shall be provided for access to all serviceable parts or assemblies. The cabinet and frame shall be capable of supporting a minimum of 3,000 pounds, which includes the cleaner components, work load, and abrasive load, without showing any evidence of damage. An instruction plate shall be located on the front of the machine cabinet. These instructions shall include the proper operating and service procedures for the blast cleaning machine.

3.6.1.1 Cabinet work door. The cabinet work door shall be dust and abrasive tight when closed. The opening and closing of the door may be either manually or power operated. The door shall be provided with a safety inner-lock switch, which stops the blasting unit when the door is open and prevents the conveyor from reversing when the door is closed. The door shall be provided with a lock, which locks automatically when the door is closed and has to be manually or electrically unlocked before the door can be opened.

3.6.2 Airless blasting unit. The airless blasting unit shall be provided with a cycle control plug or valve, which shall stop the blasting unit and abrasive flow at the end of the blast cycle or when any of the other cleaning machine operations are interrupted. The blasting unit shall be driven by a 5 horsepower (hp), fan-cooled motor (minimum) with multiple V-belt drive. The blasting unit shall consist of the following principal components.

3.6.2.1 Shaft and bearing assembly. The shaft and bearing assembly shall be of dust tight construction. The shaft and bearing assembly shall consist of ball or roller bearings, shaft, and dust proof oil seals appropriate to the type of machine construction and mounting. The shaft shall be constructed to accommodate the wheel or runner assembly.

3.6.2.2 Wheel or runner assembly. The wheel or runner assembly shall consist of the blades or vanes, an impeller, and a control cage mounted on the shaft and bearing assembly. A minimum of eight replaceable blades or vanes shall be secured to the hub or side plates of the wheel or runner assembly.

3.6.2.2.1 Impeller and control cage. The impeller and control cage shall be mounted on the inside diameter of the wheel to distribute abrasive to the blades or vanes. The abrasive shall be fed by gravity into the impeller and, from there, the impeller paddles shall discharge the abrasive through slots in the control cage onto the blades or vanes, which direct the abrasive at high velocity against the tumbling work pieces.

3.6.2.3 Wear plates. The inside of the wheel or runner housing shall be completely lined with replaceable wear plates. The inside ends of the drum or barrel heads shall be lined with replaceable wear plates. All wear plates shall be of a wear-resistant material with at least 50 times the life of mild steel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

3.6.2.4 Abrasive flow and direction control. The rate of flow and the direction of the abrasive for blast cleaning shall be capable of being controlled by the operator. The control device shall be mechanical and shall be accessible for adjustment by the operator.

3.6.3 Endless belt conveyor. The endless belt conveyor shall be made of an abrasive-resisting metal or of a molded rubber base material, as specified (see 6.2). If a rubber belt conveyor is used, a mechanically connected belt is not acceptable. Holes of 1/4 inch nominal diameter shall be provided in the belt to allow the abrasive to fall into the hopper and the abrasive handling mechanism. Adjustments for tension and alignment of the belt conveyor shall be made from the outside of the cabinet. A totally enclosed, dust tight, safety mechanism shall be provided to stop the blasting unit and the belt conveyor if work is jamming or if the belt conveyor is overloaded.

3.6.3.1 Work load capacity. The maximum work load capacity of the belt conveyor shall be as specified in Table I. The belt conveyor shall also be able to withstand the impact of pieces weighing 25 pounds. Holding and tumbling the work load shall be done without evidence of strain or damage to the blast cleaning machine or any of its components.

3.6.3.2 Conveyor pulleys and guides. The conveyor pulleys and guides shall be mounted on the machine frame, and shall be constructed to prevent the abrasive from clogging or building up between the pulleys and belt conveyor.

3.6.3.3 Conveyor drive. The belt conveyor shall be driven by the applicable motor specified in Table I. The conveyor drive shall run from the motor through a reducer unit to the rear conveyor shaft. The drive shall be protected from direct blast of the abrasive.

3.6.4 Drum or barrel heads. A drum or barrel head shall be located on each side of the belt conveyor to guide its travel and to form the contour of the blasting chamber, where the work load is held and tumbled for cleaning. The heads shall be driven by the belt conveyor. The heads shall be made of heavy steel and shall have provisions for securing wear plates to the inside faces. The drum or barrel head hubs shall be mounted on heavy duty antifriction type bearings in dust-tight housings.

3.6.5 Abrasive handling system. The abrasive handling system shall retrieve the used abrasive from beneath the belt conveyor and return it to the storage hopper, completing the cycle for abrasive cleaning. The abrasive handling system shall consist of an elevator and drive mechanism, a removable wire screen abrasive separator, and a storage hopper.

3.6.5.1 Elevator and drive mechanism. A bucket-type elevator shall carry the abrasive from the hopper, which is located beneath the belt conveyor and screen, to the separator. From here the abrasive shall fall into the abrasive storage hopper. The elevator shall be motor driven by a standard V-belt unit or appropriate reduction drive unit. The elevator tension and alignment shall be adjustable without requiring disassembly of the elevator or any of its components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

TABLE I. Size and requirements

CHARACTERISTIC	REQUIREMENT Size 1	Size 2	Size 3	Size 4
Load capacity (cubic feet), not less than	1.5	3	8.5	12
Work load (pounds), not less than	225	400	1,000	1,500
Metallic abrasive (pounds)	4,500	15,000	25,000	40,000
Max. work load capacity of belt conveyor (pounds)	225	400 (not less than)	1,000	1,500
Conveyor drive motor	1/3 hp	1/2 hp	3/4 hp	1 hp
Elevator drive motor	1/2 hp	3/4 hp	1 hp	1-1/2 hp
Storage hopper capacity, abrasive flow (pounds)	4,500	15,000	25,000	40,000
Exhaust fan motor	2 hp	3 hp	4 hp	5 hp
Air-cloth-ratio (cu. ft. per min.)	3.5 to 1	4.5 to 1	5.5	6.5
Outlet velocity of air from the exhauster (feet per minute)	2,400	3,300	4,300	5,300
Cloth dust filters (square feet)	300	350	450	550

3.6.5.2 Removable wire screen. A removable wire screen shall be provided between the apron conveyor and the abrasive hopper for removing all coarse refuse from used abrasive.

3.6.5.3 Abrasive separator. An abrasive separator shall be located between the storage hopper and where the abrasive is emptied from the elevator buckets. The abrasive separator shall separate the dust, refuse, and abrasive fines from the usable abrasive. The dust and abrasive fines shall be exhausted by the dust collector, and the coarser refuse shall be diverted from entering the abrasive storage hopper and shall be collected in another area in the cabinet. Any mechanical action required by the separator shall be provided by the elevator drive mechanism.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

3.6.5.4 Storage hopper. The storage hopper shall be mounted over the airless blasting unit so that the abrasive is gravity fed to the blasting unit. The storage hopper shall have an adjustable orifice for regulating the abrasive rate of flow to the blasting unit. The storage hopper shall have the capacity to maintain a minimum abrasive flow to the airless blasting unit as specified in Table I.

3.6.6 Dust collector. Unless otherwise specified (see 6.2), a dust collector shall be supplied with each machine. The dust collector shall be the suction type and shall consist of, but not be limited to, the following principal component parts.

3.6.6.1 Dust collector cabinet and frame. The dust collector cabinet shall have a steel frame capable of supporting at least 2,500 pounds. The cabinet panels shall be fabricated from sheet steel not less than Manufacturers Standard Gage No. 14. The cabinet shall provide access to the dust filters for periodic inspection and replacement. The cabinet area enclosing the dust filters shall be dust tight.

3.6.6.2 Cloth dust filters. The total area of the cloth dust filters shall be not less than the area specified in Table I. The dust filters shall be attached to the shaking mechanism so that no part of the filtering area will touch any part of the cabinet or mechanism.

3.6.6.3 Filter shaking mechanism. The shaking mechanism shall be mounted on the top or side of the cabinet. The shake action shall effectively remove dust without damaging the dust filters. If an electric motor is required, a unit of not less than one-third horsepower shall be used.

3.6.6.4 Dust hopper. The dust hopper shall be mounted directly beneath the dust filter cabinet with an 18 inch clearance from the floor. Only updraft type filter systems shall require a screen or baffle which shall prevent coarse material from being drawn into the filter before dropping into the hopper. Dust and all foreign refuse shall be removed by manually opening a locked gate at the bottom of the hopper.

3.6.6.5 Exhaust fan and motor. The exhaust fan and motor may be mounted on top of the cabinet. The exhaust fan motor shall be as specified in Table I. The exhaust fan and motor shall be capable of handling at least 1,050 cubic feet of air per minute (cfm) at 6 inches of water column static pressure. The air-cloth-ratio shall not exceed that specified in Table I at the maximum cfm. The outlet velocity of the air from the exhauster shall be as specified in Table I. The motor and exhaust fan shall be provided with a multiple V-belt drive when belts are required to transmit power. Updraft type filter systems shall be provided with an interrupt circuit which shall prevent simultaneous operation of the shake mechanism and exhauster. Downdraft filter systems shall be provided with means for breaking negative pressure at intervals during continuous operation of the exhauster.

3.6.6.6 Operating controls. The operating control panel shall include all the electrical controls with their function properly marked. The wiring circuit and components within the control panel shall conform to applicable NEMA Electrical Standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

3.6.6.7 Instruction plate. An instruction plate shall be located on the front of the dust collecting cabinet. These instructions shall include the proper operating and service procedures for the dust collector.

3.6.7 Electrical components. Unless otherwise specified (see 6.2), the blast cleaning machine shall be completely wired when furnished. Electrical components, including starters, relays, switches, wiring, and their enclosures, shall conform to, and shall be located in accordance with, NEMA Electrical Standards except as specified herein. There shall be no component part used in any application where the requirements exceed the manufacturer's rating for the part.

3.6.7.1 Motors. Unless otherwise specified (see 6.2), all motors shall be the induction, squirrel-cage type, totally enclosed, dust tight, and operate from 230/460 volts, 60 hertz (Hz), alternating current (ac), 3-phase, conforming to the requirements of CC-M-1807, with class B insulation and continuous duty rating. When starters are required, they shall conform to type I, class 2 requirements of MIL-S-12514. Motors shall be initially wired for 230 volts.

3.6.7.2 Push button circuits. Push button stations shall be provided for each starter, and shall be located on the cabinet within easy reach of the operator. All push button circuits shall be 115 volt. Each motor shall be provided with an individual dustproof push button switch.

3.7 Spare parts. When specified (see 6.2), the following spare parts shall be furnished with each machine in the quantity specified:

Item		Quantity
(a)	Vanes or blades for blasting unit	One set
(b)	Wear plates for blasting unit	One set
(c)	Wear plates for drum or barrel heads	One set

3.8 Painting. Unless otherwise specified (see 6.2), painting and finishing shall be in accordance with standard commercial practice provided the following minimum criteria are met or exceeded: all surfaces to be painted shall be clean and free of all foreign matter detrimental to painting and at least one coat of primer and one coat of enamel, or equivalent, applied.

3.9 Product identification. The blast cleaning machine shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2), shall include the National Stock Number.

3.10 Workmanship. Standards of workmanship shall assure that the blast cleaning machine shall have the stability and efficient operating characteristics found in standard commercial items and as specified in Section 3 herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2), quality conformance inspection shall consist of (a) through (c) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).

(b) Tests (see 4.6).

(c) Packaging inspection (see 4.7).

4.4.1 Sampling. When required (see 6.2), sampling for quality conformance inspection shall be as specified in MIL-STD-105 at the Inspection Level and Acceptable Quality Level (AQL) specified in the contract. For packaging inspection (see 4.7), special inspection level S-4 and an AQL of 4.0 percent defective shall be used.

4.5 Product examination. Each complete blast cleaning machine shall be examined to determine compliance with Section 3. As a minimum, the following characteristics shall be examined:

CHARACTERISTICS	REQUIREMENT PARAGRAPH
Construction and assembly, not as specified	3.4
Threads, not as specified	3.4.2
Electrical connections, not as specified	3.4.3
Lubrication requirements, not as specified	3.4.5
Safety devices, as required	3.4.6
Principal components, not as specified	3.6
Machine cabinet and frame	3.6.1
Airless blasting unit	3.6.2
Endless belt conveyor	3.6.3
Drum or barrel heads	3.6.4
Abrasive handling system	3.6.5
Dust collector	3.6.6
Electrical components not as specified	3.6.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

Motors	3.6.7.1
Push button circuits	3.6.7.2
Spare parts when required	3.7
Painting not as specified	3.8
Identification marking not as specified	3.9
Workmanship not as specified	3.10

4.6 Tests.

4.6.1 Loading to capacities. Before testing, the blast cleaning machine shall be loaded for operation. The belt conveyor shall be loaded with the applicable maximum work load specified in Table I. The abrasive handling system shall be loaded with metallic abrasive to the applicable minimum capacity that shall maintain the rate of flow shown in Table I.

4.6.6.1 Conveyor load capacity. The belt conveyor shall be operated through a cycle that includes agitating the work load, opening and closing the work door, and reversing the belt conveyor to unload the conveyor to determine compliance with 3.6.3.1

4.6.1.2 Abrasive rate of flow. While the blast cleaning machine is in operation, a measurement of the abrasive rate of flow between the storage hopper and the airless blasting unit shall be taken to determine compliance with 3.5.1.

4.6.2 Functional test of blast cleaning machine. The blast cleaning machine shall be loaded in accordance with 4.6.1. The machine shall then be operated through a complete blast cleaning cycle including working all the principal components, controls, valves, switches, and other working parts necessary in order to determine compliance with 3.5.1.

4.6.3 Functional test of dust collector. The dust collector shall be connected to the blast cleaning machine with a minimum distance of 20 feet between the two units. The dust collector functional test shall be run simultaneously with that of the blast cleaning machine. The dust collector shall exhaust from the cleaning machine and discharge the filtered air at the applicable velocity specified in Table I without contaminating the air in the building. The shaking device shall be actuated to remove the dust from the tubes after the exhauster has been shut off (see 3.5.2).

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be Level A in accordance with MIL-M-18058 or Industrial in accordance with ASTM D3951-82, as specified (see 6.2).

6. NOTES

6.1 Intended use. The blast cleaning machine covered by this specification is intended for use in removing rust, scale, and burrs from metal shapes, for the preparation of metal surfaces for plating, and for cleaning castings and forgings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:19Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).
(c) First article when required (see 3.1).
(d) Special safety devices when required (see 3.4.6 and 6.4).
(e) Type of endless belt conveyor required (see 3.6.3).
(f) Dust collector if different (see 3.6.6).
(g) Wiring of electrical components if different (see 3.6.7).
(h) Motors if different (see 3.6.7.1).
(i) Spare parts when required (see 3.7).
(j) Painting if different (see 3.8).
(k) Identification marking if different (see 3.9).
(l) First article inspection if different (see 4.3).
(m) Quality conformance inspection if different (see 4.4).
(n) Applicable level of protection required (see 5.1).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.4 Safety and health requirements. In order that equipment integrated into the user's operational environment will comply with OSHA limitations and controls of noise levels, radiation, electromagnetic emissions, noxious vapors, heat, etc., as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - AL

Review activity:

Army - SM

Preparing activity:
Army - AL

Project No. 4940-A459

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:19Z
Check the source to verify that this is the current version before use.