MIL-F-45060D (PA)
15 May 1975
Superseding
MIL-F-45060C (MU)
14 February 1969

MILITARY SPECIFICATION

FUZE, MINE, COMBINATION, M605
PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for one type of fuze designated as Fuze, Mine, Combination, M605

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this Specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-Z-325 - Zinc Coating, Electrodeposited, Requirements for
QQ-P-416 - Plating, Cadmium (Electrodeposited)

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specifications For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

MIL-STD-171 - Systems for Preparation, Painting and Finishing Metal and Wood Surfaces
MIL-STD-1169- Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

9298314 - Fuze, Mine, Comb M605, Parts Arrangement

(Copies of specifications, standards and drawings required by contractors In connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*For meaning of asterisk see 6.7

3. REQUIREMENTS (see 6.6)

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts and assemblies. - The parts and assemblies shall comply with all requirements specified on Drawing 929831.4, associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Embrittlement of springs. - Striker springs, release pin springs, release pin rings and pressure springs shall not break when extended to the minimum point of permanent distortion.

*3.4 Non-functioning of head assembly. - The head assembly prior to loading with silicone grease, shall not function when a 3.0 pound minimum load *is* applied to the release pin ring parallel to the axis of' the release pin, and when a 8.0 pound minimum load is applied to any one prong, or equally distributed upon all three prongs parallel to the axis of the head assembly.

*3.5 Functioning of head assembly. - The head assembly, prior to loading with silicone grease, shall function when a 12.0 pound maximum load is applied to the release pin ring parallel to the axis of the release pin, and when a 20.0 pound maximum load is applied to any one prong or equally distributed upon all three prongs parallel to the axis of the head assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:17Z
Check the source to verify that this is the current version before use.

3.6 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, cracks, chips, sharp edges, unblended radii, surface defects, dirt, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to my part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few , light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for Inspection and standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. The following certification is required:

Certification of conformance denoting performance of cold set operation on the striker spring *as* per dwg. 7548309 shall be furnished with each lot submitted for acceptance.

*4.2 Classification of inspections. - The following types of inspections shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

*4.3 First article inspection -

*4.3.1 Submission. - The contractor shall submit a first article sample (see 6.2b) as designated by the contracting officer. The first article sample shall consist of 50 assemblies and 25 complete sets of parts (i.e., 25 each of every component and every sub-assembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production process, procedures and equipment which will be used in fulfilling the contract. The first article shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

*4.3.2 Inspections to be performed. - See MIL-A-48078 the examinations of paragraphs 4.4.2.1 thru 4.4.2.16 and Table I specified herein.

*4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

*TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
	Head Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Pressure (Dwg. 7548298)				
	Examination for Defects	10		3.2	4.4.2.1
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Spring, Release Pin (Dwg. 7548308)				
	Examination for Defects	10		3.2	4.4.2.2
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Ring, Release Pin (Dwg. 7548307)				
	Examination for Defects	10		3.2	4.4.2.3
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

*TABLE I - FIRST ARTICLE INSPECTION CONTINUED

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
	Head Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Striker (Dwg. 7548309)				
	Examination for Defects	10		3.2	4.4.2.4
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Pin, Release (Dwg. 7548305)				
	Examination for Defects	10		3.2	4.4.2.5
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Pin, Safety, Inter-Locking (Dwg. 7548294)				
	Examination for Defects	10		3.2	4.4.2.6
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

*TABLE I - FIRST ARTICLE INSPECTION CONTINUED

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
	Head Assembly and Components				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Striker (Dwg. 7548310)				
	Examination for Defects	10		3.2	4.4.2.10
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Pin, Safety, Striker (Dwg. 7548295)				
	Examination for Defects	10		3.2	4.4.2.12
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Prong (Dwg. 7548297)				
	Examination for Defects a. Total Length (min) b. Diameter (min) c. Diameter of Knob (max)	10		3.2	7548297/Gage
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

*TABLE I - FIRST ARTICLE INSPECTION CONTINUED

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
	Head Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Washer (Dwg. 7548311)				
	Examination for Defects a. Thickness (max) b. Outside Diameter (min) c. Diameter of Hole (max)	10		3.2	7548311/Gage
	Plating thickness test	5		3.2	4.5.4
	Salt Spray test	5		3.2	4.5.5
	Plating Adhesion test	5		3.2	4.5.6
	Head Assembly (Dwg. 7548285)				
	Examination for Defects	50		3.2	4.4.2.16
	Non-Functioning Test	50		3.5	4.5.1
	Functioning Test	50		3.6	4.5.2

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

*4.4.1 Inspection Lot Formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

*4.4.2 Examination. - See MIL-A-48078.

a. Sampling Plans. - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548298
*4.4.2.1	Spring, Pressure				NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter (max)		0.40%	3.2	Gage
132	Inside diameter (min)		0.40%	3.2	Gage
133	Solid height (max)		0.40%	3.2	Gage
134	Load at assembled height (min)		0.40%	3.2	Gage
135	Load at functioning height		0.40%	3.2	Gage
136	Spring embrittlement	(a)	0.40%	3.3	4.5.3
Minor					
201	Ends not closed		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

(a) MIL-STD-105, code letter K shall apply until three lots have met the criteria after which code letter G shall apply.

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.2	Spring, Release Pin				7548308
					NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter (max)		0.40%	3.2	Gage
132	Inside diameter (min)		0.40%	3.2	Gage
133	Solid height (max)		0.40%	3.2	Gage
134	Load at assembled height (min)		0.40%	3.2	Gage
135	Load at 0.2 inch height (max)		0.40%	3.2	Gage
136	Spring embrittlement	(a)	0.40%	3.3	4.5.3
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) MIL-STD-105, code letter K shall apply until three lots have met the criteria after which code letter G shall apply.

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.3	Ring, Release Pin				7548307
					NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Ring does not return to initial open position when closed and released		0.40%	3.2	Manual
132	Parallelism of legs at assembled position		0.40%	3.2	Gage
133	Spring embrittlement	(a)	0.40%	3.3	4.5.3
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

(a) MIL-STD-105, code letter K shall apply until three lots have met the criteria after which code G shall apply.

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.4	Spring, Striker				7548309
					NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter (max)		0.40%	3.2	Gage
132	Inside diameter (min)		0.40%	3.2	Gage
133	Solid height (max)		0.40%	3.2	Gage
134	Load at 1.0 inch compressed length		0.40%	3.2	Gage
135	Load at 1.375 inches compressed length		0.40%	3.2	Gage
136	Spring embrittlement	(a)	0.40%	3.3	4.5.3
Minor					
201	Ends not closed or not ground flat		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) MIL-STD-105, code letter K shall apply until three lots have met the criteria after which code letter G shall apply.

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.5	Pin, Release				7548305
					NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Distance between striker hole and release pin ring hole		0.40%	3.2	Gage
132	Distance between spring seat and cotter pin hole		0.40%	3.2	Gage
133	Diameter of striker hole		0.40%	3.2	Gage
134	Angle of taper at trigger contact area		0.40%	3.2	Gage
135	Run out of small outside diameter with large outside diameter		0.40%	3.2	Gage
136	Distance between spring seat and base of taper		0.40%	3.2	Gage
137	Outside diameter		0.40%	3.2	Gage
138	Outside diameter across flat		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.6	Pin, Safety, Interlocking		7548294
			NEXT HIGHER ASSEMBLY
			7548285

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Total length (min)		0.40%	3.2	Gage
132	Diameter (min)		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 20260-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.7	Head, Safety				7548293
					NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	none defined				
Major B					
131	Diameter of striker hole		0.40%	3.2	Gage
132	Outside diameter (min)		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548302
#4.4.2.8	Case				NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Major diameter of external thread		0.40%	3.2	Gage
102	Pitch diameter of external thread		0.40%	3.2	Gage
103	Minor diameter of internal thread (max)		0.40%	3.2	Gage
104	Pitch diameter of internal thread, max		0.40%	3.2	Gage
Major B					
131	Inside diameter of head cavity		0.40%	3.2	Gage
132	Depth of head cavity, min		0.40%	3.2	Gage
133	Outside diameter at both ends		0.40%	3.2	Gage
134	Inside diameter		0.40%	3.2	Gage
135	Depth to bottom of internal thread		0.40%	3.2	Gage
136	Length from internal thread face to external thread		0.40%	3.2	Gage
137	Total length		0.40%	3.2	Gage
138	Length from internal thread face to shoulder above external thread		0.40%	3.2	Gage
139	Wrench flats missing or damaged		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4010

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.9	Tube, Charge, Flash, Igniter				7548314
					NEXT HIGHER ASSEMBLY
					9298314
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Thickness through bottom		0.40%	3.2	Gage
132	Inside diameter		0.40%	3.2	Gage
Minor					
201	Total length		0.40%	3.2	Gage
202	Tube damaged (dented, wrinkled, or cut)		0.40%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T02:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548310
#4.4.2.10	Striker				NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Radius missing from inner corner of notch		100%	3.2	Visual
Major B					
131	Length from rounded end to end of notch		0.40%	3.2	Gage
132	Distance between hole and notch		0.40%	3.2	Gage
133	Diameter of flange		0.40%	3.2	Gage
134	Thickness through notch		0.40%	3.2	Gage
135	Finish improper		0.40%	3.2	Visual/Manual
Minor					
201	Profile of point		0.65%	3.2	Gage
202	Length of rounded point above flange		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548299
*4.4.2.11	Trigger				NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Outside diameter of prong flange, min.		0.40%	3.2	Gage
132	True position of center hole with flange		0.40%	3.2	Gage
133	Diameter of center hole, max		0.40%	3.2	Gage
134	Length to prong flange from angled point		0.40%	3.2	Gage
135	Diameter of plug cavity, max		0.40%	3.2	Gage
136	Angle of taper		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548295
#4.4.2.12	Pin, Safety, Striker				NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Small outside diameter (min)		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548292
*4.4.2.13	Head				NEXT HIGHER ASSEMBLY 7548285
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Diameter of large (trigger) cavity		0.40%	3.2	Gage
132	Diameter of smaller cavity adjacent to trigger cavity		0.40%	3.2	Gage
133	True position of smaller cavity with trigger cavity		0.40%	3.2	Gage
134	Diameter of striker cavity at case end		0.40%	3.2	Gage
135	True position of striker cavity at case end with trigger cavity		0.40%	3.2	Gage
136	Distance between bottom of trigger cavity and face of large diameter		0.40%	3.2	Gage
137	Distance between top of boss and striker cavity at case end		0.40%	3.2	Gage
Minor					
201	Outside diameter (small end)		0.65%	3.2	Gage
202	Smallest diameter of release pin hole, max		0.65%	3.2	Gage
203	Largest diameter of release pin hole		0.65%	3.2	Gage
204	Depth to first shoulder in release pin hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.14	Head, Flash Igniter	1 OF 1	7548312
			NEXT HIGHER ASSEMBLY: 9298314

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Major diameter of thread		0.40%	3.2	Gage
132	Pitch diameter of thread		0.40%	3.2	Gage
133	Length to shoulder behind thread		0.40%	3.2	Gage
134	Diameter of larger cavity		0.40%	3.2	Gage
135	Smaller cavity obstructed		0.40%	3.2	Visual
Minor					
201	Depth of larger cavity		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Large outside diameter		0.65%	3.2	Gage
204	Diameter of smaller cavity		0.65%	3.2	Gage
205	Outside diameter at large tube end		0.65%	3.2	Gage
206	True position of smaller cavity with outside diameter		0.65%	3.2	Gage
207	Thread damaged		0.65%	3.2	Visual
208	Wrench flats missing		0.65%	3.2	Visual
209	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.15	Housing, Primer				7548313
					NEXT HIGHER ASSEMBLY 9298314
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Major diameter of external thread		0.40%	3.2	Gage
102	Pitch diameter of external thread		0.40%	3.2	Gage
Major B					
131	Diameter of primer cavity		0.40%	3.2	Gage
132	Depth of primer cavity		0.40%	3.2	Gage
133	Minor diameter of internal thread		0.40%	3.2	Gage
134	Pitch diameter of internal thread		0.40%	3.2	Gage
135	Length to shoulder behind external thread		0.40%	3.2	Gage
136	Length of perfect internal thread, min		0.40%	3.2	Gage
137	Outside diameter at internal thread end		0.40%	3.2	Gage
Minor					
201	Depth to bottom of internal thread cavity		0.65%	3.2	Gage
202	Diameter of primer flash hole		0.65%	3.2	Gage
203	Total length		0.65%	3.2	Gage
204	Thread damaged		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4010

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 7548285
*4.4.2.16	Head Assembly				NEXT HIGHER ASSEMBLY 9298314
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Interlocking safety pin, striker safety pin or release pin of safety pin assembly missing or not interlocked		100%	3.2	Visual
2	Release pin, cotter pin missing or prong not bent		100%	3.2	Visual
Major B					
131	Distance from prong to top of release pin ring, max		0.40%	3.2	Gage
132	Total length, max		0.40%	3.2	Gage
133	Head does not rotate freely		0.40%	3.2	Manual
134	External case thread damaged		0.40%	3.2	Visual
135	Striker point damaged in case		0.40%	3.2	Visual
136	Star washer missing in case		0.40%	3.2	Visual
137	Release pin ring missing or incorrectly assembled		0.40%	3.2	Visual
138	Cords missing, damaged or knot missing from end		0.40%	3.2	Visual
139	Gasket missing from case		0.40%	3.2	Visual
140	Any part dented or distorted		0.40%	3.2	Visual
141	Crimp of case to head inadequate		0.40%	3.2	Visual
142	Prong missing or insecure		0.40%	3.2	Visual
143	Crimp of head over trigger inadequate		0.40%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

MIL-F-45060D(PA)

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
Cont'd *4.4.2.16	Head Assembly				7548285
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major B					
144	No evidence of grease extrusion at joints indicated on drawing		0.40%	3.2	Visual
145	Grease inside case, other than thin film		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship excluding interior of case		1.0%	3.7	Visual

NOTES:

SARPA QA FORM 2567, FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

*4.4.3.1 Non-functioning of head assembly (see 3.4) - Critical defect. - his test shall be performed 100 percent. Head assemblies failing to meet the specified requirements shall be classed defective and removed from the lot. The test shall be performed *as* specified in 4.5.1 using equipment In accordance with 4.4.4.

*4.4.3.2 Functioning of head assembly (see 3.5) - Major A defect.

*4.4.3.2.1 Beginning with the first lot produced and con-, timing until three (3) consecutive lots have complied with the acceptance criteria specified three hundred and fifteen (315) samples shall be selected from each lot and tested as specified in 4.5.2 using equipment in accordance with 4.4. 4. If four (4) or more assemblies fail to meet the specified requirement the lot shall be rejected. (Non-destructive Test, acceptable parts may be reassembled and returned to the lot.)

*4.4.3.2.2 After three (3) consecutive lots have met the criteria of 4.4.3.2.1, one hundred and twenty five (125) shall be selected and tested in accordance with 4.5.2 .- If two (2) or more assemblies fail the lot shall be rejected.

*4.4.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4,5 Test methods and procedures (See 6.5)

*4.5.1 Non-functioning of head assembly. - With all safety pins removed, the head assembly shall be subjected to a 3.0 pound minimum pull, applied at a rate of one foot, minimum, per minute to the release pin. The pull shall be parallel to the axis of the release pin. The head assembly shall be subjected to a 8.0 pound minimum pressure, applied at a rate of one foot, minimum, per minute to any one prong or equally distributed to all three prongs. The pressure shall be parallel to the axis of the "head assembly (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:17Z
Check the source to verify that this is the currentversion before use.

*4.5.2 Functioning of head assembly. - The release pin safety pin, interlocking safety pin and the striker safety pin shall be removed in that order. The sample shall be divided into two equal groups of head assemblies. One group, including the odd assembly, shall be subjected to a 12.0 pound maximum pull, applied at a rate of one foot maximum per minute to the release spring. The remaining group of' head assemblies shall be subjected to a 20.0 pound maximum pressure, applied at a rate of one foot maximum per minute to any one prong or equally distributed to all three prongs. The pressure shall be parallel to the axis of' the head assembly (see 6.5).

4.5.3 Spring embrittlement. - The springs and rings shall be pulled to the minimum point of permanent distortion by any method approved by the procuring activity. Springs and rings so tested shall be scrapped.

4.5.4 Plating thickness test. - The applicable components shall be tested for plating thickness in accordance with QQ-Z-325 for zinc plated parts and QQ-P-416 for cadmium plated parts.

4.5.5 Salt spray resistance. - The test shall be performed as specified in QQ-Z-325 for zinc plated parts and as specified in QQ-P-416 for cadmium plated parts with-the exception-that exposure shall consist of 24 hours white salts and 48 hours red rust. Parts so tested shall be scrapped or replated.

4.5.6 Plating adhesion test. - The applicable components shall be tested for plating adhesion in accordance with QQ-Z-325 for zinc plated parts and QQ-P-416 for cadmium plated parts.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C. - Head assemblies and components shall be packaged in accordance with MIL-STD-1169.

5.2 Packing

5.2.1 Level C. - Head assemblies and components shall be packed in accordance with MIL-STD-1169.

5.3 Marking. - Marking shall be in accordance with MIL-STD-1169.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:17Z
Check the source to verify that this is the current version before use.

*6.1 Intended use. - The fuze metal parts covered by this specification. are intended for assembly and use in the Ma6A2 Anit-Personnel Mine.

*6.2 Ordering data. - Procurement documents. shall specify the following:

a. Title number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

*6.3 Submission of inspection equipment designs for approval - (see MIL-A-48078) Submit equipment designs as required, to Commander Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801.

*6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

6.5 The head assembly shall be considered to have functioned if the striker is released and clears the head assembly. (Caution. - Personnel should exercise caution as the striker is ejected with considerable force.)

6.6 International Standardization Agreement. - Certain provisions, section 3 and 4,5; of this specification are the subject of international standardization agreement QSTAG-255. When amendment, revision, or cancellation of this specification is proposed the departmental custodians will inform their respective Departmental Standardization Officers so that appropriate action may be taken respecting the International agreement concerned.

6.7 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Actovoty:
Army-PA

Project Number: 1345-A-125

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:17Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:17Z
Check the source to verify that this is the current version before use.