MILITARY SPECIFICATION

PERISCOPE, M29

This amendment forms a part of Military Specification MIL-P-45107A(Ord), dated 9 November 1959.

Page 1, paragraph 2.1: Delete the following:

"CCC-C-271 Cheesecloth, Bleached and Unbleached"

Add the following in proper sequence:

"CCC-C-440 Cloth, Cotton, Cheesecloth, Bleached and Unbleached"

Page 3, paragraph 3.5.2, line 2: Delete "3.9.5 and 3.10.5" and substitute "3.7.1, 3.9.5 and 3.10.5".

Page 3: Add paragraph 3.7.1 as follows:

"3.7.1 Parallax adjustment screw torque. - The torque required to rotate the parallax adjustment screw shall not exceed 9 pound inches when subjected to the temperatures of 3.5.2."

Page 7, Table II: Add the following:

"5. Parallax adjusting screw torque	3.7.1	4.9.2.1.1	DST"

Page 12; Add paragraph 4.9.2.1.1 as follows:

"4.9.2.1.1 Torque. - The running torque required to rotate the parallax adjusting screw through the range of objective travel shall be measured with a special testing device affixed to the adjusting screw to determine compliance with the torque value specified."

Page 14, paragraph 5.3.1.1.1.1: Delete "CCC-C-271" and substitute "CCC-C-440".

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:22Z
Check the source to verify that this is the current version before use.

Page 15, paragraph 5.3.1.4.1: Delete and substitute the following:

"5.3.1.4.1 Immobilizing and wrapping the wedge coupling. - A flat steel spring shall be placed between the stop and the end surfaces of the wedge coupling to prevent movement of the coupling. The size of the spring shall not extend beyond the surfaces of the coupling in such a manner that it would damage the water-vaporproof bag specified in 5.3.1.4.4. The preservative coated surfaces of the wedge shall be wrapped with greaseproofed barrier material conforming to type II, grade A, class 2 of Specification MIL-B-121. The barrier material shall be secured in place with pressure-sensitive tape conforming to type I or II of Specification UU-T-106. A tag, specified in 5.5.1, shall be attached to the wrapped coupling."

Page 16, paragraph 5.3.1.4.6: Delete the last sentence and substitute the following:

"The fiberboard box shall be closed with two strips of 2 inch wide pressure-sensitive tape conforming to Specification PPP-T-76. The tape shall be applied over the top and bottom seams and extend at least 3 inches onto each end panel."

Page 16, paragraph 5.3.2.2: Delete "described" and substitute "specified".

Page 16, paragraph 5.3.2.2c: Delete the last sentence and substitute "The box shall be closed as specified in 5.3.1.4.6, except that 2 inch wide gummed tape conforming to the gummed tape specified in 5.3.1.4.3 shall be used."

Page 17, paragraph 5.5.1: Add the following sentence: "The tag to be attached to the wrapped coupling, specified in 5.3.1.4.1, shall contain the following: DO NOT REMOVE FLAT STEEL SPRING IMMOBILIZING COUPLING UNTIL THE PERISCOPE IS PLACED IN TANK."

Page 17, paragraph 5.5.2: Delete the second sentence and substitute "If the serial numbers of the periscopes in a Level A or B shipping container are in consecutive order, the serial numbers shall be indicated as specified in Standard MIL-STD-129. If the serial numbers are not in consecutive order, they shall be indicated on packing lists."

Custodian:

Army - Ordnance Corps

Preparing Activity:

Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:22Z
Check the source to verify that this is the current version before use.