MIL-T-45093A (MU)
28 December 1962
SUPERSEDING
MIL-T-45093 (Ord)
12 June 1958

MILITARY SPECIFICATION

TELESCOPES, ARTICULATED: M102 AND M102C

1. SCOPE

1.1 This specification covers articulated telescopes M102 and M102C, hereinafter referred to as telescopes. These telescopes are similar except for differences in reticle patterns. (see 6.1)

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-O-13830	Optical Components of Fire Control Instruments: General Specification Governing the Manufacture and Inspection of
MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel; Packaging of
MIL-I-45208	Inspection Requirements, General Specification for
MIL-I-45607	Inspection Equipment, Supply and Maintenance for Ordnance

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking of U. S. Military Property

DRAWINGS

Munitions Command

F8603000	Telescopes: M102 and M102C
LSQAP-8603000	List of Supplementary Quality Assurance Provisions for Telescopes M102 and 102C
IEL 8603000	Inspection Equipment List for Telescopes M102 and M102C.

PACKAGING DATA SHEET

MIL-P-14232/P8603000	Packaging of Telescopes M102 and M102C

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Initial production sample. - Unless otherwise directed by the contracting officer, an initial production sample shall be required. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production.

3.2 Materials. - Materials shall be in accordance with drawings, material specifications and general specifications forming a part of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

3.3 Fabrication. - The telescope shall be manufactured in accordance with the drawings, applicable to the model telescope specified in the contract or order and drawings pertaining thereto. The requirements of this specification are detailed only to the extent considered necessary to obtain the desired optical and mechanical characteristics, performance and permanence to insure inherent quality and performance capabilities.

3.4 General specifications. - The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specifications MIL-O-13830 and MIL-F-13926.

3.4.1 MIL-O-13830

(a) Cleanliness

(b) Illuminated reticle

3.4.2 MIL-F-13926

(a) Order of precedence

(b) Protective finished surfaces

(c) Special accuracy

(d) Finish, painting and protective

(e) Workmanship

3.5 Environmental

3.5.1 Storage temperatures. - The telescope shall show no evidence of physical failure and shall meet all requirements of this specification at standard ambient temperature (plus 60 to 90 degrees Fahrenheit) after having been exposed and thermally stabilized at ambient temperatures of plus 160 and minus 80 degrees Fahrenheit.

3.5.2 Operating temperatures. - The telescope shall meet the applicable requirements of 3.9 while exposed to, and thermally stabilized at ambient temperatures of plus 150 degrees and minus 40 degrees Fahrenheit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

3.5.3 Vibration. - The telescope shall be vibrated at a constant frequency of 30 cycles per second with an amplitude of 1/16 inch (1/8 inch maximum excursion) for a period of 5 minutes plus or minus 15 seconds. Subsequent to vibration the telescope shall show no evidence of loose or damaged parts and shall meet all requirements of this specification.

3.5.3.1 Post environmental collimation. - Subsequent to vibration the telescope shall meet the requirements of 3.8.1 and 3.8.2.

3.6 Cleanliness. - Subsequent to vibration the telescope shall meet the cleanliness requirements of Specification MIL-O-13830 and there shall be no more than five particles of dirt visible on the reticle and the area of each particle shall not be in excess of the area equivalent to a size five dig. There shall be no other dirt within the telescope which interferes with observation or adversely affects image quality.

3.7 Sealing. - The telescope shall show no evidence of leakage when subjected to an internal pressure of dry nitrogen at 5 psig for five minutes. The interior atmosphere of the accepted telescope shall contain nitrogen having a dew-point at least as low as minus 25 degrees Fahrenheit at a pressure of between 0.1 and 0.25 psig.

3.8 Accuracy.

3.8.1 Collimation. - The telescope shall be mounted on the spherical surfaces of the mounting bearings of the objective tube with the locating pin in a vertical, downward position, and the eyepiece elevated at least 4 degrees. The center of the boresight across of the AP-T,M358 (M102) or HEAT-T, 469 (M102C) reticle shall be 6.4 mils plus or minus 0.5 mil above the geometric axis and shall coincide within 0.5 mil of a plumb line passing through the geometric axis.

3.8.2 Reticle coincidence. - The line of sight through the boresight cross of the HE-T, M 356 reticle shall coincide with the aiming point through the boresight cross of the AP-T, M358 (M102) or HEAT-T, 469 (M102C) reticle within a maximum separation of 0.07 mil.

3.8.3 Parallax. - Parallax at the center of the field shall not exceed 0.05 mil when viewing a target between 500 and 1500 meters.

3.8.4 Resolution. - The resolving power on the optical axis shall be 8.0 seconds of arc or less.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

3.8.5 Parallelism of reticle and image. - With the telescope locating pin vertical (downward) the longest horizontal line of each reticle (60 mil line) shall be parallel to the image of the horizontal target line within 11.5 minutes of arc (11.5 minutes of arc is equivalent to an angle subtended by a 0.2 mil block at one extremity of the reticle line when the other extremity of the reticle line is in coincidence with the image of the horizontal target line).

3.8.6 Image tilt. - The image of a vertical target shall be vertical within one degree at any position of articulation. (One degree tilt is equivalent to the angle subtended by 2 mils at the edge of the field when measured across the full field of view.)

3.8.7 Reticle lean. - The angular rotation of the reticle with respect to a reference in an auxiliary telescope secured to the eyepiece shall not exceed one degree when the telescope is articulated through its full range.

3.8.8 Reticle wander. - The image of the reticle boresight mark shall not deviate by more than one degree from a fixed reference in an auxiliary telescope secured to the eyepiece of the telescope when the telescope is articulated through its full range.

3.8.9 Reticle accuracy. - The angular value for the graduations of the reticles between the zero and maximum range marks shall be as indicated on the reticle drawings within 0.3 mil.

3.8.10 Eyepiece focus. - Eyepiece focus shall be adjustable over the range of plus and minus four diopters as read on the eyepiece scale. The zero setting of the diopter scale shall indicate zero diopter within 0.25 diopter.

3.9 Operability.

3.9.1 Diopter adjustment. - The torque required to rotate the diopter adjustment shall not exceed 8 pound inches at standard ambient temperature. The torque value obtained at extreme temperatures of 3.5.2 shall not exceed the value recorded at standard ambient temperature by more than 7 pound inches.

3.9.2 Reticle shift mechanism. - The reticle shift mechanism shall be operable and firmly seat against the stops when checked at extreme temperatures of 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

3.9.3 Articulating movement. - With the telescope on its side (the locating pin horizontal), the force to move the objective tube through a full travel when rotated from the hanger bracket assembly about the articulated joint shall not exceed 25 pounds at standard ambient temperature. The force value obtained at extreme temperatures of 3.5.2 shall not exceed the value recorded at standard ambient temperature by more than 20 pounds.

3.10 Illumination. - The reticle markings on each reticle, when in the focal plane, shall appear clearly defined when illuminated by Instrument Light M50 or equivalent, while observed in a darkened area.

3.11 Identification marking. - Identification marking, unless otherwise specified shall be in accordance with Standard MIL-STD-130.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 General requirements. - Inspection requirements and procedures shall be in accordance with Specification MIL-I-45208.

4.3 Initial production sample. - Prior to production, the contractor shall submit the initial production sample in accordance with 3.1 for inspection by the contractor under the surveillance of the Government. This inspection shall be conducted at the contractor's facility, or Government approved laboratory, using test equipment authorized for use on the contract. The sample shall be inspected for all requirements of this specification by utilizing examination and testing methods prescribed herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.3.1 Initial production sample failure. - Should the production sample fail to pass the prescribed tests, the contractor shall cease those operations which are causing the rejection and shall make the necessary corrections. When corrections in the process have been made, a new production sample shall be examined and tested by the contractor under the surveillance of the Government. Acceptance of production lots will not commence until an acceptable production sample is submitted and corrective actions have been taken to eliminate deficiencies.

4.4 Lot formation. - Inspection lot sizes and lot formation shall be in accordance with Standard MIL-STD-105.

4.4.1 Defective units and lots. - Defective units and lots shall be processed as specified in Standard MIL-STD-105.

4.5 Material. - Control of material shall be in accordance with test data requirements of Specification MIL-I-45208.

4.6 Inspection of components. - Inspection requirements for component parts and subassemblies are contained herein and on Supplementary Quality Assurance Provisions (SQAP) listed in Supplementary Quality Assurance Provisions List (LSQAP)-8603000.

4.6.1 Contents of SQAP. - The contents of SQAP shall represent the minimum inspection requirements and shall be the basis for acceptance or rejection by lot of each component covered by a SQAP. The Government reserves the right, however, to inspect for the requirements of all drawings and specifications and to reject individual non-conforming items.

4.6.2 Contractor's inspection for all components not covered by SQAP. - Inspection for these components shall be in accordance with the inspection procedures of the inspection system required by Specification MIL-I-45208. The system shall include procedures for checking all positional and functional characteristics shown on the drawings which indicate precision requirements and have a bearing on the functional accuracy and performance of the telescope.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.7 Inspection equipment. - Inspection equipment shall conform to drawings listed in IEL 8603000, except as provided for under the alternative inspection procedures and inspection equipment requirements of Specification MIL-I-45208. Provisions of Specification MIL-I-45607 shall apply to test equipment provided by the Government or provided by the contractor and utilized in the Government approved inspection system. The Government reserves the right to use all approved test equipment, both Government furnished and contractor acquired, for verification inspection.

4.7.1 Accuracy requirements. - Inspection equipment which incorporates features for measuring values or sizes established by product requirements shall be capable of measuring those values within an accuracy of ten percent of the specified tolerance except as specified in 4.7.2. In cases where the ten percent accuracy imposes impractical or very difficult design and fabrication problems, or results in a test equipment cost factor which is exorbitant in relation to the cost and application of the product to be inspected, the Government shall be expeditiously advised in order that necessary appropriate action can be taken.

4.7.2 Inspection equipment design requirements.

4.7.2.1 Equipment to test collimation, parallax, resolution, image lean, and reticle accuracy. - The device shall be equipped with a suitable means to permit adjustment of the device to insure that the locating surfaces of the locating pin keyway are plumb within one minute ($0^{o}1'$). The device shall receive the telescope so that the spherical mounting surfaces of the objective tube are secured firmly in a horizontal plane in such a manner to insure complete immobilization of the objective tube assembly with the locating pin positioned in the locating pin keyway and the end of the objective tube assembly toward the appropriate target used for measuring the AP-TM358, HE-TM356 and HEAT-T,496 Reticle Patterns.

4.7.2.2 Equipment to test angular movement. - The device shall permit full range of articulation of the telescope eyepiece with a minimum amount of effort, in both upward and downward excursion, with an auxiliary telescope secured firmly to the telescope eyepiece. A reticle with a cross-lined type pattern, the lines of which shall not exceed .0010 inch width and angular tolerance shall not exceed six minutes ($0^{o}6'$), shall be incorporated in the auxiliary telescope. Provisions shall be made to permit adjustment of the auxiliary telescope for plumb within six minutes ($0^{o}6'$) when secured to the telescope eyepiece. The auxiliary telescope shall be utilized for testing image wander and image lean requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.7.2.3 Repeatability of test equipment. - The device shall be equipped with appropriate limit stops and/or reference points which will permit repeatability of the initial setting using the telescope boresight cross as a reference in coincidence with markings on the appropriate target used for measuring the reticle patterns. The total allowable shift shall not exceed .05 mil when the telescope is removed and replaced in the device three consecutive times.

4.7.2.4 Accuracy of targets. - An appropriate target to be utilized for measuring the AP-TM358, HE-TM356 and HEAT-T,469 Reticle Patterns with acceptance and rejection limitation markings or pips marked thereon, the angular tolerance of which shall not exceed twenty seconds ($0^{o}0'20"$), shall be provided. The target shall be utilized for testing collimation, parallax, resolution and reticle accuracy.

4.7.2.5 Operability of test equipment. - Rigidity, stability, ease of maintenance and adaptability of set-up and/or calibration equipment with complete provisions are prime requirements. All special set-up and/or calibration equipment necessary for certification of device accuracy shall be furnished and will become a part of the device.

4.7.2.6 Equipment to test vibration requirements. - The device shall be a type capable of producing vertical motion at a constant frequency of 30 cycles per second with an amplitude of 1/16 inches (1/8 inch maximum excursion). This device shall be equipped with an adapter which will permit the mounting of the telescope to the adapter in a normal operating position. The base of the adapter shall be secured firmly to the device.

4.7.2.7 Equipment to test torque requirements. - A torque wrench type tester with a minimum range of from zero to twenty pound inches, the accuracy of which shall be plus or minus one-quarter pound inch throughout the entire zone of excursion, shall be utilized. This device shall be equipped with an adapter to accommodate testing of the diopter adjustment.

4.7.2.8 Equipment to test tube articulation force. - A pull type scale with a minimum range of from zero to sixty pounds shall be utilized, the accuracy of which shall be plus or minus one-quarter pound throughout the entire zone of excursion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.8 Acceptance inspection.

4.8.1 Classification of defects. - The classification of defects in Tables I and II shall constitute the minimum inspection requirements to be performed prior to acceptance or rejection by lots. The AQL specified pertains to each individual characteristic.

4.8.1.1 Disposition of rejected lots. - Rejected lots shall be screened for all defective characteristics. After corrections have been made and the Government inspector informed of the corrective action taken, the lots shall be resubmitted for acceptance as outlined in Standard MIL-STD-105.

Table I

Classification of Defects

Use Inspection Level L7 in Table IIIB with Sampling Plan Table IVA of Standard MIL-STD-105.

Critical: None defined.

Major: AQL 4.0 Percent Defective	Req't Par.	Q.A. Par.	Test Method
101. * Diopter adjustment torque, excessive	3.9.1	4.9.6.12	Special Test Equip.(STE)
102. * Reticle shift mechanism operating improperly	3.9.2	4.9.6.12	STE
103. * Articulating force excessive	3.9.3	4.9.6.12	STE
104. Improper sealing	3.7	4.9.5	Standard Meas. Equip.(SME)
105. Improper collimation, post environmental	3.5.3.1	4.9.6.3	STE

Minor: None defined.

* NOTE: The above tests shall be performed while the telescope is stabilized at ambient temperatures of minus 40 degrees and plus 150 degrees Fahrenheit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

Table II

Classification of Defects

Use Inspection Level II in Table IIIA with Sampling Plan Table IVA of Standard MIL-STD-105

Critical: None defined.

Major: AQL 1.0 Percent Defective		Req't Par.	Q.A. Par.	Test Method
101.	Physical failure, post vibration	3.5.3	4.9.3.1	STE
102.	Uncleanliness	3.6	4.9.4	Visual (VIS.)
103.	Improper collimation	3.8.1	4.9.6.1	STE
104.	Reticle not in coincidence	3.8.2	4.9.6.2	STE
105.	Excessive parallax	3.8.3	4.9.6.4	STE
106.	Insufficient resolution	3.8.4	4.9.6.5	STE
107.	Image and reticle not parallel	3.8.5	4.9.6.6	STE
108.	Excessive image tilt	3.8.6	4.9.6.7	STE
109.	Excessive reticle lean	3.8.7	4.9.6.8	STE
110.	Excessive reticle wander	3.8.8	4.9.6.9	STE
111.	Insufficient reticle accuracy	3.8.9	4.9.6.10	STE
112.	Eyepiece focus excessive	3.8.10	4.9.6.11	SME
113.	Diopter adjustment torque excessive	3.9.1	4.9.6.12	STE
114.	Articulating force movement excessive	3.9.3	4.9.6.12	STE
115.	Incorrect reticle illumination	3.10	4.9.6.13	Vis.
116.	Incorrect identification marking	3.11	4.10	Vis.

Minor: None defined.

NOTE: The above tests shall be performed at standard ambient temperatures (plus 60 degrees to plus 90 degrees Fahrenheit).

4.9 Test methods and procedures.

4.9.1 Storage temperatures. - This test shall be conducted in accordance with Procedure II of Specification MIL-F-13926 to the conditions specified. Upon return to standard ambient temperature, the telescope shall be visually inspected for damage and then subjected to all the tests of this specification. This test shall be performed on the initial production sample only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.9.2 Operating temperatures. - This test shall be conducted in accordance with Procedure I of Specification MIL-F-13926 to the conditions specified. The telescope shall then be subjected to the tests of 4.9.6.12 while thermally stabilized at the ambient temperatures as specified in 3.5.2.

4.9.3 Vibration. - Each telescope in the sample shall be mounted on special test equipment and vibrated in accordance with the requirements of 3.5.3.

4.9.3.1 Physical failure, post vibration. - Subsequent to vibration the telescope shall be subjected to a visual and tactile examination to determine damage such as loose, bent or broken parts.

4.9.4 Cleanliness. - This test shall be conducted in accordance with Specification MIL-O-13830. There shall be no visible evidence of moisture on the internal optical surfaces of the telescope. Dirt particles shall not exceed the size specified in 3.6.

4.9.5 Sealing. - The telescope shall be subjected to the internal pressure as specified in 3.7. During the required time period, the telescope shall show no leakage. It shall then be flushed with dry nitrogen. The flushing shall continue until the gas bled from the telescope has a dew-point at least as low as specified in 3.7.

4.9.6 Accuracy.

4.9.6.1 Collimation. - The telescope shall be correctly mounted upon special testing equipment and accurately collimated in conformance with the requirements of 3.8.1.

4.9.6.2 Reticle coincidence. - Reticle coincidence shall be checked observing the alinement of the boresight cross of the HE-TM 356 reticle to be in coincidence with the aiming point through the boresight cross of the AP-TM 358 (M102) or HEAT-T,469 (M102C) reticle in compliance with 3.8.2.

4.9.6.3 Post environmental collimation. - Subsequent to the requirements of 3.5, the telescope shall be rechecked for compliance with the requirements of 3.5.3.1.

4.9.6.4 Parallax. - To determine conformance to 3.8.3 parallax shall be measured at the optical axis of the telescope by viewing a target at between 500 and 1500 meters. Any movement of the observer's head shall not cause the boresight mark to displace more than the tolerance specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.9.6.5 Resolution. - To determine conformance to 3.8.4, resolution on the optical axis shall be measured as specified for assembled optical systems in Specification MIL-O-13830 and shall conform to the requirements. The parallel bar patterns of the test target shall be clearly defined in all four meridians.

4.9.6.6 Parallelism of reticle and image. - To determine conformance to 3.8.5 parallelism of reticle and image shall be tested by positioning the telescope as specified and observing the position of each 60 mil reticle line in relation to its appropriate target. Each reticle shall conform to the tolerances specified.

4.9.6.7 Image tilt. - To determine conformance to 3.8.6, image tilt shall be tested similar to 4.9.6.8. The image of a vertical target shall conform to the requirements specified.

4.9.6.8 Reticle lean. - To determine conformance to 3.8.7, reticle lean shall be tested by observing the angular rotation of the reticles while articulating the telescope through its full range of travel. The angular rotation shall be as specified.

4.9.6.9 Reticle wander. - To determine conformance to 3.8.8, reticle wander shall be tested by observing the image of each reticle boresight mark while articulating the telescope through its range of travel. The image shall not deviate beyond the tolerance specified.

4.9.6.10 Reticle accuracy. - To determine conformance to 3.8.9, the accuracy of the reticles shall be observed between the zero and maximum range marks and shall conform to the requirements specified.

4.9.6.11 Eyepiece focus. - To determine conformance to 3.8.10, eyepiece focus shall be checked with the aid of a dioptometer. The eyepiece of the dioptometer shall be adjusted for best focus of the dioptometer reticle with the diopter scale set at zero. The telescope reticle, at the center of the field, shall be in sharp focus within the limits specified as measured on the diopter scale of the dioptometer.

4.9.6.12 Diopter adjustment torque and articulation force. - To determine conformance to 3.9.1, 3.9.2, and 3.9.3, diopter adjustment torque and articulation force shall be measured with the test equipment specified in 4.7.2.7 and 4.7.2.8 and shall conform to the requirements at the temperatures specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

4.9.6.13 Illumination of reticle. - To determine conformance to 3.10, illumination shall be tested as specified in Specification MIL-O-13830. The markings shall be clearly defined as specified.

4.10 Identification marking. - Identification marking, unless otherwise specified, shall be visually examined to determine conformance to Standard MIL-STD-130.

4.11 Quality assurance provisions for packaging, packing and marking. - Packaging, packing, and marking shall be in accordance with Specification MIL-P-14232.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. - Packaging, packing and marking shall be in accordance with Specification MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P-8503000. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. - These telescopes are intended for use in the 120MM Gun, Heavy Tank M103 and M103A1 as a component of the secondary direct fire control system. The Telescope M102 employs a reticle calibrated in yards and is inscribed for Ammunition, HE-T, M356 and AP-T,M358. The Telescope M102C employs a reticle calibrated in meters and is inscribed for HE-T, M356 and HEAT-T,469 ammunition. The reticles for either instrument may be shifted into the focal plane. These telescopes employ a complex optical system of 8-power magnification with a 7.5 degree field of view. The telescopes are designed with an articulating joint approximately midway between the objective and eyepiece to permit the objective tube of the telescope to elevate with the gun while the eyepiece movement is approximately stationary.

6.2 Ordering data. - Procuring documents should specify the following:

(a) Title, number and date of this specification.

(b) Selection of an applicable level of preservation, packaging and packing.

(c) Applicable stock number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.

(d) Provisions for initial production sample including dates of delivery (see 3.1)

6.3 Definitions.

6.3.1 Standard measuring equipment (SME). - Common hand type measuring devices and standard gages which are usually stocked by commercial supply houses for ready supply (shelf items) and which are normally used by the inspector to perform dimensional inspection. This category also includes commercial testing equipment such as meters, optical comparators, etc.

6.3.2 Special test equipment (STE). - Special Testing Equipment is defined as special inspection fixtures, instruments and modified standard measuring equipment. Appearance of STE in the classification of defects does not imply that the equipment is currently in existance.

6.4 Design information. - Information regarding specific design not covered or referenced by this specification may be obtained from the procuring activity upon specific request of the contractor.

NOTICE: When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No 1240-A119Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:21Z
Check the source to verify that this is the current version before use.