MIL-W-45087A
23 JUNE 1961
SUPERSEDING
MIL-W-45087(Cm1C)
5 JUNE 1958

MILITARY SPECIFICATION

WARHEAD, 5 INCH ROCKET, GAS, GB, MK 40 MOD 0; FILLING ASSEMBLY

This specification has been approved by the Department of Defense and is mandatory for use by the Department of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers the isopropyl methylphosphonofluoridate (GB) filling and assembling of the Mk 40 Mod 0 rocket warhead without explosive components.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-C-10758 — Chemical Agent, Isopropyl Methylphosphonofluoridate (Fluoroisopropoxymethylphosphine Oxide).

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 — Marking for Shipment and Storage.

DRAWINGS

DEPARTMENT OF THE NAVY—BUREAU OF NAVAL WEAPONS

289026 — Warhead, 5-Inch Rocket, Gas, Mk 40 Mod 0—List of Drawings, Subassemblies and Parts (3 Sheets).

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:20Z
Check the source to verify that this is the current version before use.

2.2 **Other publications.** The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71–90 — Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Interstate Commerce Commission regulations are a part of the Code of Federal Regulations (Revised 1956) available from the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Orders for the above publication should cite "49 CFR 71–90 (Rev. 1956).")

3. REQUIREMENTS

3.1 **Materials and components.** The supplier shall ascertain prior to their use that all materials and components have met their respective specifications.

3.2 **Rust prevention of components.** The rust preservative of the warhead applied for protection for storage and transportation shall not be removed until just prior to filling.

3.3 **Filling level.** The height of GB, conforming to Specification MIL–C–10758 (see 6.2 and 6.3), shall be within the limits shown in table I when examined as specified in 4.6.3.

TABLE I. *Filling level*

Temperature range °F.	Level of liquid below top of burster well in inches	
	Minimum	Maximum
40 to 50	4.06	4.93
50 to 60	4.00	4.87
60 to 70	3.94	4.81
70 to 80	3.86	4.75
80 to 90	3.79	4.69
90 to 100	3.73	4.63

Calibration factors:

10.0 percent void at 40° F. in minimum warhead.

Expansion factor for GB = 0.00057 ml/°F/ml of agent.

3.4 **Closing.** The warhead shall be closed as shown on Drawing 1380990, which is listed on Drawing 289026. From the time of filling until completion of test specified in 4.6.2, the warhead shall be kept in a nose-up position (see 6.3).

3.5 **Agent decontamination.** The exposed surfaces of the warhead shall be free from GB contamination (see 4.6.1 and 6.4).

3.6 **Helium leakage.** The warhead shall not leak helium through the closure at a rate greater than 1×10^{-6} atmospheric cubic centimeter (cc) per second when tested as specified in 4.6.2.

3.7 **Workmanship.** The warhead shall be free from damage which could affect subsequent assembly and functioning.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Supplier's responsibility.** The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *Joint responsibility.* Tests prescribed by 4.6 will be performed jointy by the Government and the supplier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:20Z
Check the source to verify that this is the current version before use.

4.2 Special provisions.

4.2.1 *Alternative inspection (including testing) procedures.* The supplier may utilize any alternative inspection procedure which will insure equal or better quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.1.1 *Filling level.* When an alternative procedure is approved for use in determining the filling level, the procedure shall be monitored in accordance with 4.6.3 to insure the requirements of this specification are satisfied.

4.2.2 *Supplemental evidence.* The supplier shall provide evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 have been satisfied.

4.3 Lotting. A lot shall consist of the warheads filled and assembled by one manufacturer, at one plant, using the same materials, under essentially the same filling conditions. However, no more than one lot of agent, one lot of metal parts as identified by one manufacturer, and one metal part interfix number shall be represented in any one lot of filled warhead. For ballistic considerations a sublot shall consist of the warheads having the same zone designation (see 5.1).

4.4 Sampling. Sampling shall be conducted in accordance with Standard MIL-STD-105.

4.5 Examination. Sample warheads and level A preparation for delivery thereof shall be examined in accordance with the classification of defects and Standard MIL-STD-105.

4.5.1 *Classification of defects.*

4.5.1.1 *Warhead, gas, 5-inch rocket, Mk 40 Mod 0—GB filling assemby and marking diagram* (Wwg 1380990).

Categories	*Defects*	*Acceptance standards*
**Critical:*		
1	Contamination.	4.6.1
2	Helium leakage.	4.6.2
3	Filling excessive.	4.6.3
Major—AQL 1.0 percent defective.		
101	Component missing or incorrectly assembled.	
**102	Burster well thread damaged.	
103	Damage (base threads).	
104	Marking incorrect.	
105	Burster well not seated on forward face of warhead body.	

* Each warhead in the lot shall be examined for these defects.

** Check prior to insertion of burster well.

Categories	*Defects*	*Acceptance standards*
Minor—AQL 2.5 percent defective.		
201	Filling insufficient.	4.6.3
202	Marking missing or illegible.	
203	Protective finishes missing or incorrect.	
204	Contamination (other than agent).	
205	Threads protective coating missing or inadequate.	

4.5.1.2 *Preparation for delivery* (sec. 5).

Categories	*Defects*
Critical:	None defined.
Major—AQL 4.0 percent defective.	
101	Pallet incorrect.
102	Quantity per pallet incorrect.
103	Strapping incorrect.
104	Damage (pallet wracked or broken).
105	Marking incorrect, missing, or illegible.

4.6 Tests.

4.6.1 *GB decontamination.* Contamination shall be determined by the use of an approved Chemical Corps GB agent detector system.

4.6.2 *Helium leakage.* Prior to closing, the void above the agent shall be evacuated to a pressure not greater than 7.5 pounds per square inch absolute (psia) and filled with helium to a pressure of 22 psia to insure a partial pressure due to helium of not less

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:20Z
Check the source to verify that this is the current version before use.

than 15 pounds per square inch gage (psig) after closing. The closure area shall be sealed off by a test head manifolded to a vacuum system and a mass spectrometer-type helium leak detector. The test head shall be evacuated to and maintained at a pressure lower than 20 microns of mercury during the test. The leak detector shall be calibrated to respond to a leak of 1 x 10—^{6} atmospheric cc per second of helium at the test head when a standard leak is introduced into the system at that point.

4.6.3 *Filling level.* The height of the GB in the filled warhead shall be located radiographically with the warhead oriented in a vertical, nose-up position.

5. PREPARATION FOR DELIVERY

5.1 Packing, level A. The filled and closed warheads shall be packed for shipment or storage on the same pallets as the empty warheads were received. The pack shall comply with the Interstate Commerce Commission regulations and the warheads shall be segregated by zone before shipment.

5.2 Marking. In addition to any special marking required by the contract or order, palletized shipments shall be marked in accordance with Standard MIL–STD–129 and Interstate Commerce Commission regulations.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number, and date of this specification.

6.2 Filling level. When filled as specified in 3.3, the warhead carries approximately 5 pounds of GB. This information is furnished as an aid to procurement and not as a criterion for filling.

6.3 Precautions. Because of the hazards attending the filing of munitions with GB, suppliers are advised to exercise all necessary precautions to protect personnel from injury during filling and handling. Care should be taken to prevent wetting the closure with agent thereby making void the results of the helium test.

6.4 Decontamination. Decontamination can be accomplished by subjecting the warhead to a spray of decontaminating solution (5- to 10-percent commercial grade soda ash, Na_2C0_3) for a minimum period of 1 minute at a minimum pressure of 15 psig in such a manner as to completely wash all surfaces. The warheads should then be rinsed with water to remove all traces of the decontaminating solution. The temperature of the spray and rinse water should be maintained at a range of 140° to 160° F. Spray pressures should have gages with an accuracy of 1 psig. An approved procedure of control of the decontaminating solution strength should be maintained by periodic examination and the time the warhead is subjected to the spray should be automatically controlled and recorded.

6.5 Safety classification. This item is chemical group A (special), explosive hazard class 11 (Chemical Corps Safety Directive No. 385–10).

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:

Army—Cm1C
Navy—Wep

Preparing activity:
Army—Cm1C

☆ U. S. GOVERNMENT PRINTING OFFICE: 611045—1961—(463)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973—714-866/3983 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:20Z
Check the source to verify that this is the current version before use.