MILITARY SPECIFICATION

BRACKET, M21 REEFING LINE CUTTER,

CARGO PARACHUTE CANOPY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size of reefing line cutter bracket.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

* PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

DRAWINGS

U.S. AIR FORCE

64D22262 - Bracket, M21 Reefing Line Cutter, Cargo Parachute Canopy

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2), the contractor shall furnish sample unit(s) for the first article inspection and approval (see 4.3, 6.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

3.2 Materials and construction. The materials, construction and supplementary processes involved in the fabrication of the cutter bracket shall conform to the requirements specified or shown on Drawing 64D22262 (see 6.5).

3.3 Workmanship. The workmanship shall conform to the quality established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3)
2. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for defects in table I and for compliance with dimensions specified. The presence of any defects listed in table I or any dimensions not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 End item inspection. The inspection lot for visual and dimensional examination shall consist of all brackets offered for inspection at one time. The sample unit shall be one bracket.

* 4.4.2.1 Visual examination. An examination shall be made of the brackets for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish anodic coating	Not finished as specified		X
	Coating is flaking or otherwise not adherent	X	
	Coating not uniform, or smooth		X
	Dirt, smudge, oil, grease, or other foreign matter		X
	Any breaks, scratches, or tool marks thru coating to metal		X
Design	Any departure from design indicated on drawing not otherwise specified herein	X	
Construction workmanship	Cracked, fractured, malformed, or otherwise damaged	X	
	Any sharp edges, burrs, or metal slivers	X	
Identification marking	Missing, incomplete, not legible, not permanently idented or not as specified		X

* 4.4.2.2 Dimensional examination. An examination shall be made of the brackets to determine compliance with dimensions specified. Any dimensions not meeting specified requirements shall be a defect. The inspection level shall be S-4 with an AQL of 4.0, expressed in terms of defects per hundred units.

* 4.4.3 Inspection of packaging. An examination shall be made to determine that preservation-packaging, packing, and marking as required by section 5 are complied with. Defects shall be as indicated in table II. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The inspection level shall be S-2 with an AQL of 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of packaging

Examine	Defects
Markings (interior and exterior container)	Omitted; incorrect; illegible; improper size, location, or method of application.
Materials	Component missing, damaged or defective.
Workmanship	Contents not compact in containers, incomplete closure of container flaps, bulging or distortion of containers.
Contents (interior and exterior containers)	Number per container not as specified.

* 4.4.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the appendix of PPP-B-636.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or Commercial, as specified (see 6.2).

* 5.1.1 Level A. One hundred brackets shall be packaged in a snug-fitting fiberboard box conforming to style RSC, grade W6c, of PPP-B-636. The box shall be agitated during filling to assure a compact and well-filled box. Each box shall be closed and waterproofed with tape in accordance with the appendix of the box specification.

* 5.1.2 Commercial. Brackets shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

* 5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Six hundred brackets, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636; or overseas type, style A or I, grade A or B, type 2 load of PPP-B-601, as specified (see 6.2). Each shipping container shall be closed and reinforced in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B packing. Six hundred brackets, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

* 5.2.3 Commercial packing. Brackets, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

* 6.1 Intended use. The M21 reefing line cutter bracket covered by this specification is intended to be used with the G-11A and G-11B cargo parachute canopy to hold the M21 reefing line cutter.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
* (b) When a first article is required (see 3.1, 4.2.1 and 6.3).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
* (d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample. The first article should consist of one unit. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

* 6.4 Contract data requirements. Any items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification, (see 3.2).

* 6.6 Changes from previous issue. The margins of this specifications have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - AS

Review activity:

Army - AV

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 1670-0604

☆ U. S. GOVERNMENT PRINTING OFFICE: 1977-703-122/6653

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-43119B - Bracket, M21 Reefing Line Cutter, Cargo Parachute Canopy

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:44Z
Check the source to verify that this is the current version before use.