INCH - POUND

MIL-DTL-43098/40
03 September 2019

DETAIL SPECIFICATION SHEET

MEDALLION, LIEUTENANT GENERAL ANDREW T. MCNAMARA ICON AWARD,
DEFENSE LOGISTIC AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-43098.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Epoxy, Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finished Chip Number 4.

DIMENSIONS:
DIAMETER: 3 inches (REF)
THICKNESS (At outer rim): 0.245 inch ± 0.010 inch

DECOPRATION CASE: The decoration set shall consist of a medallion and lapel button packaged in a presentation case conforming to MIL-C-14633, Type XV, Style 3 with a custom pad to be produced as part of the development. The following shall be inscribed on top of the presentation case using four lines: (line 1) Defense Logistics (line 2) Agency (line 3) LTG Andrew T. (line 4) McNamara Icon Award.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:41Z
Check the source to verify that this is the current version before use.

EPOXY (Obverse only): Epoxy shall be applied to the medallion as indicated above and as specified below, and shall match TIOH Hard Enamel Color Chip Number listed.

TIOH HARD ENAMEL COLOR CHIP NUMBER	LOCATIONS
Red #1	Alternating strips starting with 2nd stripe
White #28	Alternating strips starting with 1st stripe, eagle head and feathers
Blue #18	Chief (Top) of shield
Transparent Brown #25	Eagle wings and body
Blue #30	Background behind eagle

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished obverse hub or die.

2. Obverse the outside rim will have no inner/outer wall as it will be a jagged edge all the way around. The background behind the letters will be recessed and the letter shall be the same height as the rim. On the inside rim, all the circles shall be domed shaped. The rim in which the circles are on shall be recessed slightly so that top of the domed circles reach the same height as the letters and outer rim. The background behind the bust/image shall be recessed. The bust of Mr. McNamara shall be modeled with medium to high relief. On the uniform, we really want to see relief/clarity with the stars and US Insignia.

3. Reverse the entire background internal to the outer rim shall be recessed. The letters shall be raised to meet the same height as the outer rim. The nine circles shall be recessed with the contents inside each circle to be modeled. On the center image, the scroll will be raised and the letters on the scroll will be raised. The stars will be flush and will be the same height as the scroll. The flag rim and the rim around eagle will have the same height as the stars. The colors of the epoxy will be listed below. If you are able to put a dike line around the beak, try and do so without making the dike line so thick that it takes away from eagle itself. If this cannot be accomplished, flush metal for the beak will be accepted.

4. This item is not authorized for commercial sale, and may be produced only under Government contract and at the request of the Defense Logistics Agency.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-2019-345)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:41Z
Check the source to verify that this is the current version before use.