MIL-D-17762B(SHIPS)
AMENDMENT-2
3 July 1967
SUPERSEDING 1/
Amendment-1
1 February 1966

MILITARY SPECIFICATION

DAVITS AND WINCHES, BOAT

POWER OPERATED

This amendment forms a part of Military Specification MIL-D-17762B(SHIPS) dated 2 August 1965.

Page 1, paragraph 2.1, SPECIFICATIONS, MILITARY: Delete "MIL-D-963" and substitute "MIL-D-1000/2 - Drawings, Engineering and Associated Lists."

Page 2, PUBLICATIONS, BUREAU OF SHIPS: Delete "BUREAU OF SHIPS" and substitute "MILITARY".

Page 2, DRAWINGS, BUREAU OF SHIPS: Delete "BUREAU OF SHIPS" and substitute "MILITARY".

Page 3, paragraph 3.2.1.2, line 4: Delete "0° F." and substitute "-20° F.".

Page 3, paragraph 3.2.3: Delete and substitute:

"3.2.3 Bearings.-Antifriction bearings in accordance with FF-B-171 or FF-B-185 shall be used throughout; except, bronze bushings may be used for control and accessory shafts. All sheave bearings and bearings which will be inaccessible after installation, except those lubricated by an oil bath shall be of the "Sealed for Life" type. All other bearings shall be fitted with pressure grease fittings in accordance with type I or III of MIL-F-3541. When bushings are used, positive means shall be provided to prevent the bushing from turning and cutting off the supply of lubricant. In

1/ CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ETC.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIRE-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:32Z
Check the source to verify that this is the current version before use.

MENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

all applications of antifriction bearings, the assembly drawing of the winch shall bear a certificate signed by a responsible official of the bearing manufacturing company showing that the bearing applications proposed are approved by his company as to all details of mounting, the load and speed to which the bearing will be subjected, the lubrication of the bearings, after having given full consideration to the intended service reaquirements."

Page 4, paragraph 3.2.5.7: Add at end of paragraph: "Swivels shall not be used at the boat hooks or in any part of the falls system."

Page 4, paragraph 3.2.6: Insert the following new paragraph:

"3.2.6 Guards.- Expanded metal guards shall be provided on the underside of the trackways. The guards shall extend from 6 inches below the davit arm outboard stop to 12 inches above the extreme inboard travel of the davit arm rollers. The guards shall be so designed as to prevent the extension of fingers or other members into the path of the davit arms in their movement. The guards shall be manufactured in easily handled sections and shall be attached to the davit structure by hex head bolts."

Page 7, paragraph 3.5.1.2, line 5: Delete and substitute:

"Duty - Short time, 15 minutes, for type I davits
30 minutes varying, for type II, III and IV davits"

Page 7, paragraph 3.5.2, at end of paragraph: Add: "The brake and hand-crank interlock switches, trackway limit switches, the master switch and geared limit switch, where used, shall be in accordance with the applicable controller specification."

Page 8, paragraph 3.5.3, at end of paragraph: Add: "The master switch shall include a long wipe feature. That is, the switch shall have two positions in each direction of operation, and operate so that the first position sets up the circuit and operation of the winch begins in the second switch position. Operation shall then continue with the switch in either of the two positions, stopping only when the switch is returned to the "OFF" position."

Page 9, paragraph 3.10: Delete "class A in accordance with MIL-D-963." and substitute "in accordance with MIL-D-1000/2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:32Z
Check the source to verify that this is the current version before use.

Page 9, paragraph 3.10.1, line 2: Delete "MIL-D-963" and substitute "MIL-D-1000/2".

Page 9, paragraph 3.11, item (d): Add at end: "The lubrication diagram shall also have notations as to the locations of "Sealed for Life" bearings with instructions for periodic inspection based on the manufacturers recommendations."

Page 11, paragraph 6.1:

Item (d): Line 1, after "winch" delete "k"; line 2, add "3.2.1)."
Item (e): Add "3.2.1.3."

Preparing activity:
Navy - SH
(Project 2030-N004)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:32Z
Check the source to verify that this is the current version before use.