MIL-S-17794E
10 June 1985
SUPERSEDING
MIL-S-17794D
13 August 1980

MILITARY SPECIFICATION

SNOWPLOWS, TRUCK-MOUNTED: DISPLACEMENT TYPE, 36,000 GVWR, 4 BY 4

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.2 Scope. This specification covers V-blade, reversible blade, and rollover blade displacement type snowplows, mounted on a 4 by 4 commercial truck powered by a diesel engine.

1.2 Classification. Truck-mounted, displacement snowplow shall be one of the following types, classes, and styles, as specified (see 6.2).

Type II - V-blade.
Type III - Reversible blade.
Type IV - Rollover blade.

Class A - Chassis with dump body.
Class B - Chassis with sander body.

Style 1 - With right-hand leveling wing.
Style 2 - With left-hand leveling wing.
Style 3 - With right- and left-hand leveling wings.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3825

DISTRIBUTION STATEMENT A.
Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-C-3774 - Crates, Wood; Open, 12,000- and 16,000-Pound Capacity.
MIL-A-8421 - Air Transportability Requirements, General Specification for.
MIL-H-14435 - Hitches, Snowplow, Front-of-Vehicle Mounting.
MIL-C-52950 - Crates, Wood, Open and Covered.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-209 - Slinging Eyes and Attachments for Lifting and Tying Down Military Equipment.
MIL-STD-1223 - Administrative Wheeled Vehicles Treatment, Painting, Undercoating, Identification Marking, Data Plates and Warranty Notice Standards.
MS51317 - Light, Warning, Vehicular, Rotating, DC.

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

(Application for copies of DoT should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Code of Federal Regulations, Title 45, Part 1201 - New Motor Vehicles and Engines.

(Application for copies should be addressed to the Public Affairs Office, Environmental Protection Agency, Rockville, MD 20852.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC., (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA. 15096)

STATE OF CALIFORNIA

California Vehicle Code.

(Application for copies should be addressed to the Department of Motor Vehicles, 2570 24th Street, Sacramento, CA 95809.)

TRUCK BODY AND EQUIPMENT ASSOCIATION, INC. (TBEA)

Hydraulic Hoist and Dump Body Classification Chart.

(Application for copies should be addressed to the Truck Body and Equipment Association, Inc., 1012 Fourteenth Street, N. W., Washington, DC 20005.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. Snowplows shall be commercial products of manufacturer's latest design and shall meet the requirements specified herein. The snowplow shall consist essentially of a four-wheel, four-wheel drive, commercial, diesel-engine-driven truck, with engine forward or cab over engine chassis on which the blade, dump or sander body, and leveling wing(s) are mounted. Truck chassis and cab shall be furnished with all parts and components, commercially furnished with a truck of not less than 36,000 pound gross vehicle weight rating (gvwr). Single rear wheel shall be furnished and shall be mounted without the use of wheel spacers. Snowplows shall be supplied as self-contained units, with all parts and accessories to make a complete and serviceable unit.

3.2 First article. When specified (see 6.2), the contractor shall furnish one complete snowplow for first article inspection and approval (see 4.2.1 and 6.4).

* 3.3 Standard commercial product. The snowplow shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the snowplow being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.3.1 Painting and marking. As specified (see 6.2), by the procuring activity for the apopropriate service, treatment, painting, identification marking, data plates, and warranty notice shall be in accordance with MIL-STD-1223.

3.3.2 Instruction plates. The snowplow shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment, and shall be securely affixed thereto with nonferrous screws, rivets or bolts of not less than 1/8-inch diameter.

3.3.3 Rustproofing. When specified (see 6.2), the truck cab, chassis, shall be rustproofed in accordance with the requirements of FED-STD-297.

Source: https://assist.dla.mil -- Downloaded: 202610-18T10:34Z
Check the source to verify that this is the current version before use.

3.3.4 Drain plugs. The drain plugs, installed throughout the the snowplow for the purpose of draining lubricants, shall be of the permanent magnet type.

3.3.5 Tow hooks. Tow hooks shall be provided on the rear of the truck and shall be attached to the truck frame members.

3.3.6 Rear wheel splash and stone throw protection. Manufacturer's standard splash guards shall be provided in back of rear tires. Splash and stone throw protection shall be in accordance with SAE J682.

3.3.7 Lifting and tiedown devices. When specified (see 6.2), lifting and tiedown devices conforming to MIL-STD-209 shall be furnished.

3.3.8 Air transportability. When specified (see 6.2), the snowplow shall be air transportable in aircrafts indicated by the procuring activity. Transportability requirements shall be in accordance with MIL-A-8421.

* 3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

* 3.6 Safety. All parts subject to high operational temperatures, that are of such a nature or are so located, as to be or become a hazard to the safety of the operating personnel, shall be insulated, enclosed, or fully guarded to the extent necessary to eliminate the hazard. The snowplow shall comply, if applicable, with OSHA regulations in effect at time of manufacture.

3.7 Weights and rating. The gvwr rating for the truck shall be not less than 36,000 pounds (lb). The dry weight of the truck chassis, with single tires, and cab with standard equipment (but not including weight of dump or sander body, plow with components, fuel, engine coolant, and lubricants) shall be not less than 13,000 lbs for engine forward type and not less than

Source: https://assist.dla.mil -- Downloaded: 202610-18T10:34Z
Check the source to verify that this is the currentversion before use.

12,500 lbs for cab over engine type. The application of weight to the chassis for the purpose of meeting the dry chassis weight requirement is not acceptable. Component and vehicular ratings shall not be raised to meet the requirements of this specification.

3.8 Performance.

3.8.1 Speeds and gradeability. High and low speed requirements shall be met with truck loaded to rated gvwr.

* 3.8.2 High speed gradeability. Truck shall ascend 1.5 percent grades at 50 miles per hour (mph) when calculated in accordance with SAE J688 (see 6.5).

3.8.3 Low speed. Low speed shall be calculated with engine operating at not less than 35 percent of recommended governed speed, and shall provide a vehicle speed of not more than 3 mph.

3.8.4 Brake performance. Service brakes shall comply with the performance requirements specified in DoT Federal Motor Carrier Safety Regulations, section 393.52. The parking brake shall be adequate to hold the truck, loaded to rated gvwr, on any grade on which it is to be operated under all conditions of loading on a surface free from snow, ice, or loose material. In any event, the parking brake shall be capable of locking the braked wheels to the limit of traction.

3.9 Environmental conditions.

* 3.9.1 Temperature conditions. The snowplow shall start and operate at rated capacity in any ambient temperature between -25 degree (°) Fahrenheit (F) and +110°F. The snowplow shall not be damaged by storage in any ambient temperature from +160°F to -65°F for periods of several days at a time.

3.9.2 Winterization. When specified (see 6.2), the complete snowplow shall be winterized and be able to start and operate in any ambient temperature as low as -65°F.

3.10 Truck.

3.10.1 Chassis. The truck chassis shall be constructed to perform under all snowplow operational requirements indicated herein without permanent deformation. The truck chassis shall be of the conventional style. Chassis frame shall be suitable in every respect for use with the hitch and pusher bracket specified in 3.11.

3.10.2 Wheelbase and overall width. Wheelbase shall be not less than 138 inches and not more than 158 inches. Cab to axle dimension shall provide for mounting the leveling wing mechanism(s) back of the cab, and provide space for dump or sander body as furnished. Overall width shall not exceed 96 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

3.10.3 Truck engine. The truck engine shall be a diesel engine having horsepower, torque, and speed characteristics to satisfactorily meet all truck performance requirements specified in 3.8.1, 3.8.2, and 3.8.3.

3.10.3.1 Oil filter. Full flow type oil filter shall be furnished.

3.10.3.2 Governor. Engine governor shall be set and sealed to limit engine to maximum recommended operating speed.

* 3.10.3.3 Heavy-duty cooling systems. A heavy-duty cooling system shall be provided. The cooling system shall be of the pressurized type of sufficient capacity to maintain a cooling liquid temperature of not less than 140°F, and to provide proper cooling without overheating or loss of coolant when operating in an ambient temperature range of -25°F to +125°F during operating conditions of either stationary or mobile performance as specified.

* 3.10.3.3.1 Coolant recovery system and indicators. The coolant recovery system shall include a de-aeration system, a surge tank, or a coolant recovery reservoir of not less than 2 quarts capacity. In addition, a low coolant level or high coolant temperature alarm buzzer and red warning light shall be provided on the cab instrument panel.

3.10.3.4 Air pollution control. All snowplows shall comply with EPA Motor Vehicle Air Pollution Standards applicable on the date of manufacture to nonmilitary, nonexport motor vehicle products. When specified (see 6.2), snowplows shall additionally comply with the State of California regulations governing air pollution control applicable on the date of manufacture.

3.10.4 Fuel system. Fuel system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.65.

* 3.10.4.1 Air cleaner. An engine intake air cleaner shall be furnished. Air cleaner shall be dry type, 2 stage with air cleaner condition indicator and automatic water and dust evacuator. The cleaners shall be located and protected to preclude entrance of snow.

3.10.4.2 Fuel tank. Fuel tank capacity shall be not less than 75 gallons. When more than one tank is furnished, means shall be provided to assure equalized fuel level in both tanks. When both right and left hand leveling wings are furnished, fuel tank capacity shall be not less than 50 gallons.

3.10.5 Electrical system.

* 3.10.5.1 Starting system. A 24 volt (V) or 12V negative ground starting system, with 12V lighting system, and with not less than a 65-ampere alternator, shall be furnished. Engine starting equipment shall include an ether starting system of the measured shot type with storage capacity of not less than 12 fluid ounces. Batteries are not to be mounted on top of truck front fenders.

Source: https://assist.dla.mil -- Downloaded: 202640-18T10:34Z
Check the source to verify that this is the currentversion before use.

3.10.5.2 Lighting. All truck lights, reflectors, and wiring shall be as specified herein and shall be in conformance to DoT Federal Motor Carrier Safety Regulations, sections 393.19 through 393.26(d), 393.27 through 393.31, and 393.33. The electrical circuits shall be protected by circuit breaker(s) and shall be controlled by heavy-duty service switches. Circuits shall be color coded or numbered. Headlights and turn signals shall be mounted so that plow blade will not interfere with illumination of road or visibility of signals. The following additional lights shall be furnished:

* a. One spotlight, on the forward part of the truck cab, controllable by the driver when seated in his operating position.
b. One amber warning light conforming to MS51317, part no. MS51317-2. The warning light shall be so installed as not to be obstructed by exhaust pipes or other components for more than a 15° continuous horizontal angle by each obstruction.
c. Interior cab light(s).
* d. Two backup lights.

* 3.10.5.3 Batteries. Not less than two 12V negative ground batteries, of the maintenance free type, shall be provided. The batteries shall be rated for at least the engine manufacturer's recommended cold cranking ampere for engine starting at -25°F (-65°F if winterized) and for the necessary reserve capacity for the electrical load. Batteries shall be contained in a metal box or frame with an acid resistant interior coating and/or pan, in a protected, easily accessible location. Batteries shall not be mounted on the top of the chassis front fenders.

3.10.6 Exhaust system. The exhaust system shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.83. Exhaust mufflers, when stacked, shall be furnished with a heat shield.

* 3.10.7 Transmission. A torque converter and manually controlled full power-shift or automatic type transmission, matched to the operating characteristics of the diesel engine, shall be provided. Design of transmission and location of controls shall provide for the maximum practicable ease in gear selection. The transmission shall have not less than four forward and one reverse gear ratios. The shifting of gears in forward speed, either up or down through all available gear ratios, shall be possible without interrupting the output of power from the engine through the drive train of the truck. Torque capacity to the components shall be adequate to transmit the maximum gross torque of the engine through all gear reductions or torque muliplications, or not less than the torque required for wheel slip on a surface having a coefficient of 0.80 whichever is less. Gear reduction shall be sufficient to allow peak torque engine speed at torque converter efficiency of not less than 70 percent. Gears shall be heat-treated and properly finished to insure quiet operation and long life.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

* 3.10.8 Transfer assembly. The transfer assembly shall provide a drive to the front and rear axles. When a cam or gear type differential is used, a manual or automatic locking means shall be provided that will maximize the transmission of torque to all wheels, regardless of traction conditions.

3.10.9 Drive train components. The drive train components, including, but not limited to the torque converter, transmission(s), propeller shafts, axle shafts, and differential, shall be matched to the engine, shall be compatible, and shall transmit the engine torque at converter stall condition as multiplied by torque converter through all reductions or wheel slip conditions, whichever is less.

3.10.10 Suspension. Truck shall be equipped with suspension system having components with a rated capacity at least equal to the loads imposed on each member, measured at the ground, with truck loaded to rated gvwr. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. Shock absorbers of the heavy-duty, double-acting, hydraulic type shall be mounted on the front axle.

* 3.10.11 Axles. Front and rear axles shall be manufacturer's standard full floating type, designed for single tire mounting. The front and rear tread widths shall not vary more than 6 inches. Wheel spacers shall not be used to obtain correct tread widths. The rear axle shall be equipped with limited slip, manual or automatic locking type differential. The torque capacity of each axle differential shall be at least 10 percent in excess of the maximum torque, to which the axle could be subjected under any operating condition with the truck loaded to rated gvwr. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with truck loaded to rated gvwr. The power transmitting shaft on the steering axles shall incorporate steering joints of a type that produces no objectionable steering characteristics throughout their range of angular travel, with the steering joints enclosed in sealed housings.

3.10.12 Wheels, rims, tires, and tubes. Chassis shall be equipped with single front and single rear wheels. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tire furnished. Tire and rim sizes shall be the same for all wheels interchangeable front and rear, on each snowplow. Wheels shall be 10-lug, disc type.

3.10.12.1 Tires. Tires shall be tubeless type with all weather traction type tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel at the ground, when the snowplow, with plow attached and raised, is loaded to its rated gvwr with sand in the body. Tires shall be of not less than 100 level quality and of domestic make.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

* 3.10.12.2 Spare wheel. A spare wheel, less tire and tube, shall be furnished.

3.10.12.3 Tire chains. Four antiskid tire chain assemblies, consisting of two side chains with cross chains and suitable end fasteners, shall be provided. Tire chain assemblies shall be designed for use with the tires and wheels furnished with the snowplow.

3.10.12.4 Tire chain clearance. Clearance shall be provided for installation and use of tire chains on all wheels.

3.10.13 Brakes. Brakes shall conform to the DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.42, 393.45 through 393.52, and as specified herein.

* 3.10.13.1 Service brakes. Truck shall be equipped with manufacturer's standard full-air type four-wheel brakes. Braking system shall be complete with all necessary components including the following:

a. Air compressor, unloader-head type, engine driven and lubricated, air or water cooled, and having a capacity of not less than 12 cubic feet per minute.
b. Air storage reservoir(s) with not less than 2,240 cubic inches total capacity; reservoir(s) shall be equipped with drain, and with safety and check valves between compressor and last reservoir tank.
c. Foot control, suspended or treadle type.
d. Quick release valve, for rear brakes.
e. Automatic moisture ejector, heated type.
f. Limiting valve for front brakes, combined with quick-release valve.

3.10.13.2 Parking brake. Parking brake shall conform to the requirements of DoT Federal Motor Carrier Safety Regulations, section 393.41.

3.10.13.3 Air brake emergency system. When specified (see 6.2), an emergency brake system shall be furnished for full air application brakes. The system shall be capable of being manually applied by the operator seated in the driver's seat. A manual or mechanical means to release the brakes shall be provided when compressed air is not available to release the brakes. The emergency system shall conform to the requirements of the California Vehicle Code, section 26508. The emergency system, when provided, shall also serve as a parking brake and shall conform to DoT Federal Motor Carrier Safety Regulation, section 393.41.

3.10.14 Steering. Manufacturer's current standard power assist steering shall be furnished. Design of power assist mechanism shall permit manual steering in event of failure of the power system.

Source: https://assist.dla.mil -- Downloaded: 202610-18T10:34Z
Check the source to verify that this is the currentversion before use.

* 3.10.15 Cab. The truck cab shall be of steel or aluminum construction, fully enclosed and insulated, not less than 72 inches wide overall, and shall seat two men on cushioned seats. The seat for the driver shall be adjustable for height and fore and aft position. Cab glazing and window construction shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.60 (a) and 393.61 (a). Windshield shall be tinted for glare protection in accordance with manufacturer's standard for tinted, heat absorbing glass. The windshield shall be heated and controlled by a dash mounted switch. Tinting of lamination is not acceptable. The cab shall be provided with dual sun visors of a type that will afford the driver and the plow operator sun protection. Cab ventilators shall be located to minimize entry of snow. The cab shall have a hinged door on each side providing easy access. Running boards, cab stops, and assist handles and bars shall be of ample size and design to insure safety and easy entrance and exit on both sides of the cab for personnel wearing bulky arctic overshoes, mittens, and outer garments. All step surfaces on the exterior of the truck shall be nonskid, grated type. The cab shall have two heated, outside rearview mirrors, one mounted on each side of the cab, each with at least 85 square inches of reflective area, and each with at least three supporting arms. Manufacturer's standard fastenings and two pairs of seat belts shall be furnished and installed for use with the seats supplied.

3.10.15.1 Windshield wipers and washers. Cab shall be equipped with dual windshield wipers and dual windshield washers. Windshield wipers shall be multispeed type and operated by either vacuum with booster, air, or electric motor(s). Washer supply container shall have a minimum capacity of 1 quart.

3.10.15.2 Cab heater and defroster. Cab heater and insulation shall be capable of providing and maintaining a minimum inside temperature of 55°F at an ambient temperature of -25°F, with 10-15 mph wind. Heater shall be manufacturer's standard liquid coolant operated type meeting the requirements of DoT Federal Motor Carrier Safety Regulations, section 393.77, as applicable. Defroster shall keep not less than 75 percent of the windshield cab doors and rear window area clear at an ambient temperature of -25°F and shall be provided with an air regulating control. Heater and defroster controls shall be mounted on the instrument panel.

3.10.15.3 Instrument panel. The cab shall be provided with an instrument panel equipped with instruments and controls located in full view of, and for convenient operation by the operator. All instruments and controls shall be permanently identified as to their function and illuminated by rheostat controlled lighting. All instrument and controls necessary for proper operation of the truck shall be provided and shall, as a minimum, include the following:

a. Voltmeter.
b. Fuel level gage.
c. Lubricating oil pressure gage.
d. Engine coolant temperature gage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

e. Speedometer with recording odometer.
f. Tachometer.
g. Air reservoir pressure gage.
h. Low air pressure warning, visual and audible type.
i. Starting switch.
j. Light switches and headlight beam indicator.
k. Engine hour meter.
l. Horn.
m. Torque converter oil temperature guage.

* 3.10.15.4 Two-way radio equipment. When specified (see 6.2), installation space shall be provided in the cab for two-way radio equipment. Dimensions of the required space shall be specified (see 6.2).

3.11 Hitch and pusher bracket. Unless otherwise specified (see 6.2), the hitch and pusher bracket shall be the manufacturer's standard and shall be compatible with the snowplow furnished. Hitch shall be so designed to allow a minimum of 9 inches road clearance when plow is in the transport position. Hitch shall allow easy attachment and detachment of plows furnished. When specified (see 6.2), the snowplow hitch shall conform to MIL-H-14435.

3.12 Hydraulic power control system. The hydraulic system shall consist of at least a power takeoff, a pump, a control valve assembly, rams, oil reservoir and all necessary piping, tubing, and fittings for mounting the equipment on the truck. The system shall incorporate a pressure relief device to prevent buildup of pressure exceeding the rating of any component. The hydraulic system shall incorporate a filtration system conforming to SAE J931.

3.12.1 Power takeoff. The power takeoff shall be designed for continuous operation, driven from the front end of the truck engine crankshaft, and controlled by a lever located in the truck cab. The gear ratio shall be such that it offers compatibility between the engines governed revolutions per minute (rpm) and the pumps maximum rated rpm.

3.12.2 Pump. Pump shall be of a heavy-duty type, with sufficient capacity to provide satisfactory operation of all hydraulic components and attachments required.

3.12.3 Valve assembly. The valve assembly shall be the manufacturer's current design and conveniently positioned for controlling the operation of hydraulic equipment. Control levers shall be operable by personnel wearing arctic clothing and so located in the cab as to be operable by the driver.

3.12.4 Oil reservoir. The oil reservoir shall have sufficient capacity to hold not less than 110 percent of the oil required in the system. A shutoff valve, a drain, and a filler opening of not less than 1-1/2 inches in diameter, with splashproof filler cap and oil screen, shall be provided.

Source: https://assist.dla.mil -- Downloaded: 202610-18T10:34Z
Check the source to verify that this is the current version before use.

3.12.5 Hydraulic lines and fittings. Hydraulic tubes, hoses, and fittings shall conform to SAE J514, J516, J517, and J524. All hydraulic lines shall be of sufficient size to permit free flow of hydraulic fluid at temperature down to -40°F. Hydraulic lines shall be mounted to minimize vibration, back pressure, clogging, and leakage.

3.13 Plow types.

3.13.1 Type II. The V-blade moldboard of type II plow shall be fabricated from steel sheet of not less than 8 gage (0.1644) thickness. Moldboard shall be equipped with reversible cutting edges. Cutting edges shall be 1/2 inch thick, 8 inches wide, and of the manufacturer's recommended length for the moldboard. Tip reinforcements shall be provided at the back of the moldboard. The face of the V-blade shall be smooth with the proper curvature to lift and roll the snow up and off the road. Full flare plates or spring deflectors and adjustable shoes, casters, or heel adjusting chains shall be provided. The V-blade shall have the following dimensions:

	Feet	Inches
Working width, minimum	8	6
Height, rear end, minimum	6	6, including deflector
Height, front end, minimum	3	5

3.13.2 Type III. The reversible blade moldboard of type III plow shall be made of steel sheet of not less than 10 gage (0.1345-inch) thickness. The cutting edge shall be 1/2-inch thick, not less than 6 inches wide, and of the manufacturer's recommended length for the moldboard. The angle of the blade shall be power adjustable by the reversing mechanism to permit plowing at angles ±2° of 28°, and 35°, in either direction. Locking of the reversing mechanisms shall be provided to insure positive locking in each operating position. Moldboard shall be equipped with replaceable runners or shoes. Power reversing mechanism shall operate from full left (or right) to full right (or left) in not more than 20 seconds. The snowplow shall be equipped with a spring controlled, shock-absorbing unit which shall cushion the plow from road shocks and allow the plow to pass over obstacles and return the blade to proper position after passing the obstacle. Flare plates or spring deflectors shall be provided. The blade shall have the following minimum dimensions:

	Feet	Inches
Working width at 35° setting, minimum	8	0
Length, cutting edge, minimum	10	0
Height, moldboard, minimum	3	0

3.13.3 Type IV. The rollover blade moldboard of type IV plow shall be fabricated from steel sheet of not less than 10 gage (0.1345-inch) thickness. The moldboard shall have a uniform tapered shape symmetrical about the longitudinal centerline and shall be supported by vertical and horizontal

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

reinforcements. The driving thrust shall be transmitted by a structural frame welded to the moldboard and bolted to its horizontal reinforcements to achieve uniform load distribution. Sturdy angle iron drive bars shall connect the moldboard assembly to the truck push frame unit. Adjustable steady bars shall be provided for regulating the angle of the cutting edges with the ground. Moldboard shall be fitted with interchangeable, reversible, cutting edges 1/2 inch thick by not less than 6 inches wide, bolted to the cutting edge reinforcement angles, and not less than three, replaceable, chilled iron, wear shoes positioned behind each cutting edge. Each wear shoe shall have a bearing area of not less than 25 square inches. A replaceable, wear resisting, steel, nose shoe or runner shall be provided at the front end of the cutting edge. A planetary gear type rotating merchanism, with two double acting rams, shall be provided, which will rotate the moldboard assembly through a 180° arc for delivery of snow to either side of the snowplow, and which is controlled by levers in the snowplow cab. The mechanism shall be capable of rotating the moldboard assembly from one discharge position to the other in not more than 20 seconds, while the truck is in motion. Dimensions shall be not less than the following:

	Feet	Inches
Working width	9	0
Length, cutting edge including nose shoe	11	3
Length, moldboard	14	4
Height, front	1	6
Height, rear	5	8

3.14 Body. Truck shall be class A or class B as specified (see 6.2).

3.14.1 Dump body. Dump body shall be a commercial low mount, not more than 9 inches from top of truck frame rail to bottom of body floor, rear dump type, designed for heavy-duty operations, including loading by power shovel. The body shall have a 5 cubic yard water level capacity without the use of sideboards. Inside width shall be 84 inches minimum with overall width not exceeding 96 inches. Body floor, sides, and front head shall be constructed from not less than 8 gage (0.1644-inch) steel. When body floor is constructed in two or more pieces, an automatic seam weld, having full penetration, is acceptable without reinforcement; when hand welded, underside of joint shall be reinforced with 8 inches wide, 8 gage (0.1644-inch) butt plates welded between crossmembers. Body floor shall be provided with 1/4-inch steel wear plate and a 1-inch hardwood cushion. Wood parts shall be treated in accordance with the requirements of MIL-STD-1223. Wear plate shall be welded watertight. Full-length, channel formed, rub rail of minimum width to cover rear tire treads shall be provided. Not less than three triangular or box-section side braces shall be equally spaced, on each side of the body, between the head sheet and full-box type rear corner posts, and welded to the body side plates. Side braces shall be constructed of not less than 10 gage (0.1345-inch) steel. Front head sheet shall be formed or reinforced for rigidity. Head sheet and tailgate shall be not less than 8 inches higher than

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

the sides. Sides shall have pockets provided at each end for insertion of side boards. The interior of body shell and side reinforcements shall be welded with continuous welds. The rub rail shall be attached using continuous welds, or with intermittent welds for not less than 50 percent of the edge length of contact edges.

3.14.1.1. Cab protector. Full cab protector shall be provided and shall be bolted to front end of body. Cab protector shall be not less than 8 gage (0.1644-inch) steel. Cab protector shall be capable of supporting an evenly distributed load of not less than 2,000 lbs. Cab protector is not intended to be used for additional payload capacity. Cab protector shall be removable and will not be required when leveling wing(s) are specified (see 3.15).

3.14.1.2 Tailgate. Tailgate panel shall not be less than 8 gage (0.1644-inch) steel. Tailgate shall be double-acting, opening from top or bottom. Tailgate shall have heavy-duty hardware, heavy-duty support chains, and heavy-duty tailgate latch operable by a control at the left front corner of dump body. Tailgate shall be reinforced to prevent deformation under load.

3.14.1.3 Body understructure. Body longitudinal sills, each having a minimum section modulus equivalent to that provided by a 5-inch, 10 pound per foot I-beam, shall be provided to support hoist load. Not less than eight crossmembers shall be provided. Each crossmember shall have a minimum section modulus equivalent to that provided by a 4-inch, 7.7 pound per foot I-beam. Construction shall provide a body structure capable of supporting a uniformly distributed load of not less than 370 pounds per square foot of floor area, throughout the full lift range. Crossmembers shall be welded to the body with not less than 4-inch lengths of weld, front and rear of both ends of each crossmember, and with staggered, intermittent welds of not less than 4-inch lengths on not more than 12-inch centers. Contact edges of crossmembers with longitudinal sills, and contact edges of welded reinforcements, shall be welded for not less than 50 percent of the edge-length.

3.14.1.4 Hydraulic hoist. Hoist shall be manufacturer's standard with a minimum hoist classification of 50 in accordance with TBEA Hydraulic Hoist and Dump Body Classification Chart. Hoist shall lift body to a minimum dumping angle of 50° from top of truck chassis frame. Power takeoff, pump, and valve shall be manufacturer's standard for the hoist model furnished. Valve and power takeoff controls shall be located in the cab.

3.14.1.5 Safety lock. A mechanical safety lock, permanently affixed to the dump body, shall be furnished. Safety lock shall provide positive retention of the dump body with body in the up position for servicing or repair. Safety lock mechanism shall not interfere with operation of body under any operating conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

3.14.1.6 Body mounting. Dump body shall be constructed for two-position mounting. When body is in rear position, clearance for installation of leveling wings, when furnished, shall be provided. Body shall be mounted to the truck chassis in accordance with manufacturer's standard commercial practice.

3.14.2 Sander body. Sander body shall consist of steel hopper, a conveyor or unloader device, spreader disk(s), provision for powering the spreader disk(s), and all controls necessary to operate and control the unit from the cab. The spreader disk(s) shall be powered by either a separate gasoline engine or by a hydraulic system driven by the truck engine, as specified (see 6.2). Material discharge stream shall be controllable in width from 8 feet to at least 30 feet, and the rate of discharge shall be even and controllable.

* 3.14.2.1 Hopper. The hopper shall be constructed of not less than 10 gage (0.1345-inch) steel with a water level capacity of not less than 6 cubic yards. Hopper shall be reinforced with formed vertical outer support channels constructed of not less than 10 gage (01345-inch) steel, and of sufficient size and number to adequately support the body when loaded to full capacity. The interior to the hopper shall be of smooth contour, free of obstructions and starting 14 to 16 inches from top, shall taper to the bottom of the hopper. The taper shall be 45° and extend the full length of the inside of the hopper. Catwalks made of nonslip steel grating shall be provided on both sides of the hopper.

* 3.14.2.2 Conveyor. The conveyor shall be of the pintle, roller chain or combination chain type. Adjustment of the chain, to allow for stretch, shall be of the screw type with enclosed compression springs, permitting not less than 3-inch adjustment. All bearing shall be of ample size to carry the imposed load and shall be protected by seals. Conveyor treads and drags shall be of sufficient size to cover throat opening and to deliver the material to the spreader unit at a maximum discharge rate of not less than 1 ton per minute. Discharge gate shall be adjustable and self-locking in various positions to permit a controlled and uniform delivery. Feeder chute shall be of not less than 10 gage (0.1345-inch) steel and adjustable to permit varying the pattern of spread. A replaceable bolt on wear plate of not less than 3/16-inch steel plate, shall be mounted below the conveyor.

3.14.2.3 Spreader engine. The spreader engine, when furnished, shall be a gasoline engine having horsepower, torque, and speed characteristics to satisfactorily meet all spreader performance requirements specified herein.

3.14.2.4 Spreader disk(s). Spreader disk(s) with radial vanes shall be funished. Disk and vane material shall be abrasion-resistant steel of 144 to 183 Brinell hardness. Disk(s) shall be capable of delivering a spread pattern from 8 feet to not less than 30 feet in width while uniformly applying 4 to 5 lbs of sand per 100 square feet with the snowplow moving at a speed of 18 mph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

3.15 Leveling wing(s). When specified (6.2), leveling wing(s) shall be furnished. Wing shall be carried entirely by the chassis, and its position shall not be affected by any motion of the front plow, so that the wing can be used independently of the front-mounted plow and can be hydraulically set and held in any required angle and position. Wing shall be provided with a renewable cutting edge and renewable shoes. Leveling wing moldboard shall be constructed of sheet steel, correctly curved for efficient displacement of the material, and shall be not less than 8 gage (0.1644-inch) thickness, not less than 10 feet long, not less than 24 inches high at the front, and 34 inches high at the rear. The moldboard shall be reinforced along its entire length by substantial structural steel shapes. Road clearance shall be not less than 10 inches when the wing is in the raised position. A shock absorbing unit shall be furnished to cushion the wing from road shocks and allow the blade to pass over obstacles without damage.

3.16 Tools. Each snowplow shall be furnished with tools required for exchanging mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, jack handle, and wheel nut wrench. The jack shall be of such closed height as to permit its location under axle or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded snowplow to a height adequate to permit removal and replacement of wheel and tire assembly. Stowage space of sufficient size to accommodate jack, handtools, antiskid chains, warning flares, and reflectors shall be furnished for retaining equipment during vehicle oeration. Stowage space for these tools may be furnished inside the cab. When stowage space for these tools is located outside the cab, it shall be waterproof and shall provide for locking with a padlock.

3.17 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.18 Workmanship.

3.18.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

Source: https://assist.dla.mil -- Downloaded: 202640-18T10:34Z
Check the source to verify that this is the currenversion before use.

3.18.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.18.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.18.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.18.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the casting ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

4.2.1 First article inspection. The first article inspection shall be performed on one complete snowplow of the type, class, and style to be delivered on contract when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.5, and the packaging inspection of 4.6.

4.3 Examination. Each snowplow shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First article tests. When furnished, the first article shall be tested as specified in 4.4.1 through 4.4.6 and, as applicable, the tests specified in 4.4.7 and 4.4.8. Following the tests the first article shall be inspected for evidence of leakage in the hydraulic system, breakage or deformation of any part, malfunction of any component, to determining conformance to this specification. Failure to pass any phase of the required tests shall constitute cause for rejection. Tests specified in 4.4.2 through 4.4.5 shall be conducted with body loaded to rated gvwr.

4.4.1 Hydraulic test. Operate all hydraulic equipment through the full travel range of the rams not less than 10 times. Determine that pressure relief is incorporated in accordance with 3.12.

4.4.2 Road test. Snowplow shall be driven over paved and graveled roads for not less than 50 miles at speeds up to 50 mph. Wheels shall be turned to extreme right and left, while truck is stopped on a dry, hard surface, to determine adequacy of the power-assist steering.

4.4.3 Plowing test. Plowing test shall be conducted directly after the road tests. During this test, a strip of snow not less than 4 inches deep, 32 feet wide and 1/2 mile long shall be cleared at a speed of not less than 20 mph. This test shall be conducted at as low a temperature as weather permits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

4.4.4 Service brake test. Not less than 25 sudden and successive stops shall be made from a speed of 20 mph on dry, level, road surface to determine conformance to 3.8.4.

4.4.5 Parking brake test. Parking brake shall be tested for conformance to 3.8.4.

4.4.6 Low temperature test. The snowplow shall be subjected to an ambient temperature of -25°F for 24 hours. At the end of this period, at least three engine starts shall be accomplished to determine conformance to 3.9.1, allowing a minimum interval of 2 hours between starts. After the third start, the engine shall be allowed to warm to normal operating temperature and all other operable components of the snowplow shall be operated in a normal manner. It shall be then demonstrated that the cab heater is capable of maintaining a cab temperature in conformance to 3.10.15.2.

4.4.7 Sanding test. When sander body is supplied, the hopper shall be loaded to capacity with dry sand and the snowplow driven over a course at 18 mph with the spreader set to spread sand at each of the following widths to verify conformance to 3.14.2 through 3.14.2.4:

a. First test run - 8 feet wide by 500 feet long.
b. Second test run - 16 feet wide by 500 feet long.
c. Third test run - 30 feet wide by 1,000 feet long.

The loaded snowplow shall be weighed before and after each test run to obtain the weight of sand distributed. The sand distributed and the surface to be covered shall contrast in color sufficiently so that the uniformity of distribution can be seen.

4.4.8 Winterization. When winterization is required, the snowplow shall be exposed to an ambient temperature of -65°F for 36 hours or until stabilization is reached. The winterization equipment shall be operated and engine started to determine conformance to 3.9.2.

4.5 Production unit tests. Each snowplow shall be adjusted and serviced for operation. All controls shall be operated not less than 10 times to determine that the various components function properly. The snowplow shall be subjected to the road test specified in 4.4.2 except the driving distance shall be not less than 10 miles. Service brakes shall be tested with not less than 5 stops as specified in 4.4.4. Failure to pass any phase of these tests shall be cause for rejection.

* 5. PACKAGING

5.1 Preservation. Preservation of the complete snowplow shall be level C. The snowplow shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage. The vehicle shall be lubricated for operational service in accordance with the technical manual.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing of the complete snowplow shall be level C. The complete snowplow shall be shipped mobile in a manner which will insure arrival at destination in a satisfactory condition. Preparation for delivery shall comply with applicable carrier rules and regulation.

5.2.1 Crated components. When specified (see 6.2), the blades and leveling wings shall be removed from the truck for shipment and shall be packed in open crates conforming to MIL-C-52950, type V, style A, class 1 or MIL-C-3774, type I, style A. The contents shall be anchored, blocked, and braced in accordance with the applicable crate specification.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The snowplows covered by this specification are intended for use as general purpose plows for high speed snow removal from airfield runways, taxiways, parking spaces, and roads.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type, class, and style of plow required (see 1.2).
c. Specification and Standards (see 2.1.1)
d. When first article is required (see 3.2, 4.2.1, and 6.3).
e. Identification of appropriate service for painting and marking (see 3.3.1).
f. When undercoating is required (see 3.3.3).
g. When lifting and tiedown devices are required (see 3.3.7).
h. When air transportability is required (see 3.3.8).
i. When winterization is required and instruction for winterization (see 3.9.2).
j. When snowplows shall comply with State of California regulations governing air pollution control (see 3.10.3.4).
k. When emergency brake system is required (see 3.10.13.3).
l. When spare for two-way radio is required and dimensions of space required (see 3.10.15.4).
m. Type of hitch and pusher bracket if not as specified (see 3.11).
n. When hitch conforming to MIL-H-14435 is required (see 3.11).
o. Whether dump body or sander body is required (see 3.14).
p. Whether gasoline engine or hydraulic system is required to drive spreader disks (see 3.14.2).
q. Whether right, left, or both leveling wings are required (see 3.15).
r. When removed blades and leveling wings are to be packed in crates (see 5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL) and invokes the provisions of DoD Federal Acquisition Regulations (FAR) Supplement 27.410-6, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DoD FAR 27.410-6 are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Performance prediction. Complete copies of SAE J688 form and computation for low speed requirements for each snowplow furnished under contract should be submitted as specified in the contract. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient temperature, and still, dry air. The SAE Work Sheet Item 1 should include truck model number, wheelbase, engine model number, transmission model number, and truck type. The factors to be used in predicting truck ability (see 3.8.2) are established as follows for the corresponding SAE J688 tables:

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.	
Table 2	- Altitude Factor.	1.00
Table 3	- Rolling Factor.	1.613
Table 4	- Area Factor.	0.173
Table 5	- Velocity Factor.	250.0
Table 6	- Altitude Factor.	1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit gvwr (to nearest, higher 1,000 lbs) and the engine revolutions per minute (to nearest 100 revolutions) which is required for 50 mpy geared speed. For gvwr and engine speed beyond the range of this table, factors shall be extrapolated.	
Table 8	- Grade Factor	1.75
Table 8A	- Correction Factor.	Not required.
Table 9	- Road Factor.	0.0

Source: https://assist.dla.mil -- Downloaded: 202640-18T10:34Z
Check the source to verify that this is the current version before use.

* 6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - ME
Navy - YD

Preparing activity:

Navy - YD

(Project 3825-0167)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMP. /EMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-17794E	SNOWPLOWS, TRUCK-MOUNTED: DISPLACEMENT TYPE, 36,000 GVWR, 4 BY 4

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-18T10:34Z
Check the source to verify that this is the current version before use.