MILITARY SPECIFICATION

VALVES, BOILER BLOW, SHIPBOARD USE

This amendment forms a part of Military Specification MIL-V-17737F(SH), dated 4 December 1981, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

At bottom of page, "Beneficial comments statement", line 3: Delete "SEA 3112" and substitute "SEA 55Z3".

PAGE 2

2.1.1, under SPECIFICATIONS, MILITARY: Delete reference to "MIL-S-1222".

PAGE 3

2.2, under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM): Add:

"ASTM A 193 - Alloy-Steel and Stainless Steel Bolting Materials for High-Temperature Service. (DoD adopted)
ASTM A 194 - Carbon and Alloy Steel Nuts for Bolts for High-Pressure and High-Temperature Service. (DoD adopted)"

PAGE 4

3.2.2: Delete and substitute:

"3.2.2 Valve stems. Valve stems shall be of corrosion-resisting type 416 stainless steel conforming to MIL-S-862, ASTM A 314, or ASTM A 582 and heat treated to 248-304 Brinell hardness (Rockwell hardness RC 24 to RC 32) in accordance with ASTM A 582."

FSC 4820

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:31Z
Check the source to verify that this is the current version before use.

3.2.3: Delete and substitute:

"3.2.3 Bolts, studs, cap screws, and nuts. Bolts, studs, and cap screws shall be grade B7 or B16 alloy steel in accordance with ASTM A 193. Nuts shall be grade 7 or 4 in accordance with ASTM A 194."

LAST PAGE

DD Form 1426, Standardization Document Improvement Proposal address: Delete and substitute:

"COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362"

Preparing activity:
Navy - SH
(Project 4820-N444)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1982—605-034/960 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:31Z
Check the source to verify that this is the current version before use.