|NOT MEASUREMENT|
|SENSITIVE|

MIL-F-23019E(YD)
27 November 1991
SUPERSEDING
MIL-F-23019D(YD)
27 April 1985

MILITARY SPECIFICATION

FINISHING MACHINES, CONCRETE, ROTARY, POWER DRIVEN, HAND CONTROLLED

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers gasoline and electric power driven concrete finishing machines.

1.2 Classification. Machines shall be one of the following classes, as specified (see 6.2).

Class A - Gasoline-engine-driven.
Class B - Electric-motor-driven.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

|Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.|

AMSC N/A FSC 3895

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

TT-P-664 - Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-P-40 - Packaging and Packing of Hand Tools.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-V-173 - Varnish, Moisture- and Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).
MIL-P-514 - Plate, Identification, Instruction and Marking, Blank.
MIL-T-704 - Treatment and Painting of Material.
MIL-E-10062 - Engine, Preparation for Shipment and Storage of.
MIL-T-22085 - Tapes, Adhesive, Preservation and Sealing.
MIL-P-46093 - Primer Coating, Synthetic (For Brake Drums).

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-2073 - Packaging Requirement Codes.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

DEPARTMENT OF LABOR (DoL)
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards With Supplemental Revisions.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

MG 1 - Motors and Generators.
WD 5 - Wiring Devices, Specific Purpose.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

J534 - Standard for Lubrication Fittings.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

UNDERWRITERS LABORATORIES INC. (UL)

UL 62 - Flexible Cord and Fixture Wire.

(Application for copies should be addressed to the Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENT

3.1 Description. The finishing machine shall consist essentially of a four-arm, rotating spider with replaceable combination finishing and floating blades, power unit frame, stationary ring, and a handle with operating controls. The machine shall be designed for applying the final uniform smooth surface to freshly poured concrete.

3.2 Performance. When equipped with floating blades, the machine shall produce a smooth, even textured surface. The machine, equipped with finishing blades, shall be capable of troweling the surface to a true plane.

3.3 First article. When specified (see 6.2), the contractor shall furnish a machine for first article inspection and approval (see 4.2.1 and 6.4).

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.5 Standard commercial product. The machine shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the machine being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.6 Safety. Parts subject to high operating temperatures and parts energized electrically, which are of such a nature or so located as to become a hazard to operating and maintenance personnel, shall be insulated, enclosed, or guarded to the extent necessary to eliminate the hazard. Machine shall be equipped with a stationary blade guard. The guard shall encompass the trowel blades and extend not less than 1/2 inch or 3/4 inch beyond the working circumference of the blades. A deadman type control shall be furnished to stop blade rotation in the event the handle is released. The deadman control shall be either the positive engagement type, held by the operator's hand, centrifugal lever that disengages the clutch, or may be a grounding type switch for use on gasoline-engine-driven machines. The machines shall comply with OSHA requirements.

3.7 Ease of maintenance. Design of the machine shall permit ready accessibility to all parts for maintenance and repair by the use of conventional general-purpose handtools. Replacement and adjustment of component parts shall be accomplished with minimum disturbance to other elements on the machine. Each operation shown in the following list shall be accomplished, as applicable to the class of machine furnished, by one man in not more than the time specified:

Maintenance operations list

a. Remove, replace, and adjust V-belt(s) - 20 minutes.
b. Lubricate - 5 minutes.
c. Drain engine lube oil and refill crankcase - 15 minutes.
d. Remove and replace four rotary blades - 20 minutes.
e. Remove, clean, and replace carburetor intake air cleaner - 5 minutes.

3.8 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

3.9 Frame. Frame shall be designed to assure that the fully assembled machine has a low center of gravity. The frame shall consist essentially of a platform to support the power package, the stationary blade guard specified in 3.6 and means for lifting by two men. Frame shall be constructed of steel with the members joined by using one of the arc welding processes. To withstand the stress imposed, and to prevent permanent deformation or damage to itself, the frame shall be braced and reinforced wherever is necessary.

3.10 Power package.

3.10.1 Gasoline engine. The gasoline engine shall be a 5-11 horsepower (hp) as specified (see 6.2) air cooled, adequate to drive the finisher, and all connected auxiliaries at the rated speed. All accessories supplied commercially as standard equipment shall be furnished. The engine shall be furnished with at least the following:

a. A fuel tank with a sufficient capacity for not less than 1 hour normal operation.
b. Carburetor intake air cleaner.
c. Muffler with exhaust pipe located to assure expelled gases are directed away from the operator.
d. Manual speed control and choke.
e. A recoil starter.

3.10.2 Electric motor. The class B machine shall be powered by an electric motor conforming to NEMA MG 1. Motor shall be single phase type; totally enclosed, fan cooled style; intermittent duty with a two hp rating at a maximum speed of 3,600 revolutions per minute (rpm); 120-volt, alternating current, at 60 Hertz. If brushes are used, they shall be the heavy-duty, self-adjusting type, and easily accessible for servicing and replacement. Heavy-duty ball or roller bearings shall be furnished and shall be permanently lubricated. The machine shall be equipped with not less than 8 feet or 3 conductor, No. 12 American Wire Gage, type SO, flexible cord in accordance with standard UL 62. One end of the power cable shall be permanently attached to the operating handle with wires secured to the motor control switch. The equipment ground (green wire) shall be securely attached to the machine frame in a protective manner. The switch shall be a single pole, single throw type and mounted on the operating handle within easy reach of the operator. Wiring devices shall be in accordance with NEMA WD 5.

3.11 Power train. Power train shall consist of a clutch, V-belt drive, or gear drive. The output shaft of the power package shall be fitted with a heavy-duty type clutch equipped with ball bearings. The clutch control for engaging and disengaging the clutch shall be of the manual or automatic type. The manual type shall be mounted on the control handle. Gear shafts shall be mounted on bearings. The gearing shall be encased and permanently lubricated. Case shall be vented to the atmosphere. All bearings of the power train shall be of the heavy-duty type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

3.12 Spider. The machine shall have a four-arm, rotating, steel, aluminum, or cast iron spider to support the blades. The arms shall rotate about their longitudinal axis to provide adjustment of blade pitch. A control, mounted on the operating handle, shall enable the operator to simultaneously adjust the pitch of all blades while the machine is operating. The operating speed of the spider on the class A machine shall be adjustable between 56 and 120 rpm, while the machine is operating. The operating speed of the spider on the class B machine shall be not less than 50 rpm.

3.13 Blades. Machine shall be furnished with two sets of blades. One set of blades shall be float type; the second set shall be finish type. Blades shall be interchangeable or the float blades may be equipped with clips for attaching to the finish blades. All blades shall be fabricated of abrasion-resistant steel. Float type blades shall have a minimum surface area of not less than 110 square inches and a width of not less than 8 inches. Finish type blades shall be reversible with a minimum surface area of not less than 81 square inches and a width of not less than 6 inches. With either set of blades attached to the spider, the operating diameter of the machine shall be 34 to 39 inches.

3.14 Operating handle. Machine shall be equipped with an operating handle. All controls required for operation of the machine, except engine starting for class A machine, shall be mounted in a readily accessible location on the operating handle.

3.15 Lubrication. Lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.16 Fungus resistance. When specified (see 6.2), electrical components and circuit elements, including terminal and circuit connections, shall be coated with varnish conforming to MIL-V-173, except that:

a. Components and elements inherently inert to fungi or in hermetically sealed enclosures need not be coated.
b. Current-carrying contact surfaces, such as relay contact points, shall not be coated.

3.17 Identification plates. Unless otherwise specified (see 6.2), identification plates shall be furnished by the contracting officer. When identification plates are not furnished by the contracting officer, they shall conform to MIL-P-514, type I, style 1, composition A.

3.18 Cleaning, treatment, and painting. Unless otherwise specified (see 6.2), surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. When specified (see 6.2), the unit shall be cleaned, treated, and painted in accordance with MIL-T-704, type A. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.19 Workmanship.

3.19.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.19.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.19.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.19.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this document shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one machine when a first article is required (see 3.3 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4, and the packaging inspection of 4.5.

4.3 Examination. Each machine shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests. The first article shall be tested as specified in 4.4.1. Each production unit shall be tested as specified in 4.4.2. Failure to pass any test shall constitute cause for rejection.

4.4.1 First article tests. The first article machine shall be subjected to the tests specified in 4.4.1.1 through 4.4.1.3. Failure to pass either test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

4.4.1.1 Performance test. To determine conformance to the requirements of section 3, machine shall trowel the surface of a freshly poured concrete slab. The slab shall have a minimum surface dimension of not less than 12 feet by 12 feet. First, slab shall be screened. Then, with float blades attached, machine shall trowel the slab until the surface is smooth and even textured. Finally, equipped with finish blades, the machine shall finish trowel the surface of the concrete when surface conditions of the slab are suitable for that purpose. Upon completion of the finish troweling operation, the slab surface shall be examined for blade marks. During the test, each control located on the handle shall be operated not less than five times to prove conformance to 3.6, 3.10.1 or 3.10.2, 3.11, and 3.12, as applicable. To establish proof of compliance with the requirements of 3.12, the operating speed of the spider shall be measured with a tachometer.

4.4.1.2 Maintenance test. To demonstrate the ability to conform to the requirements of 3.7, one man using general-purpose handtools, shall perform the functions shown in the maintenance operations list within the time frame specified.

4.4.1.3 Lift test. Two men utilizing the lifting devices or stationary blade guard shall lift the machine from the ground surface to a height of not less than 30 inches. Height shall be defined as the vertical distance measured from the ground surface to the underside of the blade guard.

4.4.2 Operational test. Each machine shall be completely assembled, properly adjusted, and serviced for operation. When class A machine is furnished, the engine shall be started and subjected to a warmup period as recommended by the manufacturer. Each machine shall be operated for not less than 10 minutes. All controls shall be operated as many times as necessary to determine ease of operation, effectiveness, responsiveness, and that mechanisms actuated by the controls operate promptly, fully, and without restriction, malfunction, or excessive vibration. The gearing and other moving parts and, when applicable, the electric motor shall be tactually examined for excessive heating or abnormal operation insofar as is practical. Failure to pass any phase of this test shall be cause for rejection.

4.5 Packaging inspection. The preservation, packing, and marking of the item shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Methods of preservation. Cleaning processes, drying procedures, preservatives, and methods of preservation specified in the following paragraphs are listed in MIL-P-116 and shall conform to the requirements of MIL-P-116 and any applicable specifications.

5.1.1.2 Cleaning and drying. Prior to the application of preservative compounds or paint, surfaces shall be cleaned by process C-1 and dried by any applicable procedure of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

5.1.1.3 Disassembly. Disassembly shall be the minimum necessary to protect parts subject to damage or loss, and to accomplish reduction in cube. Removed bolts, nuts, pins, screws and washers shall be reinstalled in mating parts and secured to prevent their loss.

5.1.1.4 Matchmarking. Parts removed and mating parts on the equipment and attachments shall be matchmarked to facilitate reassembly. Parts and accessories removed, and mating parts on the equipment, shall be identified with weatherproof tags attached to mating parts and locations. Markings shall be applied to the tags with a waterproof material.

5.1.1.5 Unprotected surfaces. Unprotected exterior metal surfaces requiring specifically provided for herein shall be preserved as follows:

5.1.1.5.1 Unfinished (not machined) surfaces. Unfinished exterior metal surfaces shall be coated with type P-1 preservative.

5.1.1.5.2 Machined surfaces. Exposed machined surfaces shall be coated with type P-6 or P-11 preservative and wrapped or covered, as applicable, with barrier material conforming to MIL-B-121, type I, grade A, class 2. The material shall be secured in place with waterproof tape.

5.1.1.6 Engines. Engines, engine components, and accessories shall be preserved in accordance with the level A requirements of MIL-E-10062, type II, method I.

5.1.1.7 Electric motors. All openings into electric motors and controls shall be sealed with tape conforming to MIL-T-22085, type II. The power cable shall be coiled to a minimum safe diameter and secured.

5.1.1.8 Enclosed gears. Enclosed gears shall be filled to the operating level with the approved lubricant required for operation. Gear mechanism shall be operated to insure coating of all interior surfaces with preservative. The gear housing shall be identified with a weatherproof tag to indicate, "This housing is filled to the operating level with lubricant required for operation. Do not drain until first required lubrication change." Markings shall be applied to the tags with a waterproof material. The tags shall be attached in a conspicuous location.

5.1.1.9 Drive belts and pulleys. Drive belts shall be removed or released from tension. Removed belts shall be preserved method IC-1 or IC-3. Unpainted surfaces shall be coated with primer conforming to TT-P-664 or MIL-P-46093. A weatherproof tag shall be attached in a conspicuous location indicating: "Belts have been (removed or released from tension). (Install or tension) prior to operation." Markings shall be applied to the tags with a waterproof material.

5.1.1.10 Maintenance tools. Maintenance tools shall be preserved in accordance with level A preservation and packaging requirements of PPP-P-40.

5.1.1.11 Technical publications. Technical publications for each piece of equipment shall be preserved method IC-1 or IC-3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

5.1.1.12 Service parts. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve service parts.

5.1.1.13 Consolidation. Disassembled components, maintenance tools, service parts, and technical publications for each machine shall be consolidated in containers conforming to PPP-B-636, class weather-resistant. Contents shall be cushioned, blocked, and braced to prevent movement in accordance with MIL-STD-1186.

5.1.2 Level C. The equipment shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage. The equipment shall be lubricated for operational service as required in the operator's manual.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Levels A, B, and C. Packing shall be in accordance with MIL-STD-2073-1 for the applicable level specified. Containers shall be selected from table VII for the appropriate level. Open crates shall not be used for Level A packing.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTE

6.1 Intended use. The machines are intended for use in float finishing and trowel finishing the surfaces of freshly poured portland cement concrete slabs.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Class of machine required (see 1.2).
c. When a first article is required for inspection and approval (see 3.3, 4.2.1, and 6.4).
d. When 5 hp or 6 hp engine is specified (see 3.10.1).
e. When fungus treatment is required (see 3.16).
f. When identification plates conforming to MIL-P-514 are required (see 3.17).
g. Where cleaning, treatment, and painting shall be in accordance with MIL-T-704 (see 3.18).
h. Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD Federal Acquisition Regulations (FAR) Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data should be delivered by the contractor in accordance with the contract or purchase order requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Subject term (key word) listing.
engine
motor
trowel
frame
gasoline
electric

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue.

Preparing Activity:

Navy - YD

(Project 3895-N324)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-F-23019E(YD)	911127

3. DOCUMENT TITLE

FINISHING MACHINES, CONCRETE, ROTARY, POWER DRIVEN, HAND CONTROLLED

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
B. E. LEWIS	805-982-5464	551-5464
c. ADDRESS (Include Zip Code) COMMANDING OFFICER NAVAL CONSTRUCTION BATTALION CENTER (1564L) PORT HUENEME, CA 93043-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:13Z
Check the source to verify that this is the current version before use.