MILITARY SPECIFICATION
BATTERY, THERMAL, M17

This amendment forms a part of Military specification MIL-B-48304 (AR) dated 16 August 1976.

PAGE 4

Table V Event B; Change 15V to read 10V

PAGE 5

Note 4: Change first sentence to read: The voltage shall be between 28 and 35 volts when either maximum or minimum current is applied, except that open circuit voltage may be 37 volts maximum.

Note 6: Event A; Change volts to read 10 volts.

Para. 3.15 Transportation vibration; Delete 3.6. Add sentence, The first three digits of the resistance test code numbers shall be changed to 115 and 215 for high and low temperature respectively.

PAGE 6

Para 3.16 Transportation shock; Delete 3.6. Add sentence, The first three digits of the resistance test code numbers shall be changed to 116 and 216 for high and low temperatures respectively.

Para 3.17 High temperature; Delete 3.6 and change 3.6.1 to read 3.7.1. Add sentence, The first three digits of the resistance test code numbers shall be changed to 117 and 217 for high (160°F) and low (140°F) temperatures respectively.

Para 3.18 Low temperature; Delete 3.6. Add sentence, The first three digits of the resistance test code numbers shall be changed to 118 and 218 for high (-40°F) and low (-65°F) temperatures respectively.

FSC-NUOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.

PAGE 7

Para 3.19 Operation vibration; Delete 3.6. Add sentence, The first three digits of the resistance test code numbers shall be changed to 119 and 219 for high and low temperatures respectively, and the load description test code numbers shall be changed to 319 and 419 for high and low temperatures respectively.

Para 3.20 Transverse acceleration - temperature; Add sentence, The first three digits of the load description test code numbers shall be changed to 320 and 420 for high and low temperatures respectively.

PAGE 9

Table VII; Delete test d Initiator circuit resistance. Delete 3.6 from Note 3 and add sentence, The first three digits of the resistance test code numbers shall be changed to 014.

PAGE 11

Para 4.3.3 Inspection testing; Delete test c, Initiator circuit resistance.

PAGE 12

Para 4.3.3.1; Delete from title, "initiator circuit resistance (3.6)", and delete reference to applicable paragraph 4.4.1.

CUSTODIAN:
ARMY-AR

PREPARING ACTIVITY:
ARMY-AR

PROJECT NUMBER: NUOR-A088

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:21Z
Check the source to verify that this is the current version before use.