MILITARY SPECIFICATION

DELAY ELEMENT, CARTRIDGE, M13 ASSEMBLY

This amendment forms a part of Military Specification MIL-D-60568A(MU), dated 18 April 1967, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete: "MIL-E-5272 . . ." in its entirety.
Delete: "MIL-STD-639 . . ." in its entirety.
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines".

PAGE 2

Add: "2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the document which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018)

(Nongovernment standards and other publications are normally available from the organization which prepares or which distributes the documents. These documents also may be available in or through libraries or other informational services.)"

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

3.4 Delete: ". . . MIL-E-5272, Procedure XII . . ." and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I - 3.2.5 . . .".

PAGE 5

4.3.2 Delete: "The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 . . ." and substitute "The roughness comparison standards prescribed in ANSI B46.1 . . .".

PAGE 12

4.4.2 Delete: ". . . MIL-E-5272, Procedure XII" and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I - 3.2.5".

Preparing activity:
Navy - OS
Project No. 1377-N860

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.