INCH-POUND

MIL-E-70694A (AR)
AMENDMENT 1
19 JANUARY 1993

MILITARY SPECIFICATION

ELECTRONIC CONTROL UNIT: 11784504

This amendment forms a part of MIL-E-70694A (AR), dated 26 Sep 1991, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of defense.

PAGE 5

3.5.2.4: At end of paragraph add the following:

"The 9 to 13 second time period is measured from the time the target is first hit until it begins to raise again."

PAGE 12

4.7.2.1: Delete paragraphs 4.7.2.1, 4.7.2.1.1 and 4.7.2.1.2 their entirety and substitute:

"4.7.2.1 Vibration. This test shall be performed as specified in MIL-STD-810, Method 514, Procedure I-3.3.1 using Figure 514.4-1 for one hour along the vertical axis. After vibration, the assembly shall be operationally checked as specified in 4.7.4 to determine compliance with 3.3.1.1."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:52Z
Check the source to verify that this is the current version before use.

PAGE 15

4.7.4.8: Delete "...Immediately when this happens the target should lower through activation of the motor relay and down valve relay. Restore a good crystal condition..." and substitute the following:

"...Immediately when this happens, the target should lower through activation of the motor relay and down valve relay, and a signal will be generated and sent to the smoke scorer relay. Restore a good crystal condition..."

PAGE 16

4.7.4.13: At end of paragraph add the following:

"The 9 to 13 second time period is measured from the time the target is first hit until it begins to raise again."

PAGE 17

Table IV: 4th line down delete "500 Hz 4 205 to 255 MV" and substitute the following:

"500 Hz 4 205 to 280 MV"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 6920-A116)

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:52Z
Check the source to verify that this is the current version before use.