MIL-H-60132(MU)
AMENDMENT 1
9 January 1967

MILITARY SPECIFICATION

HEAD ASSEMBLY, TANK PERISCOPE: 10513625

This amendment forms a part of Military Specification MIL-H-60132(MU), dated 2 November 1964.

Paragraph 3.4: Delete and substitute:

"3.4 Sealing.- The head assembly shall show no evidence of leakage when subjected to an internal air pressure of 5 psig (constant) and while submerged, inverted from its normal mode, in 5 ± 1 inches of water."

Paragraph 4.2.2, Table 1: Add the following:

"104. Sealing 3.4 4.5.3"

Paragraph 4.3.2: Delete "3.04. Sealing 3.4 4.5.3"

Paragraph 4.5.3: Delete and substitute:

"4.5.3 Sealing.- An adapter that is capable of sealing the lower cavity of the head assembly shall be utilized in this test. The adapter shall be equipped with a valve, or port, that is capable of accepting an air hose for pressurizing the lower cavity of the head assembly. Affix the adapter to the head assembly. Pressurize the lower cavity of the head assembly with clean dry air to the value specified in 3.4. Invert the pressurized head assembly (prism down) and immerse it in water to the required depth for a period of 3 minutes ± 15 seconds. During this time period the head assembly shall be observed for evidence of leakage that will be in the form of air bubbles coming from within the assembly. The head assembly shall conform to the requirements specified in 3.4. The temperature of the water for this test shall be between 60° and 90°F. Upon completion of this test the head assembly shall be thoroughly dried and cleaned."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6650-A207Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.