MIL-P-60633A(MU)
AMENDMENT 1
6 October 1969

MILITARY SPECIFICATION

PROJECTILE, 40MM, XM577E1

This amendment forms a part of Military Specification MIL-P-60633A(MU) dated 3 March 1969.

Add new paragraphs 4.3.3.3, 4.3.3.3.1, 4.4.3 and 4.4.3.1

4.3.3.3 Wad

4.3.3.3.1 Oil absorption test.-Five wads from each lot of wads consisting of fifty pounds or fraction thereof, shall be subjected to this test to determine compliance with the requirement of the applicable drawing. Failure of any wad to comply shall be cause for rejection of the lot represented by the sample.

4.4.3 Wad

4.4.3.1 Oil absorption test.-The samples supplied in accordance with 4.3.3.3.1 shall be weighed individually to three significant figures (0.000) and recorded, prior to immersion into a container with the specified oil. The wads shall then be immersed in the oil (see Drawing C10542396 for specified oil) for a period of 144 hours. Care must be taken to assure that the wads are not touching one another and are completely covered when immersed. The wads shall be placed on a wire screen approximately 1/4 inch from the bottom of the container to assure that the wads are completely surrounded by oil. After the required immersion time (144 hours) the wads shall be removed from the container of oil and lightly blotted to remove the excessive oil, and immediately reweighed to determine the amount of oil the wads have absorbed.

Custodian

Army - MU

Preparing activity

Army - MU

Project No. 1310-A084

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:51Z
Check the source to verify that this is the current version before use.