FED SUP CLASS
5306




TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NUMBER	ØD BOLT SIZE	ØDc +.062 CONE PT.	L -.062 +.250 LENGTH	Lt -0 +.125 THREAD LENGTH	Lc +.062 CONE LENGTH	W WIDTH ACROSS CORNERS MIN	W WIDTH ACROSS CORNERS MAX	A WIDTH ACROSS FLATS MIN	A WIDTH ACROSS FLATS MAX	H HEAD HEIGHT MIN	H HEAD HEIGHT MAX	Z MAX	X MAX
-1	.500-13UNC-2A		4.500	3		.995	1.061	.725	.750	.308	.348	.040	.022
-2	.500-13UNC-2A		6.000	3		.995	1.061	.725	.750	.308	.348	.040	.022
-3	.625-11UNC-2A		6.000	3		1.244	1.326	.906	.938	.400	.444	.049	.028
-4	.625-11UNC-2A	.250	8.000	4	.250	1.244	1.326	.906	.938	.400	.444	.049	.028
-5	.625-11UNC-2A	.250	10.000	4	.250	1.244	1.326	.906	.938	.400	.444	.049	.028
-6	.625-11UNC-2A	.250	12.000	6	.250	1.244	1.326	.906	.938	.400	.444	.049	.028
-7	.625-11UNC-2A	.250	14.000	6	.250	1.244	1.326	.906	.938	.400	.444	.049	.028
-8	.625-11UNC-2A	.250	16.000	6	.250	1.244	1.326	.906	.938	.400	.444	.049	.028
-9	.625-11UNC-2A	.250	18.000	6	.250	1.244	1.326	.906	.938	.400	.444	.049	.028

REQUIREMENTS:

1. MATERIAL : MATERIAL SHALL BE STEEL GRADE 1020 OR 1025 (UNS G10200 OR G10250 IN ACCORDANCE WITH ASTM A576.
2. PROTECTIVE COATING : BOLTS SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
3. TENSILE STRENGTH : BOLTS WITH NUTS ASSEMBLED SHALL MEET THE TENSILE STRENGTH REQUIREMENTS LISTED IN THE PROCUREMENT SPECIFICATION.
4. THREADS : THREADS SHALL BE UNIFIED COARSE SERIES CLASS 2A IN ACCORDANCE WITH FED-STD-H28/2. PRIOR TO COATING ACCEPTABILITY OF SCREW THREADS SHALL BE IN ACCORDANCE WITH FED-STD-H28/20, SYSTEM 21. AFTER COATING, THE THREADS SHALL BE IN SUCH CONDITION THAT NUTS CAN BE RUN THE ENTIRE LENGTH OF THE THREAD WITHOUT THE USE OF TOOLS.
5. FINISH : FINISH SHALL BE IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
6. MARKING : BOLT HEADS SHALL BE MARKED WITH MS PART NUMBER AND MANUFACTURER'S SYMBOL OR OTHER MANUFACTURER'S IDENTIFICATION, IN ACCORDANCE WITH MIL-STD-130.
7. PART NUMBER : THE PART NUMBER SHALL CONSIST OF THE BASIC MS SHEET NUMBER, FOLLOWED BY A DASH NUMBER TAKEN FROM TABLE I.

EXAMPLE: MS35798-5
- DASH NUMBER
- BASIC MS SHEET NUMBER

MS35798-5 INDICATES- BOLT, MACHINE, SQUARE HEAD, HOT GALVANIZED (POLE LINE), .625-11UNC-2A, LENGTH, 10.000.

Ⓑ ENTIRE STANDARD REVISED

APPROVED 19 NOV 50 REVISED Ⓑ 16 OCT 87

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
ARMY-ER Other Cust NAVY-YD AIR FORCE-99		BOLT, MACHINE, SQUARE HEAD, HOT GALVANIZED (POLE LINE)	MS35798
PROCUREMENT SPECIFICATION ANSI C135.1	SUPERSEDES:		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1128

REVIEWER ACTIVITIES: CIVIL AGENCIES COORDINATING ACTIVITIES: ARMY-GL,ME GSA-FSS AIR FORCE-82 NASA-JFK DLA-IS
USER ACTIVITIES: NSA-NS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.

FED SUP CLASS
5306

8. UNLESS OTHERWISE SPECIFIED, EACH BOLT SHALL BE FURNISHED WITH ONE NUT ASSEMBLED THERE-ON. NUT SHALL CONFORM TO MS21304.

9. TOP OF HEAD SHALL BE FLAT CHAMFERED; THE DIAMETER OF THE CHAMFER CIRCLE SHALL BE EQUAL TO THE MAX WIDTH ACROSS FLATS WITHIN A TOLERANCE OF -15%.

NOTES:

1. ALL DIMENSIONS IN INCHES.

2. THE MAXIMUM WIDTH ACROSS FLATS APPLIES AT ALL POINTS.

3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.

4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITAION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

REVIEWER ACTIVITIES: CIVIL AGENCIES COORDINATING ACTIVITIES
ARMY-GL, ME
AIR FORCE-82
DLA-IS
GSA-FSS
NASA-JFK

USER ACTIVITIES:
NSA-NS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 19 NOV 50 REVISED (B) FOR CHANGES SEE PAGES 1 AND 2

P.A. ARMY-ER Other Cust NAVY-YD AIR FORCE-99	INTERNATIONAL INTEREST	TITLE BOLT,MACHINE,SQUARE HEAD, HOT GALVANIZED (POLE LINE)	MILITARY STANDARD MS35798
PROCUREMENT SPECIFICATION ANSI C135.1	SUPERSEDES		PAGE 2 OF 2

DD FORM 1 MAY 73 672-1 (COORDINATED)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5306-1128

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:28Z
Check the source to verify that this is the current version before use.