
FED. SUP CLASS
5305



NOMINAL SIZE		1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
B THREAD UNF-2A		28	24	24	20	20	18	16	14	12
D BODY DIAMETER	MAX	.2500	.3125	.3750	.4375	.5000	.6250	.7500	.8750	1.0000
	MIN	.2450	.3065	.3690	.4305	.4930	.6170	.7410	.8660	.9900
F WIDTH ACROSS FLATS	MAX	.4375	.5000	.5625	.6250	.7500	.9375	1.1250	1.3125	1.5000
	MIN	.4280	.4890	.5510	.6120	.7360	.9220	1.1000	1.2850	1.4690
G WIDTH ACROSS CORNERS	MAX	.505	.577	.650	.722	.866	1.083	1.299	1.516	1.732
	MIN	.488	.557	.628	.698	.840	1.051	1.254	1.465	1.675
H HEAD HEIGHT	MAX	.163	.211	.243	.291	.323	.403	.483	.563	.627
	MIN	.150	.195	.226	.272	.302	.378	.455	.531	.591
J HOLE DIAMETER	+.006 -.002	.076	.076	.107	.107	.107	.140	.140	.140	.140
K	±.010	.109	.125	.156	.156	.172	.188	.219	.250	.250
R RADIUS	MAX	.025	.025	.025	.025	.025	.045	.045	.065	.095
	MIN	.015	.015	.015	.015	.015	.020	.020	.040	.060
MIN TENSILE STRENGTH - LBS (B)		5,450	8,700	13,200	17,800	24,000	38,400	56,000	76,400	99,400

L LENGTH	TOLERANCE SIZE 3/4 AND UNDER	TOLERANCE SIZE 7/8 AND OVER	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.
.375			1	27							
.438			2	28							
.500	+0		3	29	55						
.562	-.031	---	4	30	56						
.625			5	31	57						
.750			6	32	58	84	110	133			
.875			7	33	59	85	111	134			
1.000			8	34	60	86	112	135	157		
1.250			9	35	61	87	113	136	158	182	206
1.500	+0	+0	10	36	62	88	114	137	159	183	207
1.750	-.062	-.125	11	37	63	89	115	138	160	184	208
2.000			12	38	64	90	116	139	161	185	209
2.250			13	39	65	91	117	140	162	186	210
2.500			14	40	66	92	118	141	163	187	211
2.750			15	41	67	93	119	142	164	188	212
3.000			16	42	68	94	120	143	165	189	213
3.250			17	43	69	95	121	144	166	190	214
3.500			18	44	70	96	122	145	167	191	215
3.750	+0	+0	19	45	71	97	123	146	168	192	216
4.000	-.094	-.188	20	46	72	98	124	147	169	193	217
4.250			21	47	73	99	125	148	170	194	218
4.500			22	48	74	100	126	149	171	195	219
4.750			23	49	75	101	127	150	172	196	220
5.000			24	50	76	102	128	151	173	197	221
5.500							129	152	174	198	222
6.000							130	153	175	199	223

NOTE: For notes see sheet 2.

(B) For changes see sheets 1 and 2.

APPROVED 16 JUL 1958 REVISED (A) 14 OCT 1968 (B) 1 MAY 1969

REVIEWER:AT, AV, IS, NSA, OS, 85
USER:AS, GL, MC, ME, YD

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC
Other Cust SH 82

TITLE
SCREW, CAP, HEXAGON HEAD (FINISHED HEXAGON BOLT), SHANK DRILLED FOR COTTER PIN, ALLOY STEEL, GRADE 8, PHOSPHATE COATED, UNF-2A

MILITARY STANDARD
MS51108
SHEET 1 OF 2

PROCUREMENT SPECIFICATION
FF-S-85

SUPERSEDES:
BUBX31, BUBX31.1 and BUBX32

DD FORM 672-1 (Coordinated)
PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:58Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5305

NOTES:

1. MATERIAL: Alloy steel, Grade 8, in accordance with procurement specification. Minimum ultimate tensile strength: 150,000 p.s.i.

2. PROTECTIVE COATING: Phosphate coated in accordance with procurement specification.

3. THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services, Handbook H28.

4. THREAD LENGTH: Minimum thread length shall be twice the diameter plus 1/4 inch. The tolerance shall be plus 3/16 inch or 2-1/2 threads, whichever is greater. On screws that are too short for minimum thread lengths, the distance from the bearing surface of the head to the first complete thread shall not exceed the length of 2-1/2 threads.

5. DIMENSIONS: All dimensions are in inches, unless otherwise specified.

(B) 6. HEAD MARKING: Heads shall be marked in accordance with MIL-HDBK-131. Raised markings are preferred, stampings are acceptable.

7. PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS51108-1.

8. Referenced documents shall be of the issue in effect on date of invitations for bid.

9. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

REVIEWER:AT, AV, IS, NSA, OS, 85
USER:AS, CL, MC, ME, YD

APPROVED 16 JUL 1958 REVISED (A) 14 OCT 1968 (B) FOR CHANGES SEE SHEETS 1 AND 2.

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC Other Cust SH 82	TITLE SCREW, CAP, HEXAGON HEAD (FINISHED HEXAGON BOLT), SHANK DRILLED FOR COTTER PIN, ALLOY STEEL, GRADE 8, PHOSPHATE COATED, UNF-2A	MILITARY STANDARD MS51108
PROCUREMENT SPECIFICATION FF-S-85	SUPERSEDES: BUBX31, BUBX31.1 and BUBX32.	SHEET 2 OF

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-519/A-6598

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:58Z
Check the source to verify that this is the current version before use.