MIL-B-3621C
27 April 1988
SUPERSEDING
MIL-B-3621B
10 January 1968

MILITARY SPECIFICATION

BLANKET, DOG

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers a felt-lined cotton duck dog blanket (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

C-F-206	- Felt Sheet: Cloth, Felt, Wool, Pressed
V-T-285	- Thread, Polyester
CCC-C-419	- Cloth, Duck, Cotton, Unbleached, Plied-Yarns

Army and Numbered

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3770

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

CCC-D-950 - Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20 - Label: For Clothing, Equipage, and Tentage, (General Use)
DDD-T-86 - Tape, Textile; Cotton, General Purpose (Unbleached, Bleached, or Dyed)
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-C-496 - Clips, End, Strap
MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or In Colors
MIL-B-543 - Buckles, Tongueless and Web Strap
MIL-F-10884 - Fasteners, Snap
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items, Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

1-10-34 - Blanket, Dog - Assembly Complete

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practices for Commercial Packaging

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

* 3.2 Materials (see 6.5).

* 3.2.1 Cloth, duck, cotton. The cloth shall conform to type III, 8.25 minimum to 9.25 maximum ounces per square yard of CCC-C-419.

3.2.1.1 Color and treatment. The cotton duck shall conform to type I, class A of CCC-D-950, shade Olive Drab 7.

3.2.2 Felt, wool. The lining fabric shall conform to type III, class 9A2 of C-F-206.

3.2.3 Tape, textile, cotton. The tape for reinforcement and binding shall conform to type I, class 3 of DDD-T-86, 1/2 and 1 inch widths, shade Olive Drab 7.

3.2.4 Webbing, textile, cotton. The webbing for chest and body adjustment straps shall conform to type IIb, class 8 of MIL-W-530, 5/8 and 1-1/2 inch widths, shade Olive Drab 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

3.2.5 Buckles, double bar with slider. The buckles shall conform to type III, style 3, class 3, sizes 5/8 and 1-1/2 inches of MIL-B-543.

3.2.6 Clips, end. The end clips shall conform to type I, class 1, sizes 5/8 and 1-1/2 inches, of MIL-C-496.

3.2.7 Fasteners, snap. The snap fasteners shall conform to style 2, finish 2 of MIL-F-10884 consisting of button, 24 line, size 1 and socket (male component); stud, and eyelet, size 1 (female component).

3.2.8 Thread, polyester. The thread for all stitching shall conform to type I or II, class 1, sub-class A, size E of V-T-285. The thread shall be dyed shade S-1 (Cable No. 66022) and shall show fastness to weathering equal to or better than the standard shade sample (see 6.4). If no standard sample is available, the thread shall show good fastness to weathering.

3.3 Construction. The construction shall conform in all respects to Drawing 1-10-34 and as specified herein.

* 3.3.1 Stitching. All stitches shall conform to FED-STD-751, type 301, 8 to 10 stitches per inch.

* 3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

* 3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching.

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box, box-x and W-W stitching) and continue a minimum of 1 inch beyond the defective area on to the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner.

(When making the above repairs in a. or b. above, the ends of the stitching are not required to be backstitched.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

* 3.3.1.2 Thread ends. All thread ends shall be trimmed to 1/2 inch or less.

3.3.2 Setting of end clips. The webbing shall be inserted the full depth of the clips. The clips shall be securely attached without cutting the webbing which shall lie flat at the point of entrance.

* 3.3.3 Setting of the metallic snap fastener. A hole shall be prepunched through the material before inserting the stud eyelet tube or the socket eyelet tube. The hole shall be smaller than the outside diameter of the applicable eyelet tube, so that the tube must be forced through the hole. Prepunched holes shall not be accomplished by using stud or socket eyelet tubes (as applicable). The fastener components shall be securely clinched without cutting the surrounding material. Roll of the clinched eyelet of the assembled fastener components shall not possess more than two scores (splits).

3.4 Marking. All markings shall conform to DDD-L-20.

3.4.1 Special marking. The letters "US", on the dog blanket, shall conform to type IV, class 9, in the size characters and in the location shown on the drawing. Class 9 markings shall be clearly legible after subjection to accelerated weathering. Fastness of class 9 markings shall be as specified for class 5 marking.

* 3.4.2 Identification label. The identification label shall be stitched to the blanket in the location shown on the drawing and shall conform to type VI, class 5.

3.5 Workmanship. The dog blankets shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

* 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in table I and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.4.2 In-process inspection. Inspection shall be made to determine that holes punched to receive male or female parts of snap fasteners are in compliance with 3.3.3 and dimensions which cannot be checked during end item dimensional examination. Whenever nonconformance is noted, correction shall be made to the items affected and the process.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of dog blankets. The sample unit shall be one dog blanket. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Fabric	Hole, cut, or tear	X	
	Any broken or missing yarn, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		X
Webbing and tape	Edge frayed or scalloped		X
Hardware (general)	Broken	X	
	Malformed:		
	-Fails to perform intended function	X	
	-But will perform intended function		X
	Corroded area		X
	Burr or sharp edge which may cause injury in handling or damage to fabric	X	
Buckles	Not assembled to strap as specified, i.e., reversed, failing to effect a secure fastening of straps	X	
End clips	Not securely clinched; webbing not flat at point of insertion		X
	Clinched excessively tight (cutting webbing)		X
Snap fastener	Roll of clinched eyelet fastener assembly contains more than two scores (splits)		X
Seams and stitching	Open seams:		
	-1 inch or less		X
	-More than 1 inch	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine		Defect	Classification	
			Major	Minor
Seams and stitching - continued	NOTE:	A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped or runoff stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.		
		Raw edges caught in stitching (when turnunder is required):		
		-More than 1 inch, but not more than 3 inches		X
		-More than 3 inches		X
	NOTE:	Raw edges not caught in stitching shall be classified as an open seam.		
Thread breaks, skipped or run-off stitches		On stitching other than box, box-X, or W-W stitching, overstitched less than 1 inch in each direction beyond defective stitching area		X
	NOTE:	Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seams		
		Needle chews resulting in cut, tear, or hole longer than 1/8 inch in length, or larger than 1/8 inch in diameter	X	
		One or more required row of stitching omitted (except on boxstitching)	X	
Boxstitching		One row of stitching omitted		X
		Two or more rows of stitching omitted	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Stitching ends	Overstitched less than 1 inch (except where ends are held down by other stitching, turned under in a hem, or where stitching is performed automatically)		X
	Secured with less than three tying, overlapping or backstitches when automatic stitching is performed		X
Seam and stitch type	Not specified seam or stitch type	X	
	Seam twisted, pleated, or badly puckered (unless otherwise classified herein)		X
	Any line of stitching not beginning or ending where specified (unless otherwise classified herein)		X
	Any seam not lapped or finished as specified		X
Stitch tension	Tension loose, resulting in loose bobbin or top thread		X
	Tension tight, resulting in puckering of material		X
Stitches per inch	One stitch less than minimum specified 1/		X
	Two or more stitches less than minimum specified 1/	X	
	Two or more stitches in excess of maximum specified 1/		X
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the material in order to sew over heavy places or in turning corners, shall be classifed as follows:		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Stitches per inch - continued	-Within the minor defect classification - no defect -Within the major defect classification - minor defect		
Stitching margin	Larger than specified by more than 3 inches		X
Components and assembly	Any components part or required operation omitted (unless otherwise classified herein)	X	
	Any operation not performed as specified (unless otherwise classified herein)		X
	Color of component not as specified		X
Binding	Not attached or stitched as specified on Drawing 1-10-34		X
Marking	Omitted, incorrect, illegible misplaced, or size of characters not as specified	X	
Cleanness	Any spot or stain on outside		X
	Thread ends not trimmed as specified or loose threads not removed		X

1/ Score only where the condition exists for 3 inches or more or in several areas with an accumulated distance of 5 inches or more in an individual seam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. Examination shall be made of the blanket for conformance to the dimensions annotated with an asterisk (*) on Drawing 1-10-34. The lot size shall be expressed in units of blankets. The sample unit shall be one blanket. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 10.0.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

* 4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each blanket shall be neatly folded in such a manner that the buckles are positioned inside the folds. The blanket shall then be placed in a close-fitting, clear polyethylene film bag of 0.0015 inch thickness (± 20 percent tolerance). The bag shall be formed with heat sealed seams that are straight, continuous and parallel to each other and to the formed edges of the bag. The final closure of the bag shall be sealed with the heat seal made as close as possible to the open end. Prior to or during the closure operation, excess air within the bag shall be expelled.

* 5.1.2 Commercial. Blankets shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Forty blankets, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each box shall be fitted with a taped liner conforming to V3c of PPP-B-636. Level A unit packs shall be uniformly arranged in the box to form a balanced pack. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. Forty blankets, preserved as specified in 5.1, shall be packed in a close-fitting fiberboard box conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be uniformly arranged in the box to form a balanced pack. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

* 5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Blankets, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

* 5.3 Palletization. When specified (see 6.2), blankets, packed as specified in 5.2, shall be palletized in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required information legibly printed or stamped in black, directly on the bag, across the center face on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall indicate the following information:

STOCK NO.

NOMENCLATURE

QUANTITY

6. NOTES

6.1 Intended use. The blanket is intended to provide protection for dogs in cold weather.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Stock number.
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit loads required (see 5.2.1).
f. When weather-resistant fiberboard shipping containers are required for level B shipments (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

6.4 Standard sample. For access to samples, address the contracting activity issuing the invitation for bids.

* 6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.6 Subject term (key word) listing.

Blanket
Cloth, duck cotton
Dog
Felt, wool

* 6.7 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 84
DLA - CS

Preparing activity:

Army - GL

Project No. 3770-0132

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-3621C	Blanket, Dog

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil – Downloaded: 2026-10-16T18:40Z
Check the source to verify that this is the current version before use.

DD FORM 1426 82 MAR PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84