MIL-C-3615C
2 April 1975
SUPERSEDING
MIL-C-3615B
6 June 1969

MILITARY SPECIFICATION

CAMERAS, COPYING, LITHOGRAPHIC, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for materials, methods, and procedures for the preservation, packaging, packing, and marking of copying cameras and their accessories.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-S-781	- Strapping,Steel, and Seals.
UU-T-81	- Tags, Shipping and Stock.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-C-843	- Cushioning Material, Cellulosic.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

Military

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation-Packaging, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-130	- Paper, Wrapping, Laminated and Creped.

FSC 6720

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

MIL-P-775	- Packaging of Hose, Hose Assemblies, Rubber, Plastic, Fabric, or Metal (Including Tubing); And Fittings, Nozzles and Strainers, Packaging of.
MIL-C-3774	- Crates, Wood; Open, 12,000- and 16,000-Pound Capacity.
MIL-E-16298	- Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of.
MIL-E-17555	- Electronic and Electrical Equipment, Accessories, and Repair Parts, Packaging and Packing of.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington DC 20036.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.2 Preproduction pack. The supplier shall furnish a preproduction pack within the time frame specified to prove, prior to starting production packaging and packing, that the applied preservation, packaging, packing, and marking comply with the requirements of this specification (see 6.3). Examination and tests shall be those specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.2).

3.3 Preservation and packaging. Preservation and packaging shall be Level A, B, or C, as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Assembled cameras. Each completely assembled camera, that can be secured to the crate base specified in 3.4.1.1, shall be preserved in accordance with MIL-P-116, Method IIa. The camera shall be secured by bolting directly through the barrier material to the crate base. Movable components shall be positioned to realize minimum cube, and the positioned components secured to prevent movement within the barrier material.

3.3.1.1.1 Repair parts and accessories for assembled cameras. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve and package the repair parts and accessories.

3.3.1.1.2 Maintenance tools for assembled cameras. Maintenance tools for each camera shall be preserved and packaged in accordance with PPP-P-40, Level A.

3.3.1.1.3 Technical publications for assembled cameras. The technical publications for each camera shall be preserved together in accordance with MIL-P-116, Method IC-1.

Source: https://assist.dla.mil -- Downloaded: 20261-16T18:39Z
Check the source to verify that this is the current version before use.

3.3.1.1.4 Consolidated packaging for assembled cameras. The preserved and packaged repair parts, accessories, maintenance tools, and technical publications for each assembled camera shall be consolidated packaged in close-fitting boxes conforming to PPP-B-601, Domestic Type, Grade B. Cushioning, blocking, and bracing shall be provided to prevent movement of the contents within the boxes. Strapping shall not be required.

3.3.1.2 Unassembled cameras. The unassembled components comprising complete cameras with repair parts, accessories, maintenance tools, and technical publications shall be preserved and packaged as follows.

3.3.1.2.1 Matchmarking. Components shall be matchmarked to facilitate reassembly of the cameras. Matchmarking information shall be on cloth tags conforming to UU-T-81, Type A, and the marked tags shall be attached to the components. Printing thereon shall be with waterproof ink in accordance with MIL-STD-129.

3.3.1.2.2 Preservatives. Unless otherwise indicated herein, preservatives specified shall conform to the applicable specifications listed in MIL-P-116 and shall be applied in accordance with MIL-P-116.

3.3.1.2.3 Machined and precision metal surfaces. Unpainted exterior machined and precision metal surfaces of components, including the machined surfaces of the rails, shall be coated with Type P-6 preservative. The coated surfaces shall be wrapped or covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV.

3.3.1.2.4 Other unpainted metal surfaces. Unpainted exterior metal surfaces of components such as coil springs, bolts, nuts, structural members, and similar components; and any other unpainted exterior metal surface not specified herein requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative.

3.3.1.2.5 Negative holders with adjustment mechanism, position holders with clamps, and screen holders. Exterior unpainted metal surfaces shall be coated with Type P-6 preservative and the coated surfaces wrapped or covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV. Interior metal

Source: https://assist.dla.mil -- Downloaded: 20261-16T18:39Z
Check the source to verify that this is the current version before use.

surfaces shall be coated with Type P-7 preservative. The assemblies of like description shall be preserved together in accordance with MIL-P-116, Method IA-14. The inner containers shall conform to PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 175 and the outer containers shall conform to PPP-B-636, W5c. The outer container shall be closed in accordance with Method V of box specification appendix.

3.3.1.2.6 Lensboard, copyboard, and bellows carriages; and lensboard and copyboard frame assemblies. The reducer gears, counter mechanisms, and ball-bearing rollers of the carriages shall be coated with Type P-7 preservative. All other unpainted surfaces of the bellows carriages and copyboard frame assemblies shall be coated with Type P-1 preservative. Surfaces coated with Type P-7 preservative shall, where practical, be wrapped or covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV. Preservatives shall not be allowed to contact electrical motors, oscillating-motor resistors, electrical wiring, control cables of the carriages, shutter mechanisms or felt backing around the lens-plate bearings on the lensboard assemblies. After application of the preservative, each carriage and each assembly shall be preserved in accordance with MIL-P-116, Method IIb. The inner containers shall be boxes, Type CF, Class Domestic, Variety SW, Grade 175, and the outer containers shall be V3c boxes, both conforming to PPP-B-636. The outer containers shall be waterproof sealed as specified for Method V closures in appendix to the box specification.

3.3.1.2.7 Bellows. Each bellow section shall be preserved in accordance with MIL-P-116, Method IA-15. The containers shall conform to PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 175.

3.3.1.2.8 Glass. Glass components such as diffusers, reflecting and filtering glasses, halftone screens, copyboards, and all ground glasses with or without frames shall be cleaned with lens cleaning fluid and individually wrapped with jeweler's tissue. Each glass shall be preserved in accordance with MIL-P-116, Method IA-15. The containers shall be boxes conforming to PPP-B-636, Type CF, Class Domestic, Variety SW, Grade 175, and shall be of sufficient size to allow a minimum of 2 inches of cushioning material conforming to PPP-C-843, Type II, Class B between the glass and all interior surfaces of the boxes.

3.3.1.2.9 Vacuum systems.

3.3.1.2.9.1 Pumps. The interior surfaces of pumps, including all working parts such as rotors, shafts, vanes, pistons, cylinder walls, air and oil passages, cooling systems, and oil reservoirs shall be coated with Type P-10, Type I, Grade 10 preservative. Pumps not attached to the camera shall be individually preserved in accordance with MIL-P-116, Method IA-14. All

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:39Z
Check the source to verify that this is the current version before use.

openings into pumps including the motors that are attached to cameras shall be sealed with tape conforming to PPP-T-60, Type IV. The inner container shall conform to PPP-B-636, Type CF, Variety SW, Grade 175 and the outer container shall conform to PPP-B-636, W5c. The outer container shall be closed by Method V of the box specification appendix.

3.3.1.2.9.2 Vacuum copyboards, vacuum copyboard positioning plates, diffuser-glass frames, and trammel levels. The vacuum copyboard shall not be coated with preservative. The other items shall be completely coated with Type P-7 preservative applied by wiping with a soft, clean, lint-free cloth saturated with the preservative. The copyboards, plates, frames, and levels shall be individually wrapped with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, and the barrier material secured in place with tape conforming to PPP-T-60, Type IV. Each item shall then be preserved in accordance with MIL-P-116, Method IIb. The inner container shall be boxes, Type CF, Class Domestic, Variety SW, Grade 175, and the outer containers shall be boxes, W5c, or W6c, both conforming to PPP-B-636. The outer containers shall be waterproof sealed in accordance with Method V of the appendix to the box specification.

3.3.1.2.9.3 Vacuum backs. Contact surfaces of the vacuum back shafts shall be coated with Type P-6 preservative. All other unpainted metal surfaces shall be coated with Type P-7 preservative applied by wiping with a soft, clean, lint-free cloth saturated with the preservative. Surfaces coated with preservatives shall be wrapped or covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV. Preservatives shall not be applied to silicon carbide or other similar materials. Each vacuum back shall be preserved in accordance with MIL-P-116, Method IIb. The inner containers shall be boxes, Type CF, Class Domestic, Variety SW, Grade 175, and the outer containers shall be boxes, W5c, W6c or V3c, both conforming to PPP-B-636. The outer containers shall be waterproof sealed in accordance with Method V of the appendix to the box specification.

3.3.1.2.10 Electrical equipment.

3.3.1.2.10.1 Motors. Electric motors detached from cameras shall be preserved in accordance with MIL-E-16298, Level A. Electric motors not detached from cameras shall be preserved in accordance with MIL-E-16298, Level A, using the alternate method specified for equipment assembled to machines.

3.3.1.2.10.2 Rheostats, transformers, switches, and accessories for rotating electrical equipment. These items if detached from the cameras shall be preserved and packaged in accordance with MIL-E-17555 or MIL-E-16298, Level A, as applicable. These items if not detached from the cameras shall have all openings sealed with tape conforming to PPP-T-60, Type IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

3.3.1.2.10.3 Lamp assemblies. Lamp assemblies shall be individually preserved in accordance with MIL-P-116, Method III, using boxes conforming to PPP-B-636, W5c or W6c, Style RSC as the containers. The boxes shall be waterproof sealed in accordance with Method V of the appendix to the box specification.

3.3.1.2.11 Hose and hose fittings. Hose and hose fittings detached from the cameras shall be preserved and packaged in accordance with MIL-P-775, Level A.

3.3.1.2.12 Lenses. Lenses with their mounts and caps in place, contained in the boxes provided, shall be preserved in accordance with MIL-P-116, Method IIb. The lens boxes shall serve as the inner containers. The lens boxes containing the lenses shall be completely wrapped with a minimum of 1 inch thickness of cushioning material conforming to PPP-C-843, Type II, Class B, secured in place with tape conforming to PPP-T-60, Type IV, prior to placing into the Method II barrier material. The outer container shall be a box conforming to PPP-B-636, W5c or W6c, Style RSC. The outer container shall be closed in accordance with Method V of the appendix to the box specification.

3.3.1.2.13 Lens plates. Lens plates shall be dipped in Type P-7 preservative. The preservative shall be thoroughly drained. Each plate shall be wrapped with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2 and the wraps secured in place with tape conforming to PPP-T-60, Type IV. Sets of plates shall be preserved together in accordance with MIL-P-116, Method IIb. The inner containers shall be boxes, Type CF, Class Domestic, Variety SW, Grade 175, and the outer containers shall be boxes, W5c, both conforming to PPP-B-636. The outer containers shall be closed in accordance with Method V of the appendix to the box specification.

3.3.1.2.14 Shutter-control adapter plates. Shutter control adapter plates shall be individually wrapped with paper conforming to MIL-P-130, Type II, and the wraps secured with tape conforming to PPP-T-60, Type IV. Sets of plates shall be preserved in accordance with MIL-P-116, Method IIb. Containers and the sealing thereof shall be as specified in 3.3.1.2.13.

3.3.1.2.15 Gages. Openings into cases enclosing gages or indicators shall be sealed with tape conforming to PPP-T-60, Type IV. Gages and indicators removed shall be individually preserved in accordance with MIL-P-116, Method III, using boxes conforming to PPP-B-636, W5c or W6c. The boxes shall be waterproof sealed in accordance with Method V of the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T18:39Z
Check the source to verify that this is the current version before use.

3.3.1.2.16 Darkroom-board assemblies and wood copyboards. Darkroom-board assemblies and wood copyboards shall be individually preserved in accordance with MIL-P-116, Method III. Each item shall be wrapped with paper conforming to MIL-P-130, Type II, and the wraps secured with tape conforming to PPP-T-60, Type IV. The containers shall conform to PPP-B-636, W5c. The boxes shall be closed in accordance with Method V of the appendix to the box specification.

3.3.1.2.17 Curtains. Unpainted exterior metal surfaces of the frames, requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with Type P-1 preservative. Roller ends shall be coated with Type P-7 preservative and the preservative allowed to drain. Surfaces coated with Type P-7 preservative shall be covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2 and the wraps or covers secured in place with tape conforming to PPP-T-60, Type IV. Sets of curtains shall be packaged in boxes conforming to PPP-B-636, W5c, W6c, or V3c, as applicable. The boxes shall be closed in accordance with Method V of the appendix to the box specification.

3.3.1.2.18 Miscellaneous components. Miscellaneous components such as counterweight housings, insulation cork, rubberized cloth, shutters, and wood wedges shall be preserved in accordance with MIL-P-116, Method III. The containers shall conform to PPP-B-636, W5c or W6c. The boxes shall be closed in accordance with Method V of the appendix to the box specification.

3.3.1.2.19 Repair parts and accessories for unassembled cameras. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve and package the repair parts and accessories of unassembled cameras.

3.3.1.2.20 Maintenance tools for unassembled cameras. Maintenance tools for unassembled cameras shall be preserved and packaged in accordance with PPP-P-40, Level A.

3.3.1.2.21 Technical publications for unassembled cameras. Technical publications for each unassembled camera shall be preserved together in accordance with MIL-P-116, Method IC-1.

3.3.1.2.22 Consolidated packaging for unassembled cameras. Packaged and unpacked component items of each unassembled camera (except the supporting structures, camera trusses, and rails), shall be consolidated together in a minimum number of wood boxes conforming to PPP-B-601, Overseas Type, Grade B or PPP-B-621, Class 2. Cushioning and blocking shall be provided to prevent damage by movement of the contents within the boxes. Strapping shall not be required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

3.3.2 Level B.

3.3.2.1 Assembled cameras. Each completely assembled camera, that can be secured to the crate base specified in 3.4.2.1, shall be preserved in accordance with MIL-P-116, Method IA-16, and as follows: The camera shall be secured by bolting directly throught the barrier material to the crate base. Movable components shall be positioned to realize minimum cube and the positioned components secured to prevent movement within the barrier material. Excess air shall be evacuated prior to sealing the barrier.

3.3.2.1.1 Machined and precision metal surfaces. Machined and precision metal surfaces of component parts shall be coated with Type P-6 preservative conforming to the applicable specification listed in, and shall be applied in accordance with MIL-P-116. The coated surfaces shall be wrapped or covered with greaseproof barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV.

3.3.2.1.2 Other unpainted metal surfaces. Unpainted exterior metal surfaces of components such as coil springs, bolts, nuts, structural members, and similar components; and any other unpainted exterior metal surface not specified herein requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with Type P-1 preservative conforming to the applicable specification listed in, and shall be applied in accordance with MIL-P-116.

3.3.2.1.3 Vacuum pumps. The interior surfaces of the pumps, including all working parts such as rotors, shafts, vanes, pistons, cylinder walls, air and oil passages, cooling systems, and oil reservoirs shall be coated with Type P-10 preservative conforming to Type I, Grade 10. All openings into the interior of the pumps and electric motors shall be sealed with tape conforming to PPP-T-60, Type IV.

3.3.2.1.4 Lenses. Lenses shall be preserved and packaged as specified for Level A. The packaged lenses shall be secured to the base of the lensboard assembly.

3.3.2.1.5 Repair parts, accessories, maintenance tools, and technical publications for assembled cameras. The repair parts, accessories, maintenance tools, and technical publications for assembled cameras shall be preserved and packaged as specified in 3.3.1.1.1, 3.3.1.1.2, and 3.3.1.1.3.

3.3.2.1.6 Consolidated packaging for assembled cameras. Consolidated packaging for assembled cameras shall be as specified for Level A.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T18:39Z
Check the source to verify that this is the currentversion before use.

3.3.2.2 Unassembled cameras. The unassembled components comprising complete cameras, repair parts, accessories, maintenance tools, and technical publications shall be preserved and packaged as follows.

3.3.2.2.1 Matchmarking. Matchmarking shall be as specified for Level A, except ink need not be waterproof.

3.3.2.2.2 Preservatives. Preservatives and their application shall be as specified for Level A.

3.3.2.2.3 Machined and precision metal surfaces. Machined and precision metal surfaces shall be preserved as specified for Level A.

3.3.2.2.4 Other unpainted metal surfaces. Other unprotected metal surfaces including camera supporting structure, truss, and rails shall be preserved as specified for Level A.

3.3.2.2.5 Negative holders with adjusting mechanisms, positive holders with clamps, and screen holders. All unpainted exterior metal surfaces of the items shall be coated with Type P-6 preservative. The coated surfaces shall be wrapped or covered with greaseproof barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV. Each item shall be packaged in boxes conforming to PPP-B-636, W5c, W6c, or V3c, as applicable. The boxes shall be closed in accordance with Method V of the appendix to the box specification.

3.3.2.2.6 Lensboard, copyboard, and bellow carriages; and lensboard and copyboard frame assemblies. The items shall be coated with preservatives as specified for Level A. After application of the preservative, each item shall be preserved in accordance with MIL-P-116, Method IA-14. The containers and closure of the outer container shall be as specified in 3.3.1.2.6.

3.3.2.2.7 Bellows. Each bellow section shall be preserved in accordance with MIL-P-116, Method III. The containers shall conform to PPP-B-636, W5c, W6c, or V3c, as applicable. The containers shall be waterproof sealed with tape as specified for slotted style boxes in accordance with the appendix to the box specification.

3.3.2.2.8 Glass. Glass components shall be preserved as specified for Level A.

3.3.2.2.9 Vacuum systems.

3.3.2.2.9.1 Pumps. The interior surfaces of the pumps shall be coated with preservatives as specified in 3.3.2.1.3. Openings into the pumps and electric motors shall be sealed as specified in 3.3.2.1.3. Pumps not attached to the cameras shall be individually packaged in boxes conforming to PPP-B-636, W6c. The boxes shall be closed in accordance with Method V of the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

3.3.2.2.9.2 Vacuum copyboards, vacuum copyboard positioning plates, diffuser-glass frames, and trammel levels. The items shall be coated with preservatives as specified in 3.3.1.2.9.2. Each item shall then be preserved in accordance with MIL-P-116, Method IA-14. The containers and waterproof sealing of the outer container shall be as specified in 3.3.1.2.13.

3.3.2.2.9.3 Vacuum backs. Vacuum back surfaces shall be coated with preservatives as specified for Level A. Each vacuum back shall be preserved in accordance with MIL-P-116, Method IA-14. The containers and waterproof sealing of the outer container shall be as specified in 3.3.1.2.13.

3.3.2.2.10 Electrical equipment.

3.3.2.2.10.1 Electrical components. Electrical components such as carbons, electric motors, rheostats, and transformers (if detached from the cameras) shall be individually preserved in accordance with MIL-P-116, Method III. Containers and waterproof sealing thereof shall be as specified in 3.3.2.2.9.1. Openings into electrical components not detached from the cameras shall be sealed with tape conforming to PPP-T-60, Type IV.

3.3.2.2.10.2 Lamp assemblies. Lamp assemblies shall be individually preserved in accordance with MIL-P-116, Method III. Containers and waterproof sealing thereof shall be as specified in 3.3.2.2.9.1.

3.3.2.2.11 Hose and hose fittings. Hose and hose fittings shall be preserved and packaged as specified for Level A.

3.3.2.2.12 Lenses. Lenses shall be preserved as specified for Level A.

3.3.2.2.13 Lens plates. Lens plates shall be coated with preservative as specified in 3.3.1.2.13. The sets of plates shall be preserved together in accordance with MIL-P-116, Method IA-14. The containers and waterproof sealing of the outer containers shall be as specified in 3.3.1.2.13.

3.3.2.2.14 Shutter-control adapter plates. Shutter-control adapter plates shall be preserved in sets in accordance with MIL-P-116, Method IA-14. The containers and waterproof sealing of the outer containers shall be as specified in 3.3.1.2.13.

3.3.2.2.15 Nonelectric gages. Gages and indicators which are removed shall be individually preserved in accordance with MIL-P-116, Method III. Containers and waterproof sealing thereof shall be as specified in 3.3.2.2.9.1.

3.3.2.2.16 Darkroom-board assemblies and wood copyboards. Darkroom-board assemblies and wood copyboards shall be individually preserved in accordance with MIL-P-116, Method III. Containers and waterproof sealing thereof shall be as specified in 3.3.2.2.9.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

3.3.2.2.17 Curtains. Surfaces of the curtains shall be coated with preservatives as specified in 3.3.1.2.17. Each set of curtains shall be packaged in fiberboard boxes. Boxes and waterproof sealing thereof shall be as specified in 3.3.2.2.9.1.

3.3.2.2.18 Miscellaneous components. Miscellaneous components shall be preserved as specified for Level A.

3.3.2.2.19 Repair parts, accessories, tools, and technical publications for unassembled cameras. The repair parts, accessories, tools, and publications shall be preserved and packaged as specified in 3.3.1.2.19, 3.3.1.2.20, and 3.3.1.2.21.

3.3.2.2.20 Consolidated packaging for unassembled cameras. Consolidated packaging shall be as specified for Level A.

3.3.3 Level C. The cameras, assembled and unassembled, accessories, repair parts, maintenance tools, and technical publications shall be preserved and packaged to afford protection against deterioration and damage from the supplier to the initial destination for immediate use.

3.4 Packing. Packing shall be Level A, B, or C, as specified (see 6.2).

3.4.1 Level A.

3.4.1.1 Assembled cameras. Each assembled camera, preserved and packaged as specified, and consolidated packaged components, repair parts, accessories, tools, and publications shall be packed in a crate conforming to MIL-C-104, Type I, Class 1 or 2, Style A. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable; and, unless otherwise specified, shall be Finish B (see 6.2). When specified, Finish A strapping shall be used. Blocking, bracing, and anchoring of the crate contents shall be in accordance with the crate specification and MIL-STD-1186.

3.4.1.2 Unassembled cameras. Packaged and unpackaged components, repair parts, accessories, tools, and publications comprising each complete camera shall be packed in a crate conforming to MIL-C-104, Type I, Class 1 or 2, Style A. Blocking, bracing, and anchoring shall be provided to prevent movement and shall be in accordance with the crate specification and MIL-STD-1186. Strapping shall be as specified in 3.4.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

3.4.2 Level B.

3.4.2.1 Assembled cameras. Each assembled camera, preserved and packaged as specified, and consolidated packaged components, repair parts, accessories, tools, and publications shall be packed together in a crate conforming to MIL-C-3774, Type I, Style A. Blocking, bracing, and anchoring of the crate contents shall be in accordance with the crate specification and MIL-STD-1186.

3.4.2.2 Unassembled cameras. Packaged and unpackaged components, repair parts, accessories, tools, and publications comprising each complete camera, shall be packed in a crate conforming to MIL-C-3774, Type I, Style A. Blocking,bracing, and anchoring of the crate contents shall be in accordance with the crate specification and MIL-STD-1186.

3.4.3 Level C. The cameras, components, accessories, repair parts, tools, and publications, preserved and packaged as specified, shall be packed in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

3.5 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

3.6 Workmanship. All operations and processes involved in accomplishing the cleaning, preserving, packaging, packing, and marking requirements specified herein shall be in accordance with the highest grade practices associated with this type of work.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction pack for Level A or B shall be tested as follows: The pack shall be subjected to the railroad-car test as specified for guided impact tests in accordance with MIL-STD-1186, Appendix A. The car shall strike a string of five empty cars, with draft gear extended and the brakes set, at a speed of not less than 10 miles per hour or greater than 11 miles per hour.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers, and marking of completely preserved cameras prior to placing in the shipping containers.
(b) The second stage shall include inspection of materials, marking, blocking, and bracing of cameras and components in the containers prior to closing the shipping containers.
(c) The third stage shall include inspection of materials and marking after closing the shipping containers.

4.4.2 Unit of product. For the purpose of inspection a completed pack of any one level shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in Table I. Acceptable Quality Level (AQL) shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. Packs shall be examined for the following defects:

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:39Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects

	Defect	Level A	Level B	Level C
101.	Materials, methods, and containers not as specified for preservation, packaging, packing, and marking. Each incorrect material, method or container, shall constitute one defect (3.1, 3.3, 3.4, 3.5).	X	X	X
102.	Movable components of assembled cameras not positioned to realize minimum cube and the components not secured to prevent movement (3.3.1.1, 3.3.2.1).	X	X	-
103.	Consolidated packaging not as specified (3.3.1.1.4, 3.3.1.2.22, 3.3.2.1.6, 3.3.2.2.20.)	X	X	-
104.	Matchmarking of components of unassembled cameras not as specified (3.3.1.2.1, 3.3.2.2.1).	X	X	-
105.	Machined and precision metal surfaces not coated with preservative and the coated surfaces not wrapped or covered and the wraps or covers not secured as specified (3.3.1.2.3, 3.3.2.2.3).	X	X	-
106.	Exterior unpainted metal surfaces not coated with Type P-1 preservative as specified (3.3.1.2.4, 3.3.2.2.4).	X	X	-
107.	Surfaces of negative holders, positive holders, and screen holders not coated with preservative as specified, and the coated surfaces not wrapped or covered as specified, and the wraps or covers not secured as specified (3.3.1.2.5, 3.3.2.2.5).	X	X	-
108.	Surfaces of carriages not coated with preservative as specified, and surfaces coated with Type P-7 preservative not wrapped or covered as specified, and the wraps or covers not secured as specified (3.3.1.2.6, 3.3.2.2.6).	X	X	-
109.	Glass components not cleaned and wrapped as specified prior to preservation (3.3.1.2.8, 3.3.2.2.8).	X	X	-
110.	Sufficient cushioning not provided between glass and interior of boxes (3.3.1.2.8, 3.3.2.2.8).	X	X	-
111.	Interior surfaces of vacuum pumps not coated with preservative oil as specified (3.3.1.2.9.1, 3.3.2.1.3, 3.3.2.2.9.1).	X	X	-
112.	Openings into vacuum pumps and electric motors not sealed with tape as specified (3.3.1.2.9.1, 3.3.2.1.3, 3.3.2.2.9.1).	X	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects (Cont'd)

	Defect	Level A	Level B	Level C
113.	Diffuser-frames, trammel levels, and positioning plates not wiped with preservative as specified (3.3.1.2.9.2, 3.3.2.2.9.2).	X	X	-
114.	Surfaces of vacuum backs not coated with preservatives as specified, and the coated surfaces not wrapped or covered as specified, and the wraps or covers not secured as specified (3.3.1.2.9.3, 3.3.2.2.9.3).	X	X	-
115.	Method III containers not sealed with tape as specified (3.3.1.2.5, 3.3.1.2.6, 3.3.1.2.9.1, 3.3.1.2.9.2, 3.3.1.2.9.3, 3.3.1.2.10.3, 3.3.1.2.12, 3.3.1.2.13, 3.3.1.2.14, 3.3.1.2.15, 3.3.1.2.16, 3.3.1.2.17, 3.3.1.2.18, 3.3.2.2.5, 3.3.2.2.6, 3.3.2.2.7, 3.3.2.2.9.1, 3.3.2.2.9.2, 3.3.2.2.9.3, 3.3.2.2.10.1, 3.3.2.2.10.2, 3.3.2.2.13, 3.3.2.2.14, 3.3.2.2.15, 3.3.2.2.16, 3.3.2.2.17).	X	X	-
116.	Lens boxes not wrapped with cushioning as specified (3.3.1.2.12, 3.3.2.2.12).	X	X	-
117.	Lens plates not coated with preservative as specified, the preservative not drained as specified, and each plate not wrapped as specified, and wraps not secured as specified (3.3.1.2.13, 3.3.2.2.13).	X	X	-
118.	Shutter-control adapter plates not individually wrapped with paper as specified, and the wraps not secured as specified (3.3.1.2.14).	X	-	-
119.	Openings into cases enclosing gages and indicators not sealed as specified (3.3.1.2.15).	X	-	-
120.	Darkroom-board assemblies and wood copyboards not individually wrapped with paper as specified (3.3.1.2.16).	X	-	-
121.	Unpainted metal surfaces of curtain frames not coated with preservatives as specified, and surfaces coated with Type P-7 preservative not covered as specified and the covers not secured as specified (3.3.1.2.17, 3.3.2.2.17).	X	X	-
122.	Strapping not as specified (3.4.1.1, 3.4.1.2).	X	-	-
123.	Marking illegible, incomplete, or incorrect (3.5).	X	X	X

Source: https://assist.dla.mil -- Downloaded: 20261-16T18:39Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

(This section not applicable to this specification).

6. NOTES

6.1 Intended use. It is intended that this specification cover the requirements for preservation, packaging, packing, and marking of copying cameras and their accessories, and shall be used for reference in Section 5 of item specifications or for direct reference in contract or orders, or in the preparation of packaging data sheets.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) Level of preservation and packaging and level of packing required (see 3.3 and 3.4). Level B preservation and packaging (see 3.3.2 and 6.4) is intended to provide limited but economical protection and should be specified only when it is determined that the cameras and their accessories will be held in covered storage.
(d) When other than Finish B strapping is required (see 3.4.1.1 and 3.4.1.2).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the copying cameras and their accessories in accordance with this specification.

6.4 Level B preservation and packaging (see 3.3.2) has been developed for use by the Army and Air Force for the specific conditions specified in 6.2. For Navy procurements, details of Level B preservation and packaging, when required, should be developed at the time of procurement when all conditions are known.

Custodians:

Army - ME
Air Force - 70

User activities:

Navy - AS, MC

Preparing activity:

Army - ME

Review activities:

Army - GL, SM

Project No. 6720-0241

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-3615C Cameras, Copying, Lithographic, Packaging Of

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:39Z
Check the source to verify that this is the current version before use.