MIL-C-3607A
30 August 1961
SUPERSEDING
MIL-C-3607
12 October 1951

MILITARY SPECIFICATION

CONNECTORS, COAXIAL, RADIOFREQUENCY, SERIES PULSE,

GENERAL SPECIFICATION FOR

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 Scope. This specification covers the general requirements for weatherproof, high-voltage, series pulse, radiofrequency coaxial connectors. (See 6.1 and 6.3.)

1.2 Classification.

1.2.1 Type designation. The type designation of connectors is derived from the AN nomenclature system specified in Standard MIL-STD-196, and shall be as specified. (See 3.1 and 6.2.)

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

O-F-499 - Flux, Low Melting Point Silver Alloy Brazing.
QQ-B-613 - Brass, Leaded and Non-Leaded; Plate, Rolled Bar, Sheet and Strip.
QQ-B-626 - Brass, Leaded and Non-Leaded; Rods, Shapes, Forgings and Flat Products with Finished Edges (Bars, Flat Wire and Strips).
QQ-C-525 - Copper Alloy Ingots; (Leaded and Nonleaded Tin Bronze, Red Brass, and Semi-Red Brass).
QQ-C-530 - Copper-Beryllium Alloy Bars, Rods, and Wire.
QQ-C-533 - Copper-Beryllium Alloy Strip.
QQ-L-201 - Lead; Sheet.
QQ-N-290 - Nickel Plating (Electrodeposited).
QQ-P-330 - Phosphor Bronze Bars, Plates, Rods, Sheets, Strips, Flat Wire, and Structural and Special Shaped Sections.
QQ-P-416 - Plating, Cadmium (Electrodeposited).
QQ-S-365 - Silver Plating, Electrodeposited, General Requirements for.
QQ-S-561 - Solder; Silver.
QQ-S-571 - Solder: Lead Alloy, Tin Lead Alloy, and Tin Alloy; Flux Cored Ribbon and Wire, and Solid Form.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-585 - Boxes; Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set-Up, Paperboard.
PPP-T-76 - Tape, Pressure-Sensitive Adhesive, Paper, Water Resistant.
PPP-T-97 - Tape; Pressure-Sensitive Adhesive, Filament Reinforced.

MILITARY

MIL-I-10 - Insulating Materials, Electrical, Ceramic, Class L.
MIL-P-116 - Preservation, Methods of.
MIL-R-5847 - Rubber, Silicone; Low- and High-Temperature- and Tear Resistant.
MIL-I-8660 - Insulating and Sealing Compound, Electrical.
MIL-B-10377 - Box, Wood, Cleated, Veneer, Paper Overlaid.
MIL-L-10547 - Liners, Case, Waterproof.
MIL-T-10727 - Tin Plating; Electrodeposited or Hot-Dipped, for Ferrous and Nonferrous Metals.

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

MIL-R-15624 - Rubber Sheets; and Cut, Molded and Extruded Special Shaped Sections - Synthetic, Medium Soft, Shipboard Gasket Use Except Low Temperature Application.
MIL-S-16410 - Steel, Spring: Bars and Wire.

(For applicable detail specifications, see Supplement 1.)

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U. S. Military Property.
MIL-STD-196 - Joint Electronics Type Designation System.
MIL-STD-202 - Test Methods for Electronic and Electrical Component parts.

(Copies of specifications, detail specifications, and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS
Handbook H28 - Screw-Threaded Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

OFFICIAL CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules.

(Application for copies should be addressed to the Official Classification Committee, One Park Avenue, at 33rd Street, New York 16, N.Y.)

3. REQUIREMENTS

3.1 Detail requirements for individual connector types. Detail requirements or exceptions applicable to individual types of connectors shall be as specified in the detail specifications listed in Supplement 1 to this specification. In the event of any conflict between requirements of this specification and the detail specifications, the latter shall govern. (See 6.2.)

3.2 Material. The material shall be as specified herein. (See 3.1.) However, when a definite material is not specified, a material shall be used which will enable the connectors to meet the performance requirements of this specification. Acceptance or approval of any constituent material shall not be construed as a guaranty of the acceptance of the finished product.

3.2.1 Brass. Brass shall conform to composition 11, half-hard, of Specification QQ-B-613, or composition 22, half-hard, of Specification QQ-B-626, as applicable.

3.2.2 Ceramic. Ceramic shall conform to grade L-211 of Specification MIL-I-10, or better. Unless otherwise specified (see 3.1), parts made of ceramic shall be glazed.

3.2.3 Copper-alloy ingots. Copper-alloy ingots shall conform to composition 2, of Specification QQ-C-525.

3.2.4 Copper beryllium. Copper beryllium shall conform to condition H of Specification QQ-C-530 or QQ-C-533, as applicable. After machining and forming, parts fabricated of copper beryllium shall be heat-treated to condition HT.

3.2.5 Insulating and sealing compound. Insulating and sealing compound shall conform to Specification MIL-I-8660.

3.2.6 Lead. Lead shall conform to grade B of Specification QQ-L-201.

3.2.7 Phosphor bronze. Phosphor bronze shall conform to composition A of Specification QQ-P-330.

3.2.8 Plating.

3.2.8.1 Cadmium. Cadmium plating shall conform to class 3, type II, of Specification QQ-P-416.

3.2.8.2 Nickel. Nickel plating shall conform to class 1, type V (FC), bright, of Specification QQ-N-290.

3.2.8.3 Silver. Silver plating shall conform to Specification QQ-S-365.

3.2.8.4 Tin. Tin plating shall conform to Specification MIL-T-10727.

3.2.9 Rubber sheet. Rubber sheet shall conform to class I of Specification MIL-R-15624.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

3.2.10 Silicone rubber. Silicone rubber shall conform to class IIa, grade 50 or 60, of Specification MIL-R-5847, except that the oil immersion test is not applicable.

3.2.11 Silver solder. Silver solder shall conform to class 1 of Specification QQ-S-561.

3.2.11.1 Flux. Flux used while silver soldering shall conform to Specification O-F-499.

3.2.12 Soft solder. Soft solder shall conform to composition Sn60 of Specification QQ-S-571.

3.2.13 Spring steel. Spring steel shall conform to grade A, type II, of Specification MIL-S-16410.

3.3 Design and construction. Connectors shall be of the design, construction, and physical dimensions specified. (See 3.1.) Wherever feasible, parts having similar electrical characteristics may be combined (fabricated as a single piece) to simplify construction. Parts of unlike materials may be combined such as brass and copper beryllium, provided copper beryllium is used in the fabrication of the single-piece construction.

3.3.1 Metal parts. Unless otherwise specified (see 3.1), all metal parts shall have a silver plating of not less than 0.0005 inch thick, of sufficient smoothness and density to withstand the salt-spray (corrosion) test specified in 4.6.4. All other types of plating shall be as specified. (See 3.1.) Dimensions of metal parts shall include the plating. (See 3.1.)

3.3.2 Screw threads. Screw threads shall conform to Handbook H28, and shall have the specified fit after plating. (See 3.1.)

3.3.3 Gage tests for contacts of rubber-insert type.

3.3.3.1 Center contacts (female). The center contacts shall meet the gage tests specified in 4.6.1.1 as piece parts and 4.6.1.2 in the assembled connector.

3.3.3.2 Outer contacts. The outer contacts shall meet the gage tests specified in 4.6.1.2.2 in the assembled connector.

3.3.3.2.1 Outer contact solder joint. When outer contacts are tested as specified in 4.6.1.3, there shall be no signs of loosening.

3.3.4 Assembly and rotation. When tested as specified in 4.6.1.4, the assembled coupling nuts for electrical plug connectors and connector adapters shall not disengage. In addition, a torque of 0.75 inch-pounds maximum shall rotate the coupling nut, when applied as specified in 4.6.1.4.

3.4 Dielectric withstanding voltage. When connectors are tested as specified in 4.6.2, there shall be no evidence of breakdown.

3.5 Leakage (applicable only to pressurized connectors). When connectors are tested as specified in 4.6.3, there shall be no evidence of loss of pressure as detected by escaping air bubbles.

3.6 Salt spray (corrosion). When connectors are tested as specified in 4.6.4, there shall be no evidence of destructive corrosion or pitting. Destructive corrosion shall be construed as any type of corrosion which in any way interferes with mechanical or electrical performance.

3.7 Marking. Connectors shall be marked in accordance with Standard MIL-STD-130, with the type designation and the manufacturer's code symbol. Marking shall be in depressed characters approximately 3/32 inch high, in the place specified. (See 3.1.)

3.8 Workmanship. Connectors shall be processed in such a manner as to be uniform in quality and shall be free from sharp edges, burrs, and other defects that will affect life, serviceability, or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.1.1.1 Test equipment and inspection facilities. Test equipment and inspection facilities shall be of sufficient accuracy, quality, and quantity to permit performance of the required inspection. The supplier shall establish calibration of inspection equipment to the satisfaction of the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The examination and testing of connectors shall be classified as follows:

(a) Component-materials inspection. (See 4.3.)
(b) Acceptance inspection. (See 4.5.)
1. Inspection of product for delivery. (See (See 4.5.1.)
2. Inspection of preparation for delivery. (See 4.5.2.)

4.3 Component-materials inspection. Component-materials inspection shall consist of verification that the component materials listed in table I, used in fabricating the connectors, are in accordance with the applicable referenced specifications or requirements prior to such fabrication.

Table I. Component-materials inspection.

Component material	Requirement paragraph	Applicable specification
Brass	3.2.1	QQ-B-613 or QQ-B-626
Ceramic	3.2.2	MIL-I-10
Copper-alloy ingots	3.2.3	QQ-C-525
Copper beryllium	3.2.4	QQ-C-530 or QQ-C-533
Insulating and sealing compound	3.2.5	MIL-I-8660
Lead	3.2.6	QQ-L-201
Phosphor bronze	3.2.7	QQ-P-330
Plating:		
Cadmium	3.2.8.1	QQ-P-416
Nickel	3.2.8.2	QQ-N-290
Silver	3.2.8.3	QQ-S-365
Tin	3.2.8.4	MIL-T-10727
Rubber sheet	3.2.9	MIL-R-15624
Silicone rubber	3.2.10	MIL-R-5847
Silver solder	3.2.11	QQ-S-561
Flux	3.2.11.1	O-F-499
Soft solder	3.2.12	QQ-S-571
Spring steel	3.2.13	MIL-S-16410

4.4 Inspection conditions. Unless otherwise specified herein, all inspection shall be made at room ambient temperature, relative humidity, and pressure.

4.5 Acceptance inspection.

4.5.1 Inspection of product for delivery. Inspection of product for delivery shall consist of groups A, B, and C.

4.5.1.1 Inspection lot. An inspection lot, as far as practicable, shall consist of all the connectors of the same type designation, produced under essentially the same conditions, and offered for inspection at one time.

4.5.1.2 Resubmitted lots. If an inspection lot is rejected, the supplier may replace it with a new lot, rework it to correct the defects, or screen out the defective units, and submit it again for inspection. Resubmitted lots shall be kept separate from new lots and shall be clearly identified as resubmitted lots. Resubmitted lots shall be inspected, using tightened inspection.

4.5.1.3 Group A inspection. Group A inspection shall consist of the examinations and test specified in table II, and shall be made on the same set of sample units.

4.5.1.3.1 Sampling plan. Statistical sampling and inspection shall be in accordance with Standard MIL-STD-105 for ordinary inspection. The acceptable quality levels (AQL) shall be as specified in table II. Major and minor defects shall be as defined in Standard MIL-STD-105.

4.5.1.4 Group B inspection. Group B inspection shall consist of the examinations and test specified in table III, in the order shown, and shall be made on sample units which have passed group A inspection. A different set of sample units shall be selected for each subgroup.

4.5.1.4.1 Sampling plan. The sampling plan shall be in accordance with Standard MIL-STD-105 for small-sample inspection. Unless otherwise specified herein, normal inspection shall be used at the start of the contract. For small-sample reduced

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

Table II. Group A inspection.

Examination or test	Requirement paragraph	Method paragraph	AQL (percent defective)	
			Major	Minor
Visual and mechanical examination:	---	4.6.1	1.0	4.0
Marking	3.7	---		
Workmanship[1/]	3.8	---		
Gage tests for contacts (assembled connectors:				
Center contacts (female)	3.3.3.1	4.6.1.2.1	1.0	---
Outer contacts	3.3.3.2	4.6.1.2.2	1.0	---
Dielectric withstanding voltage	3.4	4.6.2	1.0	---

1/ Assembly, fit of parts, and plating coverage.

Table III. Group B inspection.

Examination	Requirement paragraph	Method paragraph	AQL (percent defective)	Inspection level	
				Normal and tightened inspection	Reduced inspection
Subgroup 1					
Visual and mechanical examination:	---	4.6.1			
Outer contact solder joint.	3.3.3.2.1	4.6.1.3	4.0	L8	L6
Assembly and rotation.	3.3.4	4.6.1.4			
Subgroup 2					
Leakage (applicable only to pressurized connectors).	3.5	4.6.3	4.0	L8	L6
Subgroup 3					
Visual and mechanical examination:	---	4.6.1	---	---	---
Physical dimensions[1/]	3.3	---	6.5	L7	L5

1/ Only those dimensions specified (see 3.1), shall be checked.

inspection, procedure R-1 shall be used. The AQL and inspection levels shall be as specified in table III.

4.5.1.5 Disposition of sample units. Sample units which have passed the groups A and B inspection may be delivered on the contract or order, if the lot is accepted.

4.5.1.6 Group C inspection. Group C inspection shall consist of the examinations and test specified in table IV.

4.5.1.6.1 Sampling plan.

4.5.1.6.1.1 Subgroup 1 (unassembled connectors). Equivalent piece parts for six sample units of each type connector shall be selected from the first lot produced. Thereafter, for each 500 connectors subsequently produced, piece parts for one sample unit shall be selected.

4.5.1.6.1.1.1 Physical dimensions. To facilitate inspection of the physical dimensions, the unassembled sample units shall be divided into groups

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

Table IV. Group C inspection.

Examination or test	Requirement paragraph	Method paragraph
Subgroup 1 (unassembled connectors)		
Visual and mechanical examination:	---	4.6.1
Design and construction:		
Physical dimensions[1/]	3.3	4.5.1.6.1.1.1
Gage tests for contacts	3.3.3	4.6.1.1 to 4.6.1.1.1.2, incl
Subgroup 2 (assembled connectors)		
Salt spray (corrosion)	3.6	4.6.4

[1/] Only those dimensions related to piece parts (other than gage tests for contacts) shall be checked.

of identical piece parts. Inspection of the physical dimensions shall then be performed on a group-by group basis.

4.5.1.6.1.1.2 Acceptance criteria. The acceptance criteria shall be determined as follows:

(a) For each piece part containing five or more specified dimensions, the number of dimensional defects in a group shall not exceed one. A total of not more than 10 defects per 100 specified dimensions will be accepted.

(b) No defects shall be permitted for piece parts containing less than five dimensions. In addition, no defects shall be permitted for material, plating of metal parts, and screw threads; and no failures shall be permitted in the gage tests for contacts.

4.5.1.6.1.2 Subgroup 2 (assembled connectors). Six sample units of each type connector shall be selected from the first lot produced. Thereafter, for each 500 connectors subsequently produced, one sample unit shall be selected. If any failures occur during this test, the sample shall be rejected.

4.5.1.6.2 Disposition of sample units. Sample units which have been subjected to group C inspection, subgroup 2, shall not be delivered on the contract or order.

4.5.1.6.3 Noncompliance. If a sample fails to pass group C inspection, the supplier shall take corrective action on the materials or process, or both, as warranted, and on all units of product which can be corrected and which were manufactured under essentially the same conditions, with essentially the same materials, processes, etc, and which are considered subject to the same failure. Acceptance of the product shall be discontinued until corrective action, acceptable to the Government, has been taken. After the corrective action has been taken, group C inspection shall be repeated on additional sample units (all inspection, or the inspection which the original sample failed, at the option of the Government). Groups A and B inspection may be reinstituted; however, final acceptance shall be withheld until the group C reinspection has shown that the corrective action was successful. In the event of failure after reinspection, information concerning the failure and the corrective action taken shall be furnished to the contracting officer.

4.5.2 Inspection of preparation for delivery. Sample items and packs shall be selected and inspected in accordance with Specification MIL-P-116 to verify conformance with requirements in section 5 of this specification.

4.6 Methods of examination and test.

4.6.1 Visual and mechanical examination. Connectors shall be examined to verify that the design, construction, physical dimensions, marking, and workmanship are in accordance with the applicable requirements. (See 3.1, 3.3 to 3.3.4, incl, 3.7, and 3.8.)

4.6.1.1 Gage tests for contacts of rubber-insert type (piece parts).

4.6.1.1.1 Center contacts (female). The center contacts shall be subjected to the gage tests specified in 4.6.1.1.1.1 and 4.6.1.1.1.2, as applicable, prior to assembling the center contact in the connector. The pins used in the performance of these tests may be tapered at their ends to facilitate insertion, but the tapered portions shall not be included in the specified dimensions. (See 3.3.3.1.)

4.6.1.1.1.1 Test 1. A pin 0.098 inch minimum in diameter shall be inserted into the center contact to a depth of not less than 3/16 inch, and then removed. All four contact members shall make contact with a pin 0.072 inch maximum in diameter, within 1/32 inch of their tip ends, when this pin is inserted to a minimum depth of 3/16 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

4.6.1.1.1.2 Test 2. When a pin 0.082 inch minimum in diameter is inserted to a minimum depth of 1/4 inch, the contact shall pass through a cylindrical hole 0.128 inch maximum in diameter and 1/2 inch minimum in length, when a maximum force of 2 pounds is applied. This test shall be applied only to those connectors with removable female contacts.

4.6.1.2 Gage test for contacts of rubber-insert type (assembled connectors).

4.6.1.2.1 Center contacts (female). The center contacts shall accept a pin 0.072 inch diameter, when a minimum force of 1 pound is applied.

4.6.1.2.2 Outer contacts. The outer contacts assembled to the body shall be subjected to the gage test specified in 4.6.1.2.2.1 and 4.6.1.2.2.2. (See 3.3.3.1.)

4.6.1.2.2.1 Test 1. All contact fingers of the outer spring of the plug shall make contact with a ring having a minimum inside diameter of 0.820 inch when this ring is placed over the assembly of the body and spring.

4.6.1.2.2.2 Test 2. The outer contacts shall be inserted into a polished sleeve 0.810 inch maximum in inside diameter to a minimum depth of 7/16 inch. The contacts shall then disengage from the sleeve when a maximum pressure of 4 pounds is applied.

4.6.1.3 Outer contact solder joint. A withdrawal force of 25 pounds shall be applied to the outer contact. The force shall be applied to and in the direction away from the connector body and along the longitudinal axis. (See 3.3.3.2.1.)

4.6.1.4 Assembly and rotation. The assembled coupling nut shall be subjected to a force of 100 pounds gradually applied relative to and in a direction from the connector body and along a longitudinal axis. A torque shall then be applied to the coupling nut about the axis of symmetry. The torque shall be measured with a 0-2-inch pound torque wrench. (See 3.3.4.)

4.6.2 Dielectric withstanding voltage (see 3.4). Connectors shall be tested in accordance with method 301 of Standard MIL-STD-202. The following details shall apply:

(a) Special preparations or conditions:
1. The maximum relative humidity shall be 50 percent. When facilities are not available at this test condition, connectors shall be tested at room ambient relative humidity. In case of dispute, if the test has been made at room ambient relative humidity, retest shall be made at 50 percent maximum relative humidity.
2. The center contact of plug connectors and receptacle connectors shall be positioned in such a manner as to simulate actual assembly conditions.
3. Precautions shall be taken to prevent air-gap voltage breakdowns.
4. The voltage shall be metered on the high side of the transformer.

(b) Magnitude of test voltage - (See 3.1.)
(c) Nature of potential - Alternating current.
(d) Points of application of test voltage - Between the center contact and the body.

4.6.3 Leakage (applicable only to pressurized connectors). The connectors shall be subjected to a gage pressure of 50 pounds-per-quare-inch applied to one end, and the whole connector immersed in water at approximately 20° C. The connector shall remain immersed in water for at least 20 seconds. (See 3.5.)

4.6.4 Salt spray (corrosion). Connectors shall be tested in accordance with method 101, test condition B, of Standard MIL-STD-202. At the conclusion of this test, the connectors shall be washed, shaken, air blasted, and then permitted to dry for 24 hours at 40° C. The connectors shall then be examined for evidence of corrosion. (See 3.6.)

PREPARATION FOR DELIVERY

5.1 Preservation and packaging (see 6.2.).

5.1.1 Level A. Unless otherwise specified (see 6.2), connectors shall be individually protected and unit-packaged in accordance with method IA of Specification MIL-P-116, without the use of contact preservatives. Prior to packaging, the parts of the connector shall be completely assembled wherever practical. All center contacts, where loose, shall be securely fastened to the body of the connector by wire or other approved method. Unless otherwise specified (see 6.2), five unit packages or a multiple thereof shall be further packaged in intermediate containers conforming to Specification PPP-B-566, class 1 of PPP-B-636, PPP-B-665, or PPP-B-676. The gross weight of the intermediate container shall not exceed 10 pounds.

5.1.2 Level C.. Connectors shall be afforded preservation and packaging in accordance with the supplier's normal commercial practice.

5.2 Packing (see 6.2).

5.2.1 Level A. Connectors packaged as specified (see 6.2) shall be packed in overseas-type wire-bound wood, wood-cleated fiberboard, wood-cleated plywood, nailed wood, fiber (class 2 or 3), or wood-cleated paper-overlaid boxes conforming to Specifications PPP-B-585, PPP-B-591, PPP-B-601,

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

PPP-B-621, PPP-B-636, and MIL-B-10377, respectively, at the option of the supplier. Shipping containers shall have case liners conforming to Specification MIL-L-10547; the case liners shall be closed and sealed in accordance with the appendix thereto. Case liners for boxes conforming to Specification PPP-B-636 will not be required provided the center and edge seams and manufacturers' joints are sealed with tape, at least 1-1/2 inches wide, conforming to Specification PPP-T-76. Box closures and strapping shall be as specified in the applicable box specification or appendix thereto. Fiber boxes conforming to Specification PPP-B-636 may be banded with tape conforming to type IV of Specification PPP-T-97 and appendix thereto in lieu of steel straps. The gross weight of wood boxes shall not exceed 200 pounds; fiber-board boxes shall not exceed the weight limitations of the applicable box specification.

5.2.2 Level B. Connectors packaged as specified (see 6.2) shall be packed in domestic-type wirebound wood, wood-cleated fiberboard, wood-cleated plywood, nailed wood, fiber (class 1 or 2, as specified (see 6.2)), or wood-cleated paper-overlaid boxes conforming to Specifications PPP-B-585, PPP-B-591, PPP-B-601, PPP-B-621, PPP-B-636, and MIL-B-10377, respectively, at the option of the supplier. Box closures shall be as specified in the applicable box specification or appendix thereto. The gross weight of wood boxes shall not exceed 200 pounds; fiberboard boxes shall not exceed the weight limitations of the applicable box specification.

5.2.3 Level C. Connectors packaged as specified (see 6.2) shall be packed in containers of the type, size, and kind commonly used for the purpose, in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the Uniform Freight Classification Rules, or regulations of other carriers as applicable to the mode of transportation.

5.2.4 General. Insofar as possible and practical, exterior containers shall be uniform in shape and size, shall be of minimum cube and tare consistent with the protection required, and shall contain identical quantities of identical items.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and exterior shipping containers shall be marked in accordance with Standard MIL-STD-129. (See 6.2.)

6. NOTES

6.1 Intended use. Connectors covered by this specification are intended for use in radio frequency applications up to 100 megacycles per second. They are designed for use with radiofrequency pulse cables. Their use is governed by temperature limitation of materials, and they are not recommended for use in applications where temperatures exceed 175° C.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Title, number, and date of the applicable detail specification, and the complete type designation. (See 1.2.1 and 3.1.)
(c) That the supplier shall not substitute for a specified material or combination of fabricated parts (see 3.3) unless he obtains approval from the Government. Evidence to substantiate his claim that such a substitution is suitable shall be submitted with his request. Similar notification and substantiating evidence shall be submitted at any later time if substitution becomes necessary or desirable. At the discretion of the Government, sample units may be required to prove the suitability of the proposed substitute.
(d) Levels of preservation and packaging and packing, and applicable marking. (See sect 5.)
(e) Method of preservation and packaging of Specification MIL-P-116, if other than method IA. (See 5.1.1.)
(f) Number of unit packages if other than that specified in 5.1.1.
(g) Class of fiber. (See 5.2.2.)

6.3 Engineering information. Illustrations and additional engineering information for this series of connectors are available in the Armed Services Index of R. F. Transmission Lines and Fittings, copies of which are available upon request from the Armed Services Electro-Standards Agency (ASESA), Fort Monmouth, N. J.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army - Signal Corps
Navy - Bureau of Ships
Air Force - AFSC

Preparing activity:
Navy - Bureau of Ships
(Project 5935-0167)

☆U.S. GOVERNMENT PRINTING OFFICE: 1976— 603-766:5728

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:35Z
Check the source to verify that this is the current version before use.