INCH-POUND

MIL-C-48396A (AR)
AMENDMENT 2
06 May 1993
SUPERSEDING
AMENDMENT 1
11 March 1988

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M752A1 PARTS FOR

This Amendment forms a part of MIL-C-48396A (AR), dated 30 June 1986, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, Change "M853" to "M853A1"

2.1.1, Add "MIL-STD-810 Environmental Test Methods"

PAGE 2

3.2, Add the following paragraph:

"3.2.1 Corrosion resistance (salt spray). Parts selected for the salt spray test shall show no evidence of pitting or mottling when tested in accordance with 4.5.2."

PAGE 8

* 4.4.2.2, Major 108: Delete in its entirety and substitute the following:

"108 ..Diameter of flashhole rear of pellet cavity ...0.40% ...3.2 ...Gage"

* Major 109, Delete in its entirety.



AMSC N/A

FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the currentversion before use.

PAGE 9

* 4.4.2.2, Major 126: Delete in its entirety.

Under Major category, add the following:

"129 ..Salt spray test ...(a) ...3.2.1 ...Visual/4.5.2

Note (a) See sampling plans described in paragraph 4.4.3.2"

* "130 ..Inside chamfer at entrance of primer cavity incorrect ...0.40% ...3.2 ...Gage"

PAGE 13

* 4.4.2.5, Major 103, add "to forward outside diameter and rear face" after "True position of flash holes"

* Major 113, Delete in its entirety.

Under Major category, add the following:

"114 ..Salt spray test ...(a) ...3.2.1 ...Visual/4.5.2

Note (a) See sampling plans described in 4.4.3.2"

PAGE 14

* 4.4.2.6, Major 101, delete "Outside diameter" and substitute "Forward outside diameter (OD)"

* Major 103, delete "Depth of groove" and substitute "Rear OD"

* Major 104, delete "Width of groove" and substitute "Distance from rear face to shoulder"

* Major 107, delete examination callout in its entirety and substitute "True position of cavity with rear OD"

* Major 109, delete examination callout in its entirety and substitute "True position of forward OD with rear OD"



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the currentversion before use.

PAGE 14 (Cont'd)

* Add Major 110 and 111 as follows:

"110 ..Radius at bottom of cavity over maximum ...0.40% ...3.2 ...Gage

111 ..Marking missing ...0.40% ...3.2 ...Visual"

Add Minor 204 as follows:

"204 ..Marking incomplete or illegible ...0.65% ...3.2 ...Visual"

PAGE 15

4.4.3, Add the following paragraph:

"4.4.3.2 Salt spray test (3.2.1)

4.4.3.2.1 Sampling plan. Each batch of parts anodized at the same time with the same equipment shall be considered as an anodizing lot. For the first three (3) batches, the sampling plan for this test shall be in accordance with MIL-STD-105, Table IIA, inspection level II at AQL of 0.25%. Successive lots shall be sampled as above except that level I shall apply. If a continuous anodizing process is used, the engineering activity shall provide an alternate sampling plan after details of the process are provided by the contractor. The test shall be performed as specified in 4.5.2."



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the current version before use.

* 4.5, Add the following paragraph:

"4.5.2 Salt spray test. Samples selected shall be tested using equipment and procedures in accordance with MIL-STD-810, Method 509.2, Salt Fog. Parts shall be tested with the black powder pellet end up and the pellet cavity or contact surface inclined approximately six degrees from the vertical in fixturing which does not obstruct the longitudinal flashole. Parts shall be tested for 96 hours minimum. After testing, parts shall be rinsed, dried and examined for evidence of pitting or mottling of the finish. Particular attention shall be paid to the black powder pellet cavity inside the body. The technique used to inspect the cavity must be capable of thoroughly inspecting all surfaces of the cavity (face, walls, inside and outside corners), otherwise the body shall be transversely sectioned approximately 1.75 inches from the front face in order to facilitate visual inspection. The cutting tool (if used) must not remove any part of the pellet cavity. One or more pits or mottling shall be cause for rejection of all anodized parts represented by the sample. Parts subjected to salt shall not be returned to the lot."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AE80 )



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:24Z
Check the source to verify that this is the current version before use.