MIL-C-55571A
15 June 1982
SUPERSEDING
MIL-C-55571(EL)
31 October 1967

MILITARY SPECIFICATION

CASE, MERCURIAL BAROMETER ML-48( )

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of case used as a wall cabinet to house and provide ready access to a mercurial barometer; designated Case, Mercurial Barometer ML-48( ).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

C-F-206	- Felt Sheet, Cloth, Felt, Wool, Pressed.
NN-P-530	- Plywood, Flat, Panel.
QQ-Z-325	- Zinc, Coating, Electrodeposited, Requirements for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Electronics Research and Development Command, ATTN: DELCS-PE, Fort Monmouth, NJ 07703, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6660

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Perservation, Methods of.
MIL-F-2312	- Felt, Cattle Hair or Wool, Mildew Resistant, and Moisture Resistant, Treated.
MIL-M-13231	- Marking of Electronic Items.
MIL-F-14072	- Finishes for Ground Signal Equipment.
MIL-E-55585	- Electronic Equipment and Parts, Packaging of.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.
MIL-STD-726	- Packaging Requirements Code.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein:

NATIONAL BUREAU OF STANDARDS

Handbook H28	- Screw-Thread Standards for Federal Services.

DRAWINGS

ELECTRONICS COMMAND

SC-A-47794	- Wood Guide.
SC-DL-86434	- Case, Mercurial Barometer ML-48( )

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article samples. When specified, the contractor shall furnish sample units for first article inspection and approval (see 4.3 and 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3.2 Construction. The equipment shall be constructed in accordance with SC-DL-86434, including the requirements for parts, materials, and processes thereon.

3.2.1 Recycled, virgin and reclaimed materials. Without jeopardizing the intended use of equipment furnished to this specification, selection of materials will be governed by the following:

a. There is no exclusion to the use of recovered materials.
b. There is no requirement that equipment be manufactured from virgin materials.
c. Reclaimed materials are required to the maximum extent possible.

3.3. Finish. The equipment shall be finished in accordance with MIL-F-14072 and the equipment drawings.

3.4 Marking. Marking shall conform to MIL-M-13231 and the equipment drawings.

3.5 Interchangeability. Like units, assemblies, subassemblies, and replaceable parts shall be physically and functionally interchangeable, without modification of such items or of the equipment.

3.6 Felt. Wool felt shall conform to C-F-206 and shall be given type III treatment in accordance with MIL-M-2312.

3.7 Plywood. Plywood shall be Douglas Fir or hardwood plywood conforming to NN-P-530 and SC-A-47794.

3.8 Adhesives. Adhesives and their application shall conform to requirement 23 of MIL-STD-454.

3.9 Cleaning.

3.9.1 Parts. After fabrication, parts shall be cleaned in accordance with requirement 9 of MIL-STD-454, or as specified in an applicable document.

3.9.2 Units. After assembly, units shall be cleaned thoroughly and shall be free from particles of grease, sand, metal chips, and other foreign material; when necessary such cleaning shall be performed before final assembly.

3.10 Securing of Parts.

3.10.1 General. Brackets, lugs, inserts, and other mounting arrangements shall be such as to retain items securely when subjected to normal service conditions.

3.10.2 Screws and related parts. Unless otherwise specified, screw threads shall conform to Handbook H28.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3.10.2.1 Material. Where permitted by design considerations, and unless otherwise specified, screws and related hardware shall be of carbon steel having zinc coating conforming to QQ-Z-325, or of corrosion-resistant steel, passivated.

3.11 Workmanship. Workmanship shall be in accordance with requirement 9 of MIL-STD-454 and the applicable portions of the following paragraphs herein:

a.	Felt	3.6
b.	Plywood	3.7
c.	Adhesives	3.8
d.	Cleaning	3.9
e.	Securing of parts, general	3.10.1
f.	Screws and related parts	3.10.2
g.	Material	3.10.2.1

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3) (does not include packaging).
b. Inspections covered by subsidiary documents (see 4.4).
c. Quality conformance inspection.

(1) Quality conformance inspection of equipment before packaging (see 4.5).
(2) Quality conformance inspection for packaging (see 4.8).

4.3 First article inspection. Unless otherwise specified in the contract, the first article inspection shall be performed by the contractor. It shall consist of the inspection specified in the subsidiary documents covering the items listed in 4.4 and the group A inspection specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.4 Inspections covered by subsidiary documents. The following shall be inspected under the applicable documents as part of the inspection required by this specification, and the inspection requirements specified in the contract:

Item	Requirement paragraph
Finish	3.3
Marking	3.4
Workmanship	3.11

4.5 Quality conformance inspection of equipment before packaging. The contractor shall perform the inspection specified in 4.4 and 4.5.1. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements.

4.5.1 Group A Inspection. Each unit on contract shall be inspected for conformance to the inspection in table I. Discrete lots shall be formed from units that pass this inspection. Factors of lot composition not defined herein, or in the contract, shall be in accordance with MIL-STD-105. Each lot shall be subject to sampling inspection, utilizing the procedures of MIL-STD-105, using the general inspection levels and AQLs indicated in table I.

TABLE I. Group A inspection.

Inspection	Requirement paragraph	Test method paragraph	AQL(% defective)	
			Major	Minor
Visual-mechanical	3.11	4.7	1.0	4.0
Interchangeability	3.5	4.6	1.0	4.0

4.6 Inspection for dimensional interchangeability. The dimensions listed below shall be gaged or measured to determine conformance to the physical interchangeability requirements of 3.5. When listed dimension is not within specified or design limits, it shall be considered a major defect.

a. External and internal dimensions of cases, covers, and insertable assemblies, when such dimensions affect mating of parts.
b. Dimensions of cavities, when such dimensions affect insertion of items.
c. Location of hinges and fasteners on separable parts or assemblies which must mate, such as cases, covers, and mountings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.7 Visual and mechanical inspection. Equipment shall meet the requirements of 3.11.

4.8 Quality conformance inspection of packaging. Packaging shall be inspected in accordance with MIL-P-116 to determine conformance to the requirements of section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be as specified in MIL-STD-726, coded as follows:

5.1.1 Level A. 2M-1-1-ØØ-DC-NR-X-ED-Ø-00-A

5.1.2 Level B. 1Ø-1-1-ØØ-DC-NS-X-ED-Ø-00-B

5.2 Packing and marking. Packing and marking shall be in accordance with MIL-E-55585.

6. NOTES

6.1 Intended use. The Case, Mercurial Barometer ML-48( ) is intended to be used as a wall cabinet to house and provide ready access to a mercurial barometer.

6.2 Ordering Data. Procurement documents should specify the following:

a. Title, number, and date of this specification and any amendment thereto.
b. Level A or B preservation and packing (see section 5).
c. When rough handling tests are not required (see 4.8).
d. The contractor should apply for nomenclature in accordance with the applicable clause in the contract.
e. Marking and shipping of samples.
f. Place of final inspection.
g. Number of first articles, if required, to be submitted for approval (see 3.1).

6.3 Nomenclature. The parentheses in the nomenclature will be deleted and replaced by a letter identifying the particular design, for example ML-48W (see 1.1). The contractor should apply for nomenclature in accordance with the applicable clause in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

6.4 Verification inspection. Verification by the Government will be limited to the amount deemed necessary to determine compliance with the provisions established in this specification and the contract.

Custodians:
Army - ER
Air Force - 99

Review activities:
Navy - AS
Air Force - 80

Preparing activity:
Army - ER

(Project 6660-0063)

☆U.S. GOVERNMENT PRINTING OFFICE: 1982—505-022/3348

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-55571A CASE, MERCURIAL BAROMETER ML-48( )

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND
COMBAT SURVEILLANCE AND TARGET ACQUISITION LABORATORY
ATTN: DELCS-PE
FORT MONMOUTH, NEW JERSEY 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.