MIL-C-51212B
30 June 1967
SUPERSEDING
MIL-C-51212A(MU)
2 November 1966

MILITARY SPECIFICATION

CALCULATOR, DOWNWIND TOXIC VAPOR HAZARD, LINE SOURCE, ABC-M3

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of chemical agent calculator.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-636	-	Box, Fiberboard.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

MILITARY

MIL-P-116	-	Preservation, Methods of.

FSC 6665

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL5-86-10	-	Calculator, Downwind Toxic Vapor Hazard, Line Source, ABC-M3.

(All drawings referenced in this specification, with the exception of D150-2-1, are listed on the above Edgewood Arsenal drawing.)

D150-2-1	-	Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules, and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-86-10 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings. The ink used for marking and lettering shall be compatible with the vinyl chloride material. The printing shall be legible, non-fading, and durable.

3.1.2 Components. All components of the calculator shall conform to the specifications and drawings listed on Drawing DL5-86-10 and subsidiary drawings.

3.2 Manufacture and assembly. The calculator shall be manufactured and assembled in accordance with Drawing C5-86-10.

3.3 Functioning. The calculator, when tested in accordance with 4.3.4, shall be capable of solving problems for downwind toxic hazard distances using the data listed in table I.

Table I. Problem data

Scale	Data		
	Problem 1	Problem 2	Problem 3
Source strength, kg per meter (Q)	2.26	1.20	2.26
Wind speed, meters per minute (U)	214	26.8	107
Line source length, kilometers (L)	0.4	2.0	0.2
Dosage, mg - minute per cubic meter (D)	75	45	100
Temperature gradient ($\triangle$TG), °F	0	-2	+2
Downwind hazard distance, kilometers	3.0 $\pm$ 0.3	0.56 $\pm$ 0.06	17 $\pm$ 2

3.4 Preproduction. Prior to the start of regular production, a preproduction sample of ABC-M3 calculators shall be produced in accordance with this specification for examination and test (see 4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. The calculator shall be free from imperfections such as pits, bumps, cracks, flash, abrasions, blisters, holes or porous areas and foreign matter (dirt, grease, or oil). All surfaces shall be smooth and laminations shall be uniform without unsealed areas.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Preproduction.

4.2.1 Sample. A preproduction sample of five completely assembled ABC-M3 calculators and five unassembled ABC-M3 calculators shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.2.2 Examination and nondestructive test. The components of the five unassembled calculators shall be examined for all the requirements of the drawings. The five assembled calculators shall be examined and tested in accordance with the classification of defects (4.3.3.2).

4.2.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.2.2 to be acceptable.

4.3 Regular production.

4.3.1 Lotting. A lot shall consist of the ABC-M3 calculators produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

4.3.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105. For major defect 101 level S-2 shall be used.

4.3.3 Inspection.

4.3.3.1 Examination and nondestructive tests. Sample calculators shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.3.3.2 Classification of defects.

(a) Calculator, downwind toxic vapor hazard, line source, ABC-M3 (Dwg C5-86-10).

Categories		Defects	Acceptance standards
Critical:		None defined	
Major:	AQL	1.0 percent defective	
101		Functioning	4.3.4
	AQL	2.5 percent defective	
102		Component missing, incorrect or incorrectly assembled	
103		Disks not free to turn easily	
104		Marking or lettering incorrect, illegible or missing	
105		Rivet holes in disks incorrectly located	
106		Case heat seal not continuous	
107		Workmanship (3.5)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

4.3.4 Functioning test. The test shall be conducted as follows: Solve the three problems using the data listed in table I. Align dosage (D) with line source length (L) and wind speed (U) with source strength (Q). Read the value of K opposite the specified temperature gradient ($\triangle$TG). Turn the calculator over and align the line source length (L) with the K value previously obtained. Read the downwind distance where the specified temperature gradient curve and the downwind distance line intersect. Check for compliance with table I as applicable.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Level shall be as specified (see 6.2).

5.1.1 Level A. The calculator, placed within its case, shall be individually packaged in accordance with method IC-3 of MIL-P-116. Prior to bag closure, a fiberboard filler the same size as the outside dimensions of the calculator case and conforming to type CF, class domestic, variety SW, grade 125 of PPP-F-320 shall be inserted in each bag to act as a stiffener.

5.1.2 Level C. The calculator, placed within its case, shall be packaged to provide adequate protection against deterioration and physical damage from the supply source to the first receiving activity for immediate use.

5.2 Packing. Level shall be as specified (see 6.2).

5.2.1 Level A. One hundred calculators, packaged as specified in 5.1.1, shall be packed within an overseas type cleated-plywood box conforming to PPP-B-601. Cushioning material, conforming to type II, class A of PPP-C-843, shall be used to fill all voids within the box. The box shall be closed and strapped in accordance with the appendix of PPP-B-601. Galvanized strapping shall be used.

5.2.2 Level B. One hundred calculators, packaged as specified in 5.1.1, shall be packed in a V3c, style RSC fiberboard box conforming to PPP-B-636. In addition to box closure requirements, the box seams and manufacturer's joint shall be taped. Tape banding shall be used in lieu of metal banding as a box reinforcement.

5.2.3 Level C. One hundred calculators, packaged as specified in 5.1.2, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in compliance with Uniform Freight Classification rules or the regulations of other common carriers applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D150-2-1.

6. NOTES

6.1 Intended use. This calculator is intended for use in calculating downwind hazard of chemical agents.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Level of packaging and packing required.
(c) Preproduction:

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time allowed for the Government to notify the supplier whether or not to proceed with production.

6.3 International interest. Certain provisions of this specification are the subject of international standardization agreement (see Serial No. 29, Supplement B to Quadripartite Standardization List Sheet Report). When amendment, revision or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

Custodians:

Army - MU
Air Force - 82

Preparing activity:

Army - MU (EA)

International interest (see section 6)

Project No. 6665-0150

Review activities:

Coordination Method Code - C

Air Force - 82

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
US Army Edgewood Arsenal
ATTN SMUEA-QAWS
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.

TO DETACH FORM – CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS. This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 76 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:53Z
Check the source to verify that this is the current version before use.