INCH-POUND

MIL-C-82168A(MC)
AMENDMENT 2
February 22, 1995
SUPERSEDING
AMENDMENT 1
28 March 1994

MILITARY SPECIFICATION
COAT,MAN'S, FULL DRESS, SUMMER AND WINTER,SCARLET,
U.S. MARINE BAND, DRUM MAJOR

This amendment forms a part of MIL-C-82168A(MC) dated 26 April 1974 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under Specifications: Delete FEDERAL and MILITARY specifications in entirety and add:

FEDERAL

A-A-50196	- Thread, Silk
A-A-50198	- Thread, Gimp, Cotton Buttonhole
A-A-50199	- Thread, Polyester Core,Cotton or Polyester Covered
A-A-52071	- Tape,Textile,Cotton,General Purpose,(Unbleached, Bleached or Dyed)
A-A-52094	- Thread, Cotton
A-A-52097	- Cloth, Wigan, Cotton
A-A-52106	- Cloth, Twill or Plain Weave,Polyester or Polyester Blend
DDD-L-20	- Labels for Clothing, Equipage and Tentage (General Use)

MILITARY

MIL-C-368	- Cloth, Satin, Rayon and Cloth, Twill Rayon
MIL-B-3461	- Buttons, Insignia, Metal Uniform and Cap
MIL-P-15064	- Pads, Shoulder and Sleeve-head
MIL-E-20652	- Eyelets, Metallic and Eyelet Washers (General Specification For)
MIL-C-21115	- Cloth, Tropical, Wool Polyester/Wool
MIL-C-29405	- Cloth,Broadcloth, Wool and Wool/Nylon
MIL-C-41820	- Cloth, Gabardine, Polyester and Rayon
MIL-C-82114	- Coat Front for coats, Musicians

AMSC N/A FSC 8405

DISTRIBUTION STATEMENT. Approved for public release,distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:50Z
Check the source to verify that this is the current version before use.

PAGE 3

Para 3.3.1.b delete line 2 in entirety and add: 14 ounce, conforming to type I of MIL-C-29405.

Para 3.3.3 Delete title and add "Cloth, Twill or plain weave." 3rd line after cloth delete remainder of paragraph and add "twill or plain weave, natural color, conforming to A-A-52106."

PAGE 5

Para 3.3.9 line 2 delete "type III, class 1 of DDD-T-86" and add "type II, Class 1 of A-A-52071"

Para 3.3.10 (b) line 1 substitute "14" for "16.5"; line 2 substitute "MIL-C-29405" for "MIL-C-82252"

Add new paragraph as: "3.3.10.1 Vinyl piping. The white vinyl cord for piping the upper edge of the collar shall be tubular with 7/16 inch welt and serrated edges. One acceptable product is sold by the Pearl Binding Corporation of Philadelphia, PA."

Para 3.3.11 line 3 substitute "A-A-52097" for "type I of MIL-C-16375"

Para 3.3.12.1 line 1 substitute "A-A-50196" for "V-T-301"

Para 3.3.12.2 line 1 substitute "A-A-52094" for V-T-276"
In the chart, under "type" substitute as follows: "III for 1C2"; "I" for "1A1"; "I" for 1B3": Under Ticket No. substitute "40 for 24": under ply substitute "3" for "4"
At the end of the paragraph add the following: "As an alternate to the cotton thread, a polyester core, cotton or polyester covered thread conforming to A-A-50199, ticket No. 50, 2 ply or ticket No. 70, 2 ply may be used."

PAGE 6

Para 3.3.13 line 2 after type II of substitute A-A-50198 for V-T-280."

PAGE 7

Para 3.3.16 Delete in it's entirety and substitute: "3.3.16 Collar closure hook and eye. The hook and eye for closing the collar shall be brass, black, japanned finish or black, chemical finish conforming to MIL-F-495, followed by a clear lacquer coating and conform to the requirements of figure 10 which will replace the hook and eye details contained in figure 9."

Add new paragraph as: "3.3.16.1 Eyelets. The eyelets for the collar shall be brass, rolled flange type, with the barrel scored 6 to 8 scores. The eyelets shall conform to MIL-E-20652, sheet 1A-BE108 and be enameled a black shade."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:50Z
Check the source to verify that this is the current version before use.

Para 3.3.17.1 delete in entirety and add "Combination identification/instruction label. The combination identification/instruction label shall conform to type V, classes 2 and 14 combined of DDD-L-20 except all printing and the space between lines of printing shall be minimum 10 point (approximately 1/8 inch). The content and format shall be as follows:

COLLAR SIZE_____
NOMENCLATURE_____
CONTRACT NO._____
NAME OF CONTRACTOR_____
WOOL PRODUCTS ACT INFORMATION_____

PAGE 8

Para 3.3.17.2 line 1, substitute "V" for "I"
Add new para "3.3.18 Bias Binding. The binding for the underarm shields shall be bias cut of the lining material specified in 3.3.3. The binding shall be 5/8 to 7/8 inch wide. The binding shall have sized edges."

Para 3.5.1 add new pattern part for the Material basic: Cloth, wool tropical or Cloth, wool broadcloth as follows: "11. Underarm shields 2"

PAGE 9

Under Cloth, rayon lining delete item no. 15 "underarm shield 4" Delete "Silesia or Polyester and cotton" and add "Cloth, Twill or plain weave, polyester or polyester blend"

PAGE 10

Oper 1.e delete words "cotton silesia or polyester and cotton stays" and add "twill or plain weave polyester or polyester blend stays"

PAGE 14

Oper 9. Add to title "and pipe upper edge".

PAGE 15

Add new operations as: "9.c. Position the collar on the vinyl cord, with the upper edge of the collar abutted against the cord edge. Stitch collar to the vinyl cord 1/16 inch from the edge of collar. Trim the ends even with the ends of the collar. (301 LSa-1 10-14 A A silk).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:50Z
Check the source to verify that this is the current version before use.

9.d. Position the eyelet cover on the underside at each end of the collar , with one edge of the cover 3/4 to 7/8 inch from the front end, and the bottom raw edge of the cover 1/2 to 5/8 inch from the upper cord edge. Stitch collar to cover along the cord edge adjacent to the stitching line of the collar. (301 SSa-1 10-14 A A silk)

9.e. Lap the upper cord edge of collar over the top raw edge of collar lining approximately 1/2 inch with the lining face up. Stitch collar to lining and eyelet cover along the cord edge adjacent to the stitching line of the collar. The stitching shall extend not less than 1/2 inch from end of collar. (301 SSa-1 10-14 A A silk).

9.f. Turn the collar lining and eyelet cover at the seam to the inside of collar and press smooth and flat with a heated pressing iron or pressing machine."

PAGE 16

Oper 11.c. Delete in its entirety and substitute: "11.c. Attach metal eyelets through all plies of the collar, midway between the upper and bottom edge and 1-1/2 +-1/8 inches from the folded end of collar."

PAGE 18

Oper 15. Finished appearance: Line one after"braid" insert and lace". Add at end: The lower stripe on the sleeves shall be from the gold lace specified in 3.3.15.2."

Oper 15.a. Line one after "braid" insert "and lace"

PAGE 49

Oper 69 Delete in it's entirety and substitute: "69. Sew hook and eye to collar. Finished appearance. The hook and eye shall be positioned to properly engage each other, effecting a flat, smooth closure at the front of the collar without misalignment.
a. Position and securely sew the hook to the right end and the hook to the left end of the collar. The hook and eye shall be positioned with their front edges even with the respective front ends of collar and securely sewn to the collar at the top and bottom edge of the hook and eye. The stitching on each side shall not be more than 3/8 inch from the front end of the collar, through the individual holes at the rear of the hook and eye. (Hand 16 per hook and 16 per eye C silk)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:50Z
Check the source to verify that this is the current version before use.

PAGE 62

Under Hook and Eye defects, Delete (a) and (b).

Add new figure 10.

Preparing activity
Navy-MC
Project 8405-N254

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:50Z
Check the source to verify that this is the current version before use.