MILITARY SPECIFICATION

FUZE, IMPACT, ATOMIC WEAPON

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of ring series entitled Fuze, Impact Atomic Weapon which are used in the Honest John warhead section.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1168	- Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8808362	- Container, Packing, Ammunition, For Domestic (CONUS) Shipments of Special Weapon Items, Packing and Marking.
8813374	- Ring Assembly, No. 2.
8813389	- Ring Assembly, No. 4.
8822024	- Carton, Packing, Ammunition, for Ring Assembly No. 2.
8822025	- Carton, Packing, Ammunition for Ring Assembly No, 3, (top section).
8822026	- Carton, Packing, Ammunition, for Ring Assembly No, 4.
8824938	- Carton Packing, Ammunition, for Ring Assembly No, 3, (bottom section)
8825072	- Case Section, Ballistic, Center, Aft.
8825079	- Middle Shell and Ring Switch Assembly.
8825081	- Ring Assembly, No. 3 (top).
8825082	- Ring Assembly, No. 3 (bottom).
8825153	- Adaption Kit, Atomic Warhead: M 86.
EL-8842570	- Equipment Lists.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The fuze shall comply with all requirements specified on the drawing (dwg) 8813374, 8825081, 8825082 and 8813389, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Mating assembly. The fuze shall be capable of mating mechanically and electrically when attached to mating assembly shown in drawings 8825079 Middle Shell and Ring Switch Assembly and 8825072 Case Section, Ballistic, Center, Aft or equivalent when tested as specified in 4.4.2.

3.5 Continuity resistance. The continuity resistance of each circuit of the respective connectors shall not exceed the value specified in Tables I through III when tested in accordance with 4.4.2.

Table I

Ring No. 2 (see dwg 8813374)

Terminal		
From	To	Measured Resistance (Ohms)
E2-1	E2-2	0.02 maximum (max.)
E2-2	E2-3	0.02 max.
E2-1	E2-3	0.02 max.

Table II

Ring No. 3 (top) (see dwg 8825081)

Terminal		
From	To	Measured Resistance (Ohms)
E3-4	E3-1	0.015 max.
E3-1	E3-3	0.015 max.
E3-2	E3-3	0.015 max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Ring No. 3 (bottom) (see dwg 8825082)

Terminal		
From	To	Measured Resistance (Ohms)
E3-4	E3-1	0.015 max.
E3-1	E3-3	0.015 max.

Table III

Ring No. 4 (see dwg 8813389)

Terminal		
From	To	Measured Resistance (Ohms)
E4-1	E4-2	0.02 max.
E4-2	E4-3	0.02 max.
E4-1	E4-3	0.02 max.

3.6 Insulation resistance The insulation resistance from each terminal to ground for the respective assemblies in Tables IV through VI shall be greater than 100 megohms when tested at 500 ± 50 volts direct current (vdc). Testing shall be as specified in 4.4.3.

Table IV

Ring No. 2 (see dwg 8813374)

Terminal	Ground
E2-1	This will be the test fixture ground, metal housing of ring shall be at ground potential.

Table V

Ring No. 3 (dwg 8825081 and A 8825082)

Terminal	Ground
E3-1	This will be the test fixture ground, metal housing of ring shall be at ground potential.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table VI

Ring No. 4 (dwg 8813389)

Terminal	Ground
E4-1	This will be the test fixture ground, metal housing of ring shall be at ground potential.

3.7 Environmental testing. The fuze assemblies shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The fuze assemblies shall also comply with 3.4 through 3.6 before and after each environmental test. Testing shall be as specified in 4.4.4. Tests shall be conducted in the order specified.

3.7.1 Temperature shock The fuze assemblies shall withstand temperature shock without damage and shall comply with 3.4, 3.5 and 3.6 except that the insulation resistance shall be reduced to 20 megohms, after being tested. The rest shall be conducted as specified in 4.4.4.1.

3.7.2. Humidity The fuze assemblies shall not be damaged when exposed to humidity conditions specified. The assemblies shall comply with 3.5 and 3.6 except that the insulation resistance shall be reduced to 20 megohms, after being tested as specified in 4.4.4.2.

3.7.3 Vibration. The fuze assemblies shall be mounted on a cradle equivalent to the following assembly or the assembly with associated fasteners:

Case Section, Ballistic Center, Aft, dwg 8825072. The cradle assembly shall then withstand, without damage, vibration in three mutually perpendicular axes as specified in Table VII at a temperature of 80 degrees Fahrenheit (°F) ± 20°F. The fuze assemblies shall show no indication of continuity between any terminal and the case (ground) during vibration at each condition, and shall comply with 3.4, 3.5 and 3.6 after being tested as specified in 4.4.4.3.

Table VII

Frequency Range Hertz (Hz)	Double Amplitude or Peak g* Level ± 10 Percent Tolerances (tol.)	Cycle Time to Cover Freq. Range-Minutes (+0.5 Minutes)	Time Per Axis Minimum-Minutes (80 ± 20°F.)
5-10-5	1.0 inch	3	10
10-100-10	± 5g	3	15
100-1000-100	± 5g	3	30

*Gravity (g.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

3.7.4 Shock. The fuze assemblies mounted as specified in 3.7.3, shall withstand, without damage, a minimum shock of 75 g's peak amplitude with a time duration of 9 + 3 milliseconds at half amplitude applied twice in each direction in each of three mutually perpendicular axes. The fuze assemblies shall comply with 3.4. 3.5 and 3.6 after being tested as specified in 4.4.4.4.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristics.

3.8.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.8.3 Burrs. Parts shall be free from burrs.

3.8.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 5 complete assemblies (see dwg 8813374, 8825081, 8825082 and 8813389) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table VIII. Tests shall be conducted in order specified in Table VIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table VIII

First article inspection and tests

Inspection or test	No. Units Tested 2	3	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)	X	X		X
2. Continuity resistance (see 3.5)	X	X		X
3. Insulation resistance (see 3.6)	X	X		X
4. Mating assembly (see 3.4)	X	X		X
5. *Vibration (see 3.7.3)	X	X	X	
6. *Temperature shock (see 3.7.1)	X	X	X	
7. *Humidity (see 3.7.2)	X			X
8. Shock (see 3.7.4)	X	X	X	

* Testing sequence is optional

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If and item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table IX and Table X), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table IX
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table IX and Table X), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table IX
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table X
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Ring assemblies No. 2, No. 3, and No. 4, (see dwgs 8813374, 882508, 8825082, and 8813389 as applicable).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
	101. No sealing compound on designated areas	Visua
	102. Objective evidence relative to material missing or improper (see 3.1)	Visual/Manual
Minor:		
	201. Sealing compound on hot terminals	Visual
	202. Dents or bumps that distort surface of rings over 1/16 inch from the plane of the surrounding surface	Scale
	203. Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.2 Carton, packing, ammunition, for ring assemblies (see dwg 8822024, 8822025, 8822026, and 8824938, as applicable).

Categories	Characteristics	Method of Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Critical: None defined.

Major:
101. Wrong size bag.....Visual
102. Bag not sealed.....Visual
103. Air in bag not minimized before.....Visual
104. Marking missing, incorrect or mislocated.....Visual

Minor:
201. Evidence of poor workmanship (see 3.9).....Visual

4.3.2.1.3 Packing (see dwg 8808362).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Marking missing or incorrect.....Visual
102. Incorrect or insufficient cushioning material.....Visual

Minor:
201. Evidence of poor workmanship (see 3.9).....Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test classification
a. Continuity resistance	Major
b. Insulation resistance	Major
c. Humidity	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Continuity resistance and insulation resistance. Each fuze assembly shall be tested in accordance with 4.4.2 and 4.4.3. If any item fails to comply with 3.5 and 3.6,the item shall be rejected and removed from the lot.

4.3.3.2 Humidity. A sample shall be selected at random in accordance with Table XI. the sample shall be tested in accordance with 4.4.4.2. If any item fails to comply with 3.7.2., the lot shall be rejected.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table X
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Ring assemblies No. 2, No. 3, and No. 4, (see dwgs 8813374, 882508, 8825082, and 8813389 as applicable).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
	101. No sealing compound on designated areas	Visua
	102. Objective evidence relative to material missing or improper (see 3.1)	Visual/Manual
Minor:		
	201. Sealing compound on hot terminals	Visual
	202. Dents or bumps that distort surface of rings over 1/16 inch from the plane of the surrounding surface	Scale
	203. Evidence of poor workmanship (see 3.9)	Visual

4.3.2.1.2 Carton, packing, ammunition, for ring assemblies (see dwg 8822024, 8822025, 8822026, and 8824938, as applicable).

Categories	Characteristics	Method of Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Critical: None defined.

Major:
101. Wrong size bag.....Visual
102. Bag not sealed.....Visual
103. Air in bag not minimized before.....Visual
104. Marking missing, incorrect or mislocated.....Visual

Minor:
201. Evidence of poor workmanship (see 3.9).....Visual

4.3.2.1.3 Packing (see dwg 8808362).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Marking missing or incorrect.....Visual
102. Incorrect or insufficient cushioning material.....Visual

Minor:
201. Evidence of poor workmanship (see 3.9).....Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test classification
a. Continuity resistance	Major
b. Insulation resistance	Major
c. Humidity	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Continuity resistance and insulation resistance. Each fuze assembly shall be tested in accordance with 4.4.2 and 4.4.3. If any item fails to comply with 3.5 and 3.6,the item shall be rejected and removed from the lot.

4.3.3.2 Humidity. A sample shall be selected at random in accordance with Table XI. the sample shall be tested in accordance with 4.4.4.2. If any item fails to comply with 3.7.2., the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

Table XI
Sample sizes for non-destructive testing

Lot Size	Sample Size
3-50	3
51-150	4
151-300	5
301-600	6
601-1000	8

4.3.4 Acceptance inspection equipment

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8842570). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration inctructions used by the contractor for minor classification inspection shall be approved by the Government representative arthorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Mating assembly. The assemblies may be mounted to a fixture equivalent to the mating surfaces of the assembly shown on drawing 8825072.

4.4.2 Continuity resistance. The continuity resistance between the terminals specified in Tables I,II and III shall be determined by the use of a suitable electrical resistance measuring instrument.

4.4.3 Insulation resistance. An insulation resistance tester, capable of supplying the required voltage and with which a resistance in megohms can be obtained, shall be used to measure the resistance. The current shall be libited to a maximum of 5 milliamperes to protect human life.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

4.4.4 Environmental Testing (see 3.7).

4.4.4.1 Temperature shock. The fuze assemblies shall be placed within a test chamber where the temperature is -65 + 5°F for a period of 4 hours. At the conclusion of this 4 hour period, and within 5 minutes, the fuze assemblies shall be transferred to a chamber having an internal temperature of 160 + 5°F. The fuze assemblies shall be subjected to this temperature for a period of 4 hours minimum. This completes one cycle. The number of complete cycles shall be three. At the conclusion of the third cycle the item shall be removed from the test chamber. After this test the assembly shall be tested as specified in 4.4.1 through 4.4.3.

4.4.4.2 Humidity. The fuze assemblies shall be placed in a humidity test chamber and set up to simulate installed conditions. The chamber temperature shall be maintained at 160 + 5°F during the next 6 hour period. During the following 16 hour period, the temperature in the chamber shall be gradually reduced to 80 + 20°F. This constitutes one cycle. The relative humidity throughout the cycle shall be 95 + 5 percent. The cycle shall be repeated 10 times. The air velocity through the test area shall not exceed 150 feet per minute. Upon completion of the tenth cycle the assembly shall be removed immediately from the test chamber and excessive moisture removed by blowing dry, filtered are over the unit for a period of 5 minutes. The assembly shall then be tested as specified in 4.4.2 and 4.4.3.

4.4.4.3 Vibration. The fuze assemblies shall be rigidly mounted to a fixture capable of being supported readily in each of three mutually perpendicular axes, with the fixture mounted on a suitable vibration producing apparatus, the terminals and case shall be monitored continuously during the test with instrumentation capable of detecting circuit closures of 20 microseconds duration. The item shall be vibrated at the frequencies, g amplitude, temperatures, and for the times specified in Table VII in each of three mutually perpendicular axes. Following this test the assembly shall be tested as specified 4.4.1 through 4.4.3.

4.4.4.4 Shock. The fuze assemblies shall be rigidly mounted to a fixture and the fixture mounted to a suitable shock producing device. The fuze assemblies shall be shocked as specified, twice in each of three mutually perpendicular axes. Following this test the assembly shall be tested as specified in 4.4.1 through 4.4.3.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A and C as specified (see 6.1).

5.1.1 Level A. The fuze assemblies shall be packaged in accordance with dwgs 8822042, 8822052, 882206 and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

8824938 as applicable using the specified moisture barrier.

5.1.2 Level C. The fuze assemblies shall be packaged in accordance with dwgs 8822024, 8822025, 8822026 and 8824038 as applicable except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The fuze assemblies shall be packed in accordance with dwg 8808326.

5.3 Marking. Marking shall be as specified in accordance with dwgs 8822024, 8822025, 8822026 and 8824938 as applicable and 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase decription PA-PD-1694 dated 1 November 1961.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A154

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.