MIL-G-50935B (AR)
14 May 1980
SUPERSEDING
MIL-G-50935A (PA)
18 July 1975

MILITARY SPECIFICATION

GRENADES, GP, CONE FOR

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by drawings and provides quality assurance provisions for one type of cone for general purpose grenades.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC: 1330

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

DRAWINGS

PICATINNY ARSENAL

9206200	-	Box, Fiber, for Cone
9215346	-	Cone

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer)

3. REQUIREMENTS

3.1 Material - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Cone - The cone shall comply with all requirements specified on Drawing (Dwg) D-9215346, and with all requirements specified in applicable specifications.

3.3 Workmanship - All cones shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

3.4 First article testing - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the currentversion before use.

4.3.1 Submission - The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

PART DESCRIPTION	DRAWINGS	QUANTITY
Cone	9215346	50

4.3.2 Inspections to be performed - See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

Table I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-50935B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Cone				9215346
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cone Examination for defects	50	—	3.2	4.4.2.1 (Note a)

NOTES:

(a) A sample of ten (10) cones shall be inspected for outside surface profile.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection lot formation - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination - See MIL-A-48078.

a. Sampling plans - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-50935B (AR)

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.1	Cone				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR /100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length to smaller basic diameter		0.40%	3.2	Gage
103	Length to larger basic diameter		0.40%	3.2	Gage
104	Total length		0.40%	3.2	Gage
105	Wall thickness between specified planes		0.40%	3.2	Gage
106	Wall thickness variation between planes max. (360° planes)		0.40%	3.2	Gage
107	Wall thickness variation between planes along conical elements as specified, max		0.40%	3.2	Gage
108	Wall thickness outside datums		0.40%	3.2	Gage
109	Concentricity of outside diameter with basic diameters		0.40%	3.2	Gage
110	Part cracked or dented		0.40%	3.2	Visual
111	Straightness	(a)		3.2	4.5.1
112	Outside surface profile	(a)		3.2	4.5.1
Minor					
201	Radius between outside diameter and junction with conical surface		0.65%	3.2	Gage
202	Finish improper (stain or unusual discoloration)		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

(a) Sampling per para. 4.4.3.1.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-50935B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Tube (Sealed and prior to Insertion in fiber box)				9206200
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tube damaged to the extent that contents are exposed		0.40%	3.2	Visual
102	Closure missing or not fully seated		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Manual
202	Marking missing, incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-50935B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Box, Fiber, Sealed				9206200
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to the extent that tubes are exposed		0.40%	3.2	Visual
102	Sealing strip incomplete, badly wrinkled or missing		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Manual
202	Marking missing, incorrect, or unidentifiable including incorrect color code		0.65%	3.2	Visual
203	Label missing or badly wrinkled (when applicable)		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

4.4.3 Testing -

4.4.3.1 Straightness and Outside Surface Profile - The sample parts shall be inspected for conformance to the requirements of dwg 9215346. Ten (10) parts shall be inspected to qualify each machine for production prior to use. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production from each machine. An additional three (3) parts shall be inspected after each minor machine adjustment. The last two samples are for machine control during production.

4.4.3.1.1 If any defective parts are found during qualification of the machine, the machine producing the defective part shall not be used in production.

4.4.3.1.2 If any defective parts are found when inspection is performed for machine control, the machine that produced the defective part shall be removed from production. Further, that portion of production since the last machine control check shall be rejected.

4.4.3.1.3 All machines removed from production because of some fault may, after adjustment or rework, be returned to production provided they pass the qualification test above.

4.4.3.1.4 Parts shall be inspected in accordance with paragraph 4.5.1.

4.4.4 Inspection equipment - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures -

4.5.1 Straightness and outside surface profile - The samples selected for this test shall be measured for straightness and outside surface profile along one conical element.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging (Level C). - The cones shall be preserved and packaged in accordance with Dwg. C-9206200.

5.2 Marking - Marking of the boxes shall be in accordance with Dwg. C-9205200.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

5.3 Shipping - When shipments of more than one lot are made at one time, such as in a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing in transit.

6. NOTES

6.1 Intended use - The cones covered by this specification are intended for use on grenades, general purpose; M42 and M46.

6.2 Ordering Data - See MIL-A-48078.

6.3 Submission of Inspection Equipment designs for approval - See MIL-A-48078. Submit equipment designs, as required, to Commander, US Army ARRADCOM, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1330-A143

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-G-50935B (AR) GRENADES, GP, CONE FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:44Z
Check the source to verify that this is the current version before use.