MIL-M-50768A(MU)
25 May 1972
SUPERSEDING
MIL-M-50768(MU)
30 November 1971

MILITARY SPECIFICATION

MOVEMENT, D.A.M. ASSEMBLY

1. SCOPE

1.1 This specification covers one type of movement assembly for use with high explosive ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-331	- Fuze and Fuze Components Environmental and Performance Tests For
MIL-STD-1167	- Ammunition Data Card

SPECIFICATIONS

Federal

PPP-B-26	- Bag, Plastic, Polyethylene
PPP-B-636	- Box, Fiberboard

Military

MIL-P-116	- Preservation, Methods of
MIL-P-117	- Bag, Sleeve and Tubing - Interior Packaging

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

DRAWINGS

Munitions Command

D11740782	- Movement, D.A.M. Assembly (Module)
C9270759	- Tray, Plastic
C9272185	- Box, Wirebound Packing Ammunition for Movement Assembly for Booster, M125A1
IEL 11740782	- Inspection Equipment List for Movement D.A.M. Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA-B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, N. Y. 10018.)

3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall comply with the requirements specified on applicable drawings, referenced standards, and specifications except as provided in 6.1.

3.2 Environmental

3.2.1 The movement assembly shall be installed into a booster body, #F-10520749 to form an M125A1 booster subassembly #F-10520748. The assembled unit shall comply withMIL-STD-331, Jolt, Test No. 101.

3.2.2 The movement assembly shall be installed into a booster body, #F-10520749 to form an M125A1 booster subassembly #F-10520748. The assembled unit shall comply with MIL-STD-331, Jumble, Test No. 102.

3.2.3 The movement assembly shall be installed into a booster body #F-10520749 to form an M125A1 booster subassembly #F-10520748. The assembled unit shall comply with MIL-STD-331, transportation- Vibration, Test No. 104.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

3.3 Non-arming.-The movement assembly shall not arm when spun at the non-arming speed specified on the applicable drawing.

3.4 Arming.-The movement assembly shall arm when spun at the arming speed specified on the applicable drawing.

3.5 Ballistics.- (see 6.3.2)

3.5.1 The movement assembly shall not function prematurely. (see 6.3.1)

3.5.2 Target impact nonfunction distance.-The movement assembly shall not detonate the round upon impact element function when fired in the 90MM Gun, Service Charge, (2400 feet per second, f.p.s.) on a target 180 plus 5 feet from the muzzle of the weapon.

3.5.3 Target impact function distance.-The movement assembly shall detonate the round upon impact when fired in the 105MM Howitzer, charge 7 (1550 f.p.s.) on a target 400 minus 5 feet from the muzzle of the weapon.

3.5.4 Ground or water impact.-The movement assembly shall detonate the round upon impact when fired in the 155MM Howitzer, charge 1 (680 f.p.s.) at an impact angle of 45° minimum.

3.6 Workmanship.-The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.6.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, inclusions, porosity or any similar defect.

3.6.2 Surface finish.-The requirements for surface finish are as detailed on the applicable drawings.

3.6.3 Threads.-Threads shall be full and undamaged for the entire minimum length or depth as required by the applicable drawing.

3.6.4 Burr.-No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.6.5 Foreign matter.-No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter. The method and agents used in processing cleaning shall not adversely affect the finish or contaminate the parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.2 First article sample.

4.2.1 Initial production sample.-When required by the contract, the first units of production shall be submitted as an initial production sample. The samples shall consist of the following:

40 component parts as delineated in 4.2.2
150 subassemblies as delineated in 4.2.3
90 assemblies as delineated in 4.2.4 and 4.2.5

The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.-After inspection by the contractor and provisional acceptance at source by the Government, 60 movement assemblies shall be forwarded to a designated proving ground as specified in the contract. Forty (40) component parts, 150 subassemblies and 30 movement assemblies shall be inspected as provided herein at a Government laboratory or such other facility as specified in the contract.

4.2.2 Components.

4.2.2.1 Twenty (20) of each component shall be tested as in 4.3.3.1 (Hardness).

4.2.3 Subassemblies.

4.2.3.1 Fifty (50) of each subassembly shall be tested as in 4.3.3.2 (Static load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.3.1.1 Acceptance criteria.-Failure of any subassembly to comply with the requirements of the applicable drawing shall be cause for rejection of the initial production sample.

4.2.4 Movement assemblies.-Thirty (30) movement assemblies shall be subjected to the following MIL-STD-tests:

Test	Quantity	Requirement	Test Method	Acceptance Criteria
Jolt	10	3.2.1	4.4.5.1	4.2.4.1.1
Jumble	10	3.2.2	4.4.5.2	4.2.4.1.1
Transportation-Vibration	10	3.2.3	4.4.5.3	4.2.4.1.2

4.2.4.1 Acceptance criteria.-Occurrence of any of the following in any movement assembly shall be cause for rejection of the initial production sample.

4.2.4.1.1 Jolt and Jumble.

a. Rotor armed or partially armed. (See 6.2.1 and 6.2.2.)
b. Failure of the movement assembly to meet the non-arming requirements of the applicable drawing.
c. Broken, deformed or displaced parts which render the movement assembly unsafe to handle or dangerous to use.

4.2.4.1.2 Transportation-vibration.

a. Condition listed in 4.2.4.1.1.
b. Failure of the movement assembly to meet the arming and non-arming requirements of the applicable drawing.

4.2.5 Ballistics.-Sixty (60) movement assembles, of the initial production sample, shall be subjected to the following ballistic test phases.

Phases	Quantity	Requirement	Test Method
Impact Nonfunction Distance	20	3.5.2	4.4.6.1
Impact Function Distance	20	3.5.3	4.4.6.2
Ground or Water Impact	20	3.5.4	4.4.6.3

4.2.5.1 Acceptance criteria.-The occurrence of the following shall be cause for rejection of the initial production sample:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.5.1 (Cont'd)

a. A premature burst in any phase. (See 6.3.1)
b. Function of one or more rounds upon target impact in the Impact Nonfunction Phase.
c. Failure of more than one round total to function in either of the following phases:
(1) Target Impact Function Phase.
(2) Ground or Water Impact Phase.

4.3 Inspection provisions.

4 3.1 Submission of product.-The product shall be presented in accordance with MIL-STD-105.

4.3.1.1 Lot formation.-Each inspection lot of movement assemblies shall be comprised of components (except explosive components) each produced by one manufacturer, by one process, in accordance with the same drawing and revision and specifications and revisions, as applicable, and assembled on one assembly line. Each explosive component within a lot of movement assemblies shall be limited to one manufacturer and one interfix number.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a single defect basis in accordance with MIL-STD-105. For the classification of defects contained herein, the AQL given shall be used. All nonconforming material shall be rejected. The roughness comparison specimens prescribed by ASA-B46.1 shall be used as a basis for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

4.3.2.1 Plate Top Drawing D10520705 covering a detail of Drawing D11740782.

Defect		Method of Inspection
CRITICAL		
None defined		
MAJOR	AQL = 1.0%	
101.	Outside diameter, incorrect	Gage
102.	Parallelism exceeds max.	Gage
103.	Metal defective	Visual

4.3.2.2 Plate, Bottom Drawing D10523010 covering a detail of Drawing D11740782.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.3.1.1 Acceptance criteria.-Failure of any subassembly to comply with the requirements of the applicable drawing shall be cause for rejection of the initial production sample.

4.2.4 Movement assemblies.-Thirty (30) movement assemblies shall be subjected to the following MIL-STD-tests:

Test	Quantity	Requirement	Test Method	Acceptance Criteria
Jolt	10	3.2.1	4.4.5.1	4.2.4.1.1
Jumble	10	3.2.2	4.4.5.2	4.2.4.1.1
Transportation-Vibration	10	3.2.3	4.4.5.3	4.2.4.1.2

4.2.4.1 Acceptance criteria.-Occurrence of any of the following in any movement assembly shall be cause for rejection of the initial production sample.

4.2.4.1.1 Jolt and Jumble.

a. Rotor armed or partially armed. (See 6.2.1 and 6.2.2.)
b. Failure of the movement assembly to meet the non-arming requirements of the applicable drawing.
c. Broken, deformed or displaced parts which render the movement assembly unsafe to handle or dangerous to use.

4.2.4.1.2 Transportation-vibration.

a. Condition listed in 4.2.4.1.1.
b. Failure of the movement assembly to meet the arming and non-arming requirements of the applicable drawing.

4.2.5 Ballistics.-Sixty (60) movement assembles, of the initial production sample, shall be subjected to the following ballistic test phases.

Phases	Quantity	Requirement	Test Method
Impact Nonfunction Distance	20	3.5.2	4.4.6.1
Impact Function Distance	20	3.5.3	4.4.6.2
Ground or Water Impact	20	3.5.4	4.4.6.3

4.2.5.1 Acceptance criteria.-The occurrence of the following shall be cause for rejection of the initial production sample:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.5.1 (Cont'd)

a. A premature burst in any phase. (See 6.3.1)
b. Function of one or more rounds upon target impact in the Impact Nonfunction Phase.
c. Failure of more than one round total to function in either of the following phases:
   (1) Target Impact Function Phase.
   (2) Ground or Water Impact Phase.

4.3 Inspection provisions.

4 3.1 Submission of product.-The product shall be presented in accordance with MIL-STD-105.

4.3.1.1 Lot formation.-Each inspection lot of movement assemblies shall be comprised of components (except explosive components) each produced by one manufacturer, by one process, in accordance with the same drawing and revision and specifications and revisions, as applicable, and assembled on one assembly line. Each explosive component within a lot of movement assemblies shall be limited to one manufacturer and one interfix number.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a single defect basis in accordance with MIL-STD-105. For the classification of defects contained herein, the AQL given shall be used. All nonconforming material shall be rejected. The roughness comparison specimens prescribed by ASA-B46.1 shall be used as a basis for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

4.3.2.1 Plate Top Drawing D10520705 covering a detail of Drawing D11740782.

Defect		Method of Inspection
CRITICAL		
None defined		
MAJOR	AQL = 1.0%	
101.	Outside diameter, incorrect	Gage
102.	Parallelism exceeds max.	Gage
103.	Metal defective	Visual

4.3.2.2 Plate, Bottom Drawing D10523010 covering a detail of Drawing D11740782.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
MAJOR AQL = 1.0%	
101. Outside diameter, incorrect	Gage
102. Location of holes 15 and 16 incorrect	Gage
103. Diameter of holes 15 and 16 incorrect	Gage
104. Parallelism exceeds max.	Gage
105. Metal defective	Visual

4.3.2.3 Spacer Drawing F10520707 covering a detail of Drawing D11740782.

CRITICAL

None defined

MAJOR AQL = 1.0%	
101. Diameter at top of contour incorrect	Gage
102. Contour incorrect	Gage
103. Location of holes 15 and 16 incorrect	Gage
104. Pitch diameter of holes 15 and 16	Gage
105. Minor diameter of holes 15 and 16	Gage
106. Metal defective	Visual

4.3.2.4 Pallet Assembly, Drawing D10523174 covering a detail of Drawing D11740782.

CRITICAL

None defined

MAJOR AQL = 1.0%	
101. Broken, deformed, or bent assembly	Visual
102. Balance staff inadequately staked or seated	Visual
103. Metal defective	Visual

4.3.2.5 Wheel and Pinion Escapement Drawing D10523170 covering a detail of Drawing D11740782.

CRITICAL

None defined

MAJOR AQL = 1.0%	
101. Circular runout of escape wheel and pinion, improper	Gage
102. Perpendicularity of escape wheel and pinion, improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
103. Broken or missing teeth, deformed or bent assembly	Visual
104. Escape wheel inadequately staked or seated	Visual
105. Metal defective	Visual

4.3.2.6 No. 1 Gear and Pinion Assembly, Drawing D10523167 covering a detail of Drawing D11740782.

CRITICAL

None defined

MAJOR AQL = 1.0%

101. Circular runout of gear and pinion, improper	Gage
102. Perpendicularity of gear and pinion, improper	Gage
103. Broken or missing teeth, deformed or bent assembly	Visual
104. Gear and pinion inadequately staked or seated	Visual
105. Metal defective	Visual

4.3.2.7 Rotor Assembly, Drawing D10551356 covering a detail of Drawing D11740782.

CRITICAL

None defined

MAJOR AQL = 1.0%

101. Circular runout of rotor assembly, improper	Gage
102. Perpendicularity of rotor assembly, improper	Gage
103. Broken or missing teeth, improper assembly	Visual
104. Metal defective	Visual

4.3.2.8 Escape Wheel, Drawing D10523171 covering a detail of Drawing D11740782.

CRITICAL

None defined

MAJOR AQL = 1.0%

101. Escape wheel contour, improper	Gage
102. Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.9 Movement, D.A.M. Assembly Drawing D11740782.

Defect	Method of Inspection
CRITICAL	
1. Interference condition which precludes return of either spring-loaded block from the fully open position to engagement in the rotor recess. (Check prior to nonarming test.)	Visual/Manual
2. Rotor not locked in unarmed position (see 6.2.3). Check immediately prior to packing.	Visual/Manual
MAJOR AQL = .40%	
101. Length from bottom plate to top plate including all protrusions, exceeds max.	Gage
102. Insecure, improper or incomplete assembly	Visual
103. Staking missing or inadequate	Visual
104. Metal defective	Visual
105. Burrs	Visual
106. Foreign matter	Visual
107. Threads damaged	Visual
108. Nomenclature missing, incorrect or illegible	Visual

4.3.2.10 Tray, Plastic, Drawing No. C9270759.

CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Tray damages so that contents are exposed or liable to become exposed	Visual

4.3.2.11 Bag, Plastic, Polyethylene, Drawing C9270759.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.11 (Cont'd)

	Defect	Method of Inspection
MAJOR	AQL = 1.0%	
101.	Bag torn	Visual
102.	Excess air in bag	Visual
103.	Heat seal inadequate per test requirements of MIL-P-116	Visual

4.3.2.12 Box, Fiberboard, Drawing C9270759.

CRITICAL		
	None defined	
MAJOR	AQL = 1.0%	
101.	Assembly damaged so that contents are exposed or liable to become exposed	Visual
102.	Sealing tape on top and bottom seams incomplete, badly wrinkled, or not in contact with surface containers	Visual
MINOR	AQL = 2.5%	
201.	Contents move when shaken	Visual
202.	Marking misleading, incorrect or illegible	Visual

4.3.2.13 Bag, Barrier, Drawing C9270759.

CRITICAL		
	None defined	
MAJOR	AQL = 1.0%	
101.	Bag torn	Visual
102.	Excess air in bag	Visual
103.	Heat seal inadequate per test requirements of MIL-P-116	Visual
MINOR	AQL = 2.5%	
201.	Marking misleading, incorrect or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.14 Box, Wirebound Packing, Drawing C9272185.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR AQL = 1.0%	
101. Board broken	
102. Contents exposed	
103. ICC symbol misleading incorrect or illegible	
104. Wire missing, broken or loose	
MINOR AQL = 2.5%	
201. Contents move when shaken	Visual
202. Marking misleading, incorrect or illegible	Visual

4.3.3 Inspection testing.-The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness (destructive).-Twenty (20) samples from each lot of the following components shall be subjected to the hardness test. Failure of any component to comply with the requirements specified on the applicable drawing shall be cause for rejection of the lot (see 4.4.1).

Component	Drawing No.
Wheel, Escapement	D10523171
Pin, Pallet	B10523175

4.3.3.2 Static load (destructive).-Fifty (50) samples from each lot of the following subassemblies shall be subjected to the static load test. Failure of any subassembly to comply with the requirement specified on the applicable drawing shall be cause for rejection of the lot of subassemblies, as applicable (See 4.4.2).

Pallet Assembly	D10523174
Wheel and Pinion Escapement Assembly	D10523170
No. 1 Gear and Pinion Assembly	D10523167

4.3.3.3 Arming.-Movement assembly (non-destructive).-Each movement assembly shall be subjected to the arming test. Failure of the rotor mechanism assembly to become locked in alignment with the flash hole, when spun at the Arming Spin Requirement on Drawing D11740782 shall be cause for rejection of the assembly (see 4.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.3.4 Non-arming (non-destructive).-Movement assembly shall be subjected to a non-arming test. Failure of the rotor to remain locked in the unarmed position by either or both spring loaded blocks, when subjected to the Non-Arm Spin Requirement on Drawing D11740782 shall be cause for rejection of the assembly (see 4.4.4).

4.3.3.5 Environmental tests (destructive).-Thirty (30) movement assemblies from each production lot shall be subjected to the following MIL-STD-tests (see 4.4.5).

Test	Quantity	Requirement	Test Method	Acceptance Criteria
Jolt	10	3.2.1	4.4.5.1	4.3.3.5.1.1
Jumble	10	3.2.2	4.4.5.2	4.3.3.5.1.1
Transportation-Vibration	10	3.2.3	4.4.5.3	4.3.3.5.1.2

4.3.3.5.1 Acceptance criteria.-Occurrence of any of the following in any movement assembly shall be cause for rejection of the production lot.

4.3.3.5.1.1 Jolt and Jumble.

a. Rotor armed or partially armed (see 6.2.1 and 6.2.2)
b. Broken, deformed or displaced parts which render the movement assembly unsafe to handle or dangerous to use.
c. Failure of the movement assembly to meet the non-arming requirements of the applicable drawing.

4.3.3.5.1.2 Transportation-Vibration

a. Conditions listed in 4.3.3.6.1.1
b. Failure of the movement assembly to meet the arming and nonarming requirements of the applicable drawing.

4.3.3.6 Ballistics (destructive).-Sixty (60) movement assemblies from each lot shall be subjected to the following ballistic test phases: (see 4.4.6)

Phases Ambient	Quantity	Required	Test Method
Impact Nonfunction Distance	20	3.5.2	4.4.6.1
Impact Function Distance	20	3.5.3	4.4.6.2
Ground or Water Impact	20	3.5.4	4.4.6.3

4.3.3.6.1 Acceptance criteria.-The occurrence of the following shall be cause for rejection of the lot the ballistic sample represents:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.3.6.1 (Cont'd)

a. A premature burst in any phase (see 6.3.1)
b. Function of one or more rounds upon target impact in the Impact Nonfunction Phase.
c. Failure of more than one round total to function in either of the following phases:

(1) Target Impact Function Phase.
(2) Ground or Water Impact Phase.

4.3.4 Inspection equipment.-The examinations and tests shall be made using equipment listed in IEL-11740782. Equipment design shall be in accordance with the code designation on the applicable IEL.

4.4 Test method and procedures.

4.4.1 Hardness.-The test shall be performed using the value as specified on the applicable drawing. Samples shall be tested in an area which is solidly supported in order to obtain valid readings. The median value of three hardness readings taken on each sample unit shall be used as the individual reading. All tested samples shall be scrapped.

4.4.2 Static load.-All units shall be tested to the value specified on the applicable drawing. All units subjected to the static load test shall be scrapped.

4.4.3 Arming-movement assembly.-The unarmed movement assembly shall be spun for period of 10 seconds maximum in a counterclockwise direction when viewed from the top, at a constant r.p.m. as specified on drawing D11740782. After the test has been performed, the rotor shall be returned to the unarmed position (see 6.2.1 and 6.2.3).

4.4.4 Non-arming.-The unarmed movement assembly (see 6.2.3) shall be spun for a period of 3 seconds minimum in a counterclockwise direction when viewed from the top, at a constant r.p.m. as specified on Drawing D11740782. The non-arming test shall be the last spin test to which the movement assembly is subjected prior to packing.

4.4.5 Environmental test procedures.-The component parts of the movement assembly, which have been disassembled and inspected following tests, shall be scrapped.

4.4.5.1 Jolt.-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 101. The movement assembly shall be disassembled and inspected as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.4.5.1 (Cont'd)

a. Check position of rotor

b. Subject the movement assembly to the non-arming requirements of the applicable drawing

c. Remove top plate

d. Check for broken, deformed or displaced parts (that would render the movement assembly unsafe to handle and dangerous to use).

4.4.5.2 Jumble.-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 102. The movement assembly shall be disassembled and inspected as follows:

a. Conditions listed in 4.4.5.1

4.4.5.3 Transportation-Vibration.-The test shall be performed in accordance with the procedure specified in MIL-STD-331, Test No. 104.

a. Check position of rotor.

b. Spin for movement assembly non-arming requirement

c. Spin for movement assembly arming requirements

d. Conditions listed in 4.4.5.1 (c and d)

4.4.6 Ballistics.-The movement assembly, Drawing D11740782, shall be assembled to form a booster M125A1 sub-assembly F10520748 then assembled to fuze, PD, M48A3 and a suitable projectile and fired as follows:

4.4.6.1 Impact nonfunction distance phase.-The test sample shall be fired as specified in 3.5.2 against a suitably supported one inch plywood screen of adequate size under condition delineated in 4.2.5 or 4.3.3.6 as appropriate. Observation of impact element function is required.

4.4.6.2 Impact function distance phase.-The test sample shall be fired as specified in 3.5.3 against a suitably supported one inch plywood screen of adequate size under condition delineated in 4.2.5 or 4.3.3.6 as appropriate. Report of subsequent functioning, if a dud on the screen is observed, is required.

4.4.6.3 Ground or water impact phase.-The test sample shall be fired as specified in 3.5.4 under the conditions as delineated in 4.2.5 or 4.3.3.6 as appropriate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, labeling and marking.-Packaging, packing, labeling and marking shall be as specified on Drawing C9272185.

5.2 Data cards.-Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Dimensions.

6.1.1 Compliance with tests (proving ground, ballistic performance and shop) required by the specifications and drawings is mandatory. The contractor will not assume, nor does the Government guarantee, that all possible combinations permitted by the tolerance limits of the specifications and drawings will consistently satisfy the test requirements. Therefore, the manufacturer is obligated to choose those combinations of tolerances and fits within the limits of the specifications and drawings that best suit his process needs and still satisfy the testing requirements.

6.1.2 Dimensions which are specifically referred to in the classification of defects, as listed in Section 4, are mandatory. Pertaining to other dimensions, it is recognized that current mass production methods may occassionally produce parts which are not in full compliance with all dimensional requirements, but which may provide adequate fuze performance. Therefore, the contractor, at his own risk, may utilize these parts provided there is no adverse effect on fuze functionability. This relaxation of requirements spplies to "after the fact" deviations only, to dimensions only, and does not constitute authority to establish new dimensions or to relax efforts to achieve the required sizes within the specified limits. The procedure for accomplishing dimensional changes is available under the established engineering change system. Nothing above is to be construed as relieving the contractor of any responsibility in connection with performance of the fuze.

6.1.3 The contractor shall maintain records showing deviations from dimensional requirements, the extent of such deviations, the amount of material involved, and the date the material is introduced into the assembly line. Copies of these records shall be forwarded to the agency assigned custody of the technical data.

6.2 Armed/Unarmed movement assemblies.

6.2.1 Armed.-Rotor is locked by the spring loaded detent pin in the position in which the detonator is fully visible through the flash hole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

6.2.2 Partially armed.-One or both spring-loaded safety blocks not fully seated in the rotor slots and locking the rotor.

6.2.3 Unarmed.-Rotor locked by both spring loaded safety blocks with the detonator not at all visible through the flash hole.

6.3 Ballistic parameters.

6.3.1 Premature burst.-Shall be defined as the occurrence of any of the following:

a. If the round detonates in the bore of the weapon.
b. If the round detonates in flight within 180 feet from the muzzle of the weapon.

6.3.2 Muzzle velocities mentioned in this specification are nominal only and are given for the guidance of the proving ground in selecting appropriate weapons and rounds.

6.4 Ordering data.-Procurement documents should specify the title, number and date of this specification.

Custodian

Army - MU

Preparing activity

Army - MU(FA)

Project No. 1390-A107

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.