MILITARY SPECIFICATION

MOUNTING KIT, ROLLER, MINE CLEARING:

TRACK-WIDTH, TANK-MOUNTED

This amendment forms a part of MIL-M-53008(ME), dated 8 July 1982, and is approved for use within the USA Belvoir Research and Development Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, under SPECIFICATIONS, MILITARY add:

*	"MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
*	MIL-C-22750	- Coating, Epoxy Polyamide.
	MIL-R-53007	- Roller Kit, Roller, Mine Clearing: Track-Width, Tank-Mounted."

PAGE 2

* Under STANDARDS, MILITARY add:

"MIL-STD-838	- Lubrication of Military Equipment.
MIL-STD-889	- Dissimilar Metals."

2.1.1, after STANDARDS add:

"HANDBOOKS

MILITARY

MIL-HDBK-113	- Guide for the Selection of Lubricants, Fluids, Preservatives and Speciality Products for Use in Ground Equipment Systems."

FSC 1095

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

* Under 3.4, add new paragraphs:

"3.4.1 Material deterioration and control. The item shall be fabricated from compatible materials, inherently corrosion resistant, or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operation and storage environments to which the item may be exposed.

3.4.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.4.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and subcomponents, and shall make information available upon request to the contracting officer or designated representative."

* 3.7.1, line 3, delete "Type A color forest green." and substitute "Type F or G as applicable. Unless otherwise specified (see 6.2) top coat color shall be camouflage green 383 conforming to MIL-C-46168. The kit shall then be overcoated in accordance with the Government furnished camouflage patterns with MIL-C-46168 top coat of the colors specified in the camouflage patterns."

* 3.7.2, line 3, delete "Type A, color white enamel." and substitute "Type F or G as applicable, color white 17925 in accordance with MIL-C-22750."

3.9.2, line 8, after "used.", add the following new sentences:

"Welds shall not exceed the next 1/16 inch larger size for welds up to 3/8 inch. For welds 3/8 inch and larger the size shall not exceed the next 1/8 inch larger size. Welds shall not be undersize."

3.10, add new paragraphs:

"3.10 Installation Test. The installation test shall be conducted in accordance with 4.4.3.2."

"3.11 Operational Test. The operational test shall be conducted in accordance with 4.4.3.3."

* 3.12 Government-furnished property. The following property will be furnished by the Government (see 6.5):

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.

Item No.	Description	Identification	Quantity
1	Pattern drawings	Camouflage patterns	As required"

* 3.13 Lubricants. The procedure for the selection of lubricants shall be in accordance with MIL-STD-838, section 5. Lubricants selected shall be in accordance with MIL-HDBK-113, chapter 2. When the specification of the lubricant selected includes a requirement for a qualified products list (QPL), the lubricant supplied shall be from a source that is listed on the applicable QPL."

PAGE 6

Add new paragraphs:

"4.4.3 Tests."

"4.4.3.1 Samples. Samples selected in accordance with 4.4.1 shall be subjected to the following tests, plus any other tests specified by the contracting activity to comply with requirement of 3.3. Failure of any test shall be cause for rejection."

"4.4.3.2 Test Installation of Mine Roller. One mounting kit shall be installed on an M60 tank. One roller kit, mine clearing in accordance with MIL-R-53007 shall be mounted on to the installed mounting kit using the winches and other mounting equipment provided with the mine roller and mine roller mounting kit. The mine roller shall be released and remounted at least twice using the hydraulic release mechanism and twice using the manual release mechanism. During the mounting and release of the roller, the operation shall be observed and any interference of the parts noted."

"4.4.3.3 Operational Test. Following installation of a mine roller, an operational test of the mounting kit shall be conducted consisting of 2 miles of level cross-country operation. During the operational test, both left and right turns and forward and reverse operations shall be demonstrated. Following the operational test, the mine roller shall be released and remounted at least twice using the hydraulic release mechanism and twice using the manual release mechanism. During the mounting and release of the roller, the operation shall be observed and any interference of the parts noted. Initial production operational tests for a mine roller kit and a mine roller mounting kit may be run concurrently."

PAGE 7

Table I, under major characteristics add:

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:49Z
Check the source to verify that this is the currentversion before use.

"TABLE I. Examination schedule.

Initial production	Quality conformance	Characteristics	Requirement paragraph
1	2	3	4
		CRITICAL	
X	X	1. Camouflage pattern data not as specified.	3.12
		MAJOR	
X	X	101. Dimensions are not as specified.	3.2
X	X	102. Parts and components are not complete.	3.2
X	X	103. Material is not as specified.	3.4
* X	X	104. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environment as specified.	3.4.1
* X	X	105. Dissimilar metals as specified in MIL-STD-889 are not effectively insulated from each other as specified.	3.4.2
* X	X	106. Contractor does not have documentation available for identification of material, material finishes or treatments as specified.	3.4.3
X	X	107. Safety is not as specified.	3.5
X	X	108. Parts are not interchangeable.	3.6
* X	X	109. Treatment and painting not as specified.	3.7.1, 3.7.2
* X	X	110. Paint color not as specified.	3.7.1, 3.7.2
X	X	111. Workmanship is not as specified.	3.9
X	X	112. Welding certification is not furnished.	3.9.2.1
X	X	113. Mounting kit cannot be installed.	3.10
X	X	114. Interferance noted.	3.10, 3.11
X	X	115. Operation not as specified.	3.11
* X	X	116. Camouflage patterns not as specified.	3.12

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

"TABLE I. Examination schedule. (Continued).

Initial production	Quality conformance	Characteristics	Requirement paragraph
1	2	3	4
* X	X	117. Lubricants not as specified.	3.13
		MINOR	
X	X	201. Identification marking is not as specified.	3.8"

PAGE 8

* 4.7.1, delete "Preproduction" and substitute "First article".

* 4.7.1.1, line 1, delete "preproduction" and substitute "first article".

PAGE 9

* 5.1, delete in its entirety and substitute:

"5.1 First article pack. The contractor shall furnish a first article pack for examination within the time frame specified (see 6.2) to prove prior to starting production packaging the applied preservation, packing and marking comply with packaging requirements of this specification. Examinations shall be those specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The first article pack may be prepared utilizing either the first article kit or a production mounting kit. When the first article kit is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the first article kit and production kit."

PAGE 10

6.2 delete in its entirety and substitute:

* "6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Date of issue of DODISS applicable to this contract and exceptions thereto (see 2.1.1).
* c. Time frame required for submission of initial production model (see 3.3).
d. Government and contractor testing responsibilities (see 4.1).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.

* e. Color required when other than specified (see 3.7).
* f. Time frame when camouflage pattern data (see 3.12) is required.
g. Data requirements (see 3.9.2.1 and 4.1).
h. Test requirements (see 4.4.3).
i. Time frame required for submission of first article pack (see 5.1).
j. Degree of packing required (see 5.3).

* 6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, contract data requirements list (CDRL), the data requirements identified below shall be developed as specified by an approved data item description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DOD FAR Supplement, Para 27, Sub-Part 27.410-6 are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph No.	Data Requirements	Applicable DID No.
(a) 3.12	Camouflage Pattern Photos	UDI-V-24003/M (see figure 1)
(b) 3.12	Camouflage Pattern Illustrations	DI-M-30420/M (see figure 2)

* 6.3, lines 1, 2 and 3, delete "preproduction" and substitute "first article".

Add new paragraphs:

"6.5 Government-furnished property. The contracting officer should arrange to furnish the property listed in 3.12.

* 6.6 Lubricants. MIL-STD-838, Lubrication of Military Equipment, prescribes the policy for using specification-type products wherever possible and provides specific requirements for potential use of non-standard proprietary products. MIL-STD-838 is implemented by MIL-HDBK-113, Guide for the Selection of Lubricants, Fluids, Preservatives and Speciality Products for Use in Ground Equipment Systems. The contracting officer should note that unless otherwise authorized by the US Army Belvoir Research & Development Center (ATTN: STRBE-VF), Fort Belvoir, VA 22060-5606, lubricants, fluids, and greases for ground equipment systems must be restricted to those listed under MIL-HDBK-113, chapter 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
Army - AT

Project 1095-A178

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

DATA ITEM DESCRIPTION	2. IDENTIFICATION NO(S).	
	AGENCY	NUMBER
1. TITLE PHOTOGRAPHIC PRINTS AND SLIDES	NAVY-YD	UDI-V-24003B/M
3. DESCRIPTION/PURPOSE This data consists of photographic prints and/or slides which provide a pictorial medium for exchange of technical information between developing Agency and users and becomes a permanent historical and legal record by recording configuration during the course of program development.	4. APPROVAL DATE 13 June 1972	
	5. OFFICE OF PRIMARY RESPONSIBILITY NAVFAC 0434	
	6. DDC REQUIRED	
	8. APPROVAL LIMITATION	
7. APPLICATION/INTERRELATIONSHIP 7.1 Deliverable data covered by this DID and specified in block 16 of the CDRL, is required as a visual record of equipment procured under contract.	9. REFERENCES (Mandatory as cited in block 10)	
	MCSL NUMBER(S)	

10. PREPARATION INSTRUCTIONS

10.1 These photographs shall be standard 8x10 inch prints and furnished in 2x2 inch cardboard frames; and unless otherwise specified on the DD Form 1423. Views shall include, but not be limited to, a front, side, and rear view. Background of photographs shall be void of unrelated objects.

10.2 Interior views shall be in sufficient quantity to show arrangement and layout of installed equipment.

10.3 Photographic prints shall show excellent detail and shall be color suitable for reproduction.

DD FORM 1664

FIGURE 1. Camouflage pattern photos.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

DATA ITEM DESCRIPTION	2. IDENTIFICATION NO(S).	
	AGENCY	NUMBER
1. TITLE Technical Illustrations and Graphs	USAF	DI-M-30420/M
3. DESCRIPTION/PURPOSE To provide wave plotting, drafting, computations, data reduction and/or mathematical analysis in support of research projects.	4. APPROVAL DATE 29 Oct 1976	
	5. OFFICE OF PRIMARY RESPONSIBILITY AFSC	
	6. DDC REQUIRED	
	8. APPROVAL LIMITATION	
7. APPLICATION/INTERRELATIONSHIP Mathematical Services Projects	9. REFERENCES (Mandatory as cited in block 10)	
Replaces (U)M-177/ESD	MCRL NUMBER(S)	

10. PREPARATION INSTRUCTIONS

Data will encompass plotting, drafting and artistic creative illustrations of apparatus and devices. The work may include three-dimensional pictorial representations. Completed reproducible art work must be of sufficiently high quality to be used for publication in technical journals and for visual aids at conferences, reviews and briefings.

DD FORM 1664

FIGURE 2. Camouflage pattern illustrations.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:49Z
Check the source to verify that this is the current version before use.