A-A-2559
April 7, 1988
SUPERSEDING
00-D-420B
October 19,1973
FCNE-86-421
July 16, 1986

COMMERCIAL ITEM DESCRIPTION

DISHWASHING MACHINE, HOUSEHOLD (ELECTRIC)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers an electric household dishwashing machine with pump drain, commercially produced, for use in a domestic kitchen for permanently connected undercounter installation without power cord.

Salient characteristics:

1 Standard product. The dishwashing machine provided under this purchase description shall be in accordance with ANSI/AHAM Standard DW-1.

2 Safety. The dishwasher shall be in accordance with Underwriters Laboratories Inc. (UL) Standard UL 749. Acceptable evidence of meeting the requirements of this standard shall be the UL label or listing mark, or a certified test report from a recognized testing laboratory acceptable to the Government, indicating that the dishwasher has been tested to the applicable requirements of UL 749.

3 Components. The dishwasher shall be designed for under-counter installation with a counter-balanced pull-down door, slide out racks, tub, spraying system, detergent dispenser, motors, and switches (including an energy saving switch).

3.1 Racks. The racks for dishes and silverware shall be made of plastic, plastic-coated, or rubbercoated steel wire in accordance with commercial practice. A removeable silverware basket is acceptable.

3.2 Materials.

3.2.1 Tub. The tub shall be made of commercial grade steel not less than 20 gauge with a porcelain enamel or bonded plastic on steel finish or of a polypropylene material. The polypropylene material shall meet the endurance requirements of UL.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

3.2.2 Door. The inside door panel of the metal door shall be made of commercial grade steel with a porcelain enamel or bonded plastic on steel finish or a polypropylene material. The polypropylene material shall meet the requirements of UL.

3.3 Motors. The motors shall be in accordance with UL Standard No. 749. The motor bearings shall have maintenance free permanent lubrication.

3.4 Gaskets. The gaskets shall resist deterioration when exposed to heat and detergents. A manufacturer's certificate of compliance is acceptable.

3.5 Drain air gap. If needed, the installer shall provide a drain air gap.

4 Electrical characteristics. The dishwashers shall operate on a nominal 115/120 volt, 60 Hertz, 3-wire grounding, single phase alternating current system.

5 Dimensions. Dimensions shall be in inches with optional centimeter equivalents in parentheses. Overall dimensions shall be as follows in table I.

TABLE I, DIMENSIONS

| Characteristics | Minimum (Alcove) | Maximum |
|---|---|---|
| Width | 23.5 (60.9) | 26 (66.0) |
| Depth | 24 (60.9) | 26 (66.0) |
| Height | 34 (86.4) | 36 (91.4) |

6 Automatic control. The automatic control shall cycle through the wash, rinse, dry, and stop phases. The automatic control shall also be capable of manual setting to repeat or skip any phase of the cycle. The automatic control shall have one off and not less than the following automatic cycles: heavy wash, normal wash, low energy wash, and rinse and hold. Nomenclature may vary but wash action must be equivalent.

7 Switch, safety-interlock. The dishwasher shall be equipped with a switch that will automatically stop the machine operation when the door is opened.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

8 Finish.

8.1 Enamel. Unless otherwise specified, the front panel, door front, and side panels (if any) shall be white in color with a baked-on enamel finish. The inside door panel and the interior of the tub when fabricated from steel, shall be covered with porcelain enamel or bonded plastic finish which resists acid, alkali, and staining. There shall not be any drips or runs in the enamel.

8.2 Porcelain enamel. The porcelain enamel finish shall have a glossy finish and be free from discolorations, cracks, thin spots, holes, burn-off, wrinkles, waviness, or other imperfections affecting appearance.

8.3 Polypropylene. The polypropylene tub and inside door panel shall have a smooth finish, resists acid, alkali, and staining and be warranted for ten years.

9 Life cycle costing. The life cycle costing shall be in accordance with the solicitation.

10 Instructions. Instruction booklets giving operation, installation, and maintenance instructions, dimensions, electric data and other pertinent data shall be supplied with each machine. The contractor shall also furnish copies of the manufacturers' illustrated repair parts manual as specified in the purchase order or contract.

11 Identification. The dishwasher shall be permanently marked with serial number and model number and with the manufacturers name, trade name, or trademark. In addition, the electrical characteristics and information required by UL 749 shall appear.

12 Standards. The issues of ANSI/AHAM DW-1, UL Standard 749, and NEMA MG-1 in effect on the date of the solicitation shall be used to determine compliance with the stated requirements.

13 Inspection. Completed dishwashers shall be sampled in accordance with MIL-STD-105. Examine for visual and dimensional defects using level S-2, Acceptable Quality Level (AQL) of 4.0. Test for compliance with paragraphs 3, 4, 6, and 7 using level S-2, AQL of 1.5.

14 Regulatory requirements. The offerer/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

15 Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

16 Workmanship. The finished article shall be clean, well made, and free from defects which may affect appearance, serviceability or durability.

17 Notes.

17.1 The commercial item certification clause is not required in the solicitation, when this commercial item description is used for procurement.

17.2 UL Standards are available from Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.

17.3 ANSI Standards are available from the American National Standards Institute Inc., 1430 Broadway, New York, NY 10018.

17.4 NEMA Standards are available from the National Electrical Manufacturers Association, 2101 L Street, N. W., Washington, DC 20037.

17.5 MIL-STD-105 is available from the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

17.6 The NSN for this item is 7320-01-026-4064

MILITARY INTERESTS:

NONE: DoD has waived coordination on this commercial item description until further notice.

PREPARING ACTIVITY:

GSA - FSS/FCNE
VA - 088



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.