[INCH-POUND]
A-A-2703
March 19, 1991
SUPERSEDING
(See section 6)

COMMERCIAL ITEM DESCRIPTION

DISPENSERS, SOAP

The General Services Administration has authorized the use of this commercial item description.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This commercial item description covers rigid dispensers suitable for dispensing waterless paste, liquid, and powdered soap.

1.2 Classification. The soap dispensers shall be of the following types.

Type I - Waterless paste dispenser for use with a one-gallon disposable container.

Type II - Waterless paste dispenser with integral refillable container.

Type III - Liquid soap dispenser.

Type IV - Powdered soap dispenser.

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of the invitation for bids or request for proposal unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 4510

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:25Z
Check the source to verify that this is the current version before use.

Federal Standard:

FED-STD-376 - Preferred Metric Units For General Use By The Federal Government.

Copies of commercial item descriptions and Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E 29 - Standard Practice For Using Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

3. SALIENT CHARACTERISTICS

3.1 Standard commercial product. Except as otherwise specified herein, soap dispensers shall be the manufacturer's standard commercial product for mounting on a flat vertical surface.

3.2 Materials. Unless otherwise specified (see 6.1), parts in contact with soap shall be stainless steel, chromium plated brass, chromium plated carbon steel, chromium plated aluminum, chromium plated zinc die casting, or plastic.

3.3 Mounting. A wall type bracket or holder with not less than three mounting screws shall be furnished with each dispenser. The dispensers shall be fully assembled and ready for mounting.

3.4 Finish. Unless otherwise specified (see 6.1), all exposed or visible metal parts except stainless steel shall be chromium plated. Stainless steel shall have a polished finish conforming to the manufacturer's standard product. Exposed or visible plastic shall be chromium plated, or white plastic, or the manufacturer's standard pastel color, or have a white baked on enamel finish at the manufacturer's option.

3.5 Maintenance. Dispensers shall be capable of being cleaned, filled, and repaired without the use of special tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

3.6 Instructions. Installation, operation, and maintenance instructions shall be provided with each dispenser. The instructions shall include repair procedures and a listing of available repair parts.

3.7 Leakage. No evidence of leakage shall be observed on type I, II, or III dispensers when tested in accordance with 4.6.3.

3.8 Type I. Type I dispensers shall consist of a rigid body which incorporates an actuating device and a dispensing nozzle capable of dispensing waterless paste or cream hand cleaner from a one-gallon disposable container.

3.8.1 Reservoir. Type I dispensers shall have a circular reservoir with an inside diameter of 5-7/8 inches, plus 1/16 minus 0-inches and a depth of at least 1-1/4 inches, capable of holding a one-gallon container of such diameter.

3.9 Type II. Type II dispensers shall consist of a rigid body which incorporates an actuating device, a dispensing nozzle, and an integral refillable container, capable of dispensing waterless paste or cream hand cleaner.

3.9.1 Refillable soap container. The refillable soap container shall be designed for use with a follower plate or plunger which rests on top of the soap and follows the soap level down as the soap is dispensed. Provisions will be made to prevent air lock in the soap and feed system.

3.9.2 Capacity. The integral refillable container shall have a 40 fluid ounce minimum capacity when tested in accordance with 4.6.2.

3.10 Type III. Type III dispensers shall dispense liquid soap by means of a spring action push-in valve or other suitable pump action design. The dispensing mechanism shall be capable of being operated with one hand while dispensing soap. The dispenser shall be self-priming and except for initial use after filling or refilling, shall not require more than one positive action to begin dispensing liquid soap.

3.10.1 Capacity. The liquid soap dispenser shall have a 10 fluid ounce minimum capacity when tested in accordance with 4.6.2.

3.11 Type IV. Type IV dispensers shall be equipped with a soap feed mechanism and an agitator designed to break up powdered soap with each positive action of the dispensing mechanism. The discharge opening and dispensing mechanism shall be so arranged that the soap shall not be subjected to wetting during normal use. The dispenser shall be capable of dispensing powdered soap.

3.11.1 Capacity. The powdered soap dispenser shall have a 20 fluid ounce minimum capacity when tested in accordance with 4.6.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

3.12 Workmanship. The soap dispensers shall be free of sharp edges and projections, burrs, ridges, seam lines, porosity, cracks, peeling, scratches, or other defects affecting their appearance, function, and serviceability.

3.13 Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

3.14 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch/pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

3.15 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. The levels of inspection and acceptable quality level (AQL) shall be in accordance with MIL-STD-105.

4.3 Lot formation. All soap dispensers of the same type from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

4.4 Visual and dimensional examination. A random sample of dispensers shall be selected from each lot for visual and dimensional examination in accordance with inspection level S-3, acceptable quality level (AQL) 6.5, expressed in terms of percent defective to verify compliance with this description. The sample unit shall be one dispenser. Tolerance limits specified are absolute limits as defined in ASTM E 29.

4.5 Sampling for tests. A random sample of dispensers shall be selected from each lot in accordance with inspection level S-1, acceptable quality level (AQL) 4.0, expressed in terms of percent defective. The sample unit shall be one dispenser.

4.6 Testing.

4.6.1 Preparation of samples. Each soap dispenser selected in accordance with 4.5 shall be mounted to a rigid, vertical structure or wall in accordance with the manufacturer's instructions.

4.6.2 Capacity. Fill the soap containers with commercially compatible soap and observe for conformance to the minimum capacity requirements specified in 3.9.2, 3.10.1, and 3.11.1.

4.6.3 Leakage. Actuate dispensing mechanism until soap emerges from the dispensing opening. Wipe excess soap from the dispensing opening with a clean dry cloth. After 24 hours, examine and determine conformance to 3.7.

4.6.4 Valve operating mechanism. Determine ease of operation during actuation of the valve for conformance to 3.10.

4.6.5 Self-priming. Determine self-priming requirements of the dispenser for conformance to 3.10.

4.8 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate, and shipping containers (as applicable) for conformance with the preservation, packaging, packing, labeling, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, acceptable quality level (AQL) 6.5, expressed in terms of defects per hundred units.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Type required (see 1.2).
c. Material required, if other than specified (see 3.2 and 3.4).
d. The preservation, packaging, packing, labeling, and marking desired.

6.2 Part Numbering. Soap dispensers conforming with this commercial item description shall be identified by a part number configuration consisting of identification of a portion of the specification number and type. An example of the part number configuration is shown below. This part numbering system is intended for identification and cross-indexing of the item within the Federal cataloging system. Part numbers are not required to be placed on the product or container.

```
AA2703-1
      | |____ 1 - Type I
      |       2 - Type II
      |       3 - Type III
      |       4 - Type IV
      |
      |_____ General specification number.
```

6.3 Referencing NSN's. The following NSN's reference this document (this may not be a complete list):

4510-00-919-1217	Type I	- P/N AA2703-1
4510-00-965-1134	Type II	- P/N AA2703-2
4510-00-203-2707	Type III	- P/N AA2703-3
4510-00-203-2709	Type IV	- P/N AA2703-4

6.4 Supersession data. This commercial item description supersedes Commercial Item Descriptions A-A-274, A-A-275, A-A-276, dated September 30, 1979; and Federal Specification FF-D-396H, dated March 9, 1977.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:25Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Military Coordinating Activity

Navy - YD

Custodians:

Navy - YD
Air Force - 84

Review Activity:

DLA - CS

User Activity:

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

VA - OSS
GSA - PBQ

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:25Z
Check the source to verify that this is the current version before use.