[METRIC]

A-A-2877
September 29,1994

COMMERCIAL ITEM DESCRIPTION

DRUMS, SHIPPING, STEEL DOT-6A, DOT-6B, DOT 17C AND POP

The General Services Administration has authorized the use of this commercial item description by all Federal agencies.

A. SCOPE

This Commercial Item Description covers the requirements for new, full removable head, steel drums of 113.55-liter (30-gallon) and 208.175-liter (55-gallon) capacity, that meet the Department of Transportation, and the United Nations Performance Oriented Packaging (POP) standards on the transport of dangerous goods for the shipment of white or yellow phosphorous.

B. CLASSIFICATION

B.1 Types. Types I, II, III and IV shall use galvanized steel (see c.2). Types V and VI shall use sheet steel (see c.1).

I-113.55 liters (30 gallons), DOT-6A-480, 14 gage, with RO-Bar rolling hoops made of 1.91 cm (3/4") schedule 40 pipe with an outside diameter of 2.667 cm (1.05") with a nominal weight of 16.8 grams per linear centimeter (1.13 pounds per linear foot), welded bottom chime or double seamed, and then welded with bottom chime reinforcement.

II-113.55 liters (30 gallons), DOT-6A-480, 14 gage, with RO-Bar rolling hoops made of 1.91 cm (3/4") schedule 40 pipe with an outside diameter of 2.667 cm (1.05") with a nominal weight of 16.8 grams per linear centimeter (1.13 pounds per linear foot), double seamed bottom chime.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: The General Services Administration, Office Supplies and Paper products Commodity Center, Engineering Branch, New York, N.Y. 10278.

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

FSC 8110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

III-113.55 liters (30 gallons), DOT-6B-480, 16 gage, with RO-Bar rolling hoops made of 1.91 cm (3/4") schedule 40 pipe with an outside diameter of 2.667 cm (1.05") with a nominal weight of 16.8 grams per linear centimeter (1.13 pounds per linear foot), double seamed bottom chime.

IV-113.55 liters (30 gallons), DOT-6B-480, 16 gage, with swedged-in rolling hoops, double seamed bottom chime.

V-113.55 liters (30 gallons) DOT-17C, 18 gage with two rolled or swedged-in rolling hoops, 12 gauge bolted ring with forged lugs and 0.95 cm (3/8 inch) bolt and nut, welded body seams and doubled seamed bottom chime.

VI-208.175 liters (55 gallons) DOT-17C, 16 gage with three rolled on swedged in rolling hoops, 12 gage bolted ring with forged lugs and 1.59 cm (5/8 inch) bolt and nut, welded body seams and doubled seamed bottom chime.

C. SALIENT CHARACTERISTICS

C.1 Sheet steel. Sheet steel shall be of the required U.S. Manufacturers' Standard gage, low-carbon, hot-rolled, or cold-rolled steel, commercial quality.

C.2 Galvanized steel. Galvanized steel shall be commercial quality mill galvanized steel sheets. The Galvanized coating shall be a minimum of 1.25 ounces per square foot in accordance with ASTM A90.

C.3 Gaskets. Gaskets shall be made of a suitable phosphorus resistant material.

C.4 Enamel. All drums shall be painted using enamel that conform to MIL-D-6054. Unless otherwise specified color shall be in accordance with Fed. Std. 595, No. 24064.

C.5 Tests. Drums shall pass all tests required by the United Nations Performance Oriented Packaging (POP) standards on the transport of dangerous goods for the shipment of white or yellow phosphorus, dry or in water. Drums shall also comply with applicable requirements of the Department of Transportation (DOT), (see B.1). Certification in writing to that effect must be submitted by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

C.6 Marking. Each drum shall be plainly and permanently marked by embossing on the top, and stencilling on the sides with letters, a minimum 1.27 cm (1/2-inch) in height as follows:

C.6.1 The DOT symbol to certify that the drum complies with all the requirements of the applicable specification (see B.1) and as applicable apply the load limit marking.

C.6.2 The mark "U.S." which shall show that the drum has been purchased by and is the property of the Federal Government. When the drum is procured incident to the procurement of the product contained therein, the embossing "U.S." may be omitted.

C.6.3 The standard gage of steel at the thinnest portion of the drum, the rated capacity of the drum in liters as well as in gallons, and the year of manufacture shall be abbreviated and appear in the following order: Gage, capacity, and year; for example, 16-113.55 liter (30 gal)-95, which will indicate that the drum is of 16-gage steel, is 113.55 liter (30 gallons) rated capacity, and was made in 1995.

C.6.4 The name, initials, or symbol of the manufacturer, as recorded with the Bureau of Explosives.

C.6.5 Applicable United Nations markings for dangerous goods.

D. REGULATORY REQUIREMENTS

In accordance with section 23.403 of the Federal Acquisition Regulations, the government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements of exposing suppliers' employees to undue hazards from the recovered materials.

E. QUALITY ASSURANCE PROVISIONS

E.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commmercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:26Z
Check the source to verify that this is the currentversion before use.

E.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

E.3 Each lot of drums shall be inspected for conformance to the requirements herein. Inspection shall be in accordance with MIL-STD-105 using the sampling plans specified below.

E.4 Visual characteristics - Inspection level S-4 with an Acceptable Quality level (AQL) of 4.0 percent defective. The sample unit shall be one drum.

E.5 Dimensional characteristics - Inspection level S-2 with an Acceptable Quality level (AQL) of 4.0 percent defective. The sample unit shall be one drum.

F. PACKAGING.

Packaging, packing, labeling and marking shall be as specified in the contract or order.

G. NOTES.

G.1 Application for Copies of Documents Referenced Herein:

The issue date in effect on date of invitation for bids or request for proposal shall apply.

G.1.1 MIL-STD-105 "Sampling Procedures and Tables for Inspection by Attributes" is available from Standardization Documents Order Desk; Building 4D; 700 Robbins Avenue; Philadelphia, PA 19111-5094.

G.1.2 'ASTM A90 "Standard Test Method on Weight of Coating on Zinc-Coated (Galvanized) Iron or Steel Articles" is vailable from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:26Z
Check the source to verify that this is the current version before use.

G.1.3 MIL-D-6054 "Drum, Metal-Shipping and Storage" is available from Standardization Documents Order Desk; Building 4D; 700 Robbins Avenue; Philadelphia, PA 19111-5094.

G.1.4 FED-STD-595 "Colors used in Government Procurement" and DOT Specifications are available from the U.S. Government Printing Office, Washington, DC 20402.

G.1.5 "Recommendations on the Transport of Dangerous Goods" is available from United Nations Publications, DC2-853, 2 UN Plaza, New York, N.Y. 10017.

G.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description
(b) Type of drum (see B.1)
(c) Color of enamel (see C.4)
(d) Packaging, packing, labeling and marking.

NO OFFICIAL DOD INTEREST
HAS BEEN REGISTERED

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:26Z
Check the source to verify that this is the current version before use.