[INCH-POUND]
A-A-2934
NOVEMBER 30, 1995
SUPERSEDING
GGG-I-100B
January 20, 1992

COMMERCIAL ITEM DESCRIPTION

ICE SCRAPER AND CHIPPER, SIDEWALK

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for the ice scraper specified in GGG-I-100B for all federal agencies.

1. SCOPE.
This Commercial Item Description covers a long-handled tool for scraping, chopping, or removing ice or light snow from walkways.

2. CLASSIFICATION. Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Design. The scraper shall consist of a flat blade and a long, straight handle.

3.2 Blade. The blade shall be of high grade steel of uniform quality. The socket for the handle shall be a minimum of 3-1/4 inches in depth. The socket and shank shall be forged integrally with the blade. The cutting edge of the blade shall be sharpened or beveled. The blade shall be a minimum of 6-5/8 inches wide and a minimum of 5-1/4 inches high. The blade thickness shall be a minimum of 0.090 inch at any point measured above the cutting edge.

3.3 Blade hardness. The blade shall be hardened to 25 to 47 on the Rockwell C hardness scale. When required, the blade hardness shall be tested in accordance with ASTM E18.

3.4 Handle. The handle shall be of seasoned SA grade ash conforming to NN-H-81. The handle shall be smoothly finished and covered with one coat of transparent lacquer, varnish, or wax or one coat after surface treatment utilizing heat, such as flame-treating or charring. The coating shall be applied in a manner to permit visual inspection of the wood and prevent absorption of water.

3.5 Overall length. The overall length of the scraper shall be 55 to 65 inches long.

3.6 Identification marking. The scraper shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Washington, DC 20406

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g. pits, excessive scale, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulations (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Contractor certification. The contractor shall provide certification and maintain substantiating evidence that all items being offered for acceptance meet the requirements of this Commercial Item Description and conform to the manufacturer's drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements."

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample (s) shall be inspected for all salient characteristics. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING. Requirements for preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES. (This section contains information of a general or explanatory nature that is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

7.1 Addresses for obtaining copies of referenced documents.

Federal Specifications: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC, 20407.

Federal Acquisition Regulations (FAR): Government Printing Office Superintendent of Documents, Washington, DC 20401-9371.

ANSI/ASQC Z1.4: American Society For Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 43201-4606.

ASTM E18: American Society For Testing Materials, 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959..

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.

(b) When applicable, the appropriate NSN.

(c) When applicable, the specific type, styles, classes, sizes, etc., as specified in the Commercial Item Description.

(d) If bid samples are required and the number of samples required.

(e) If first article samples are required and the number of samples required.

(f) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample scraper shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0 expressed in terms of defects per hundred units.

(g) What preservation, packaging, and marking are required.

7.3 National Stock Numbers (NSNs). The following NSN is associated with this CID. This list may not be indicative of all possible NSNs associated with this CID:

NSN 5110-00-329-3299

Military Interests:
None: DOD has no registered interest in revisions and notices to this Commercial Item Description until further notice.

Preparing Activity
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.