[Metric]
A-A-2983
December 12, 1995

COMMERCIAL ITEM DESCRIPTION
POINTER, WOOD

The General Services Administration has authorized the use of this Commercial Item Description by all federal agencies. This document replaces AA-P-560a which has been canceled.

1. Scope: This commercial item description covers lecture pointers which are hardwood, having a rubber tip at one end and a metal screw eye at the other end.

2. Salient Characteristics:

2.1 Construction: The pointer shall be made from a wooden rod turned, polished, tapered and corner rounded in accordance with good commercial practice. A screw eye shall be centered in the butt end of the undercut and tapered for a distance of not less than 12.7 mm (1/2 inch). A tapered rubber tip shall be securely fastened with good quality adhesive to the undercut portion of the rod.

2.2 Wood. The body of the pointer shall be of hardwood and shall be uniformly dried to a moisture content of not more than 12 percent. It shall be free from imperfections such as loose knots, chips, dents, pitch pockets, chipouts, splinters and splits. Mineral specks, burls, tight knots, not exceeding 1.588 mm(1/16") in diameter and birds' eyes will be permitted.

2.3 Rubber. Rubber used for the tip shall be white in color and shall be natural rubber, synthetic rubber, or a mixture of natural rubber and synthetic rubber.

2.4 Dimensions. The overall length of the pointer shall be a minimum of 91 cm (36 inches) exclusive of the screw eye. The diameter of the rod shall be approximately 14.3 mm (9/16 inch) measured at 38.1 mm (1-1/2 inches) from the rubber tip and 38.1 mm (1-1/2 inches) from the screw eye respectively. The diameter of the pointer shall be approximately 2.38 mm (3/32 inch) less than the diameter measured at 30.48 cm (12 inches) from the rubber tip. The tip shall be approximately 3.2 cm (1-1/4 inch) in length. Alternatively, the rod may be untapered, in which case the diameter shall be approximately 1/2 inch.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 2FYEE, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

2.5 Screw eye. The screw eye shall be of steel and shall have a bright plated finish. The inside diameter of the screw eye shall be not less than 6.35 mm (1/4 inch).

2.6 Finish. The wooden rod shall have a clear coating of shellac, varnish or lacquer. All surfaces of the pointer shall have a smooth uniform finish.

2.7 Workmanship. Pointer shall be securely assembled so that parts do not become loose or displaced and shall be free from defects or imperfections which may adversely affect appearance or serviceability.

3. Regulatory Requirements:

The offeror / contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4 Quality Assurance Provisions:

4.1 Contractor Certification. The contractor shall certify and maintain substantial evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

4.2 Examination and Testing

4.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibits control over their processes (e.g. Statistical Process Controls (SPC) techniques) as defined in the American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3/ American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduces excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in the applicable technical document or herein. For those product characteristics which are controlled by such a method, requirements for visual and dimensional sampling inspection may be considered to have been met.

4.2.2 End item inspection may be used by the offeror, or the Government representative, as a means to determine the effectiveness of the inprocess quality controls. Inprocess controls shall not be substituted for end item performance testing, unless it can be demonstrated that there exists a direct correlation between the process and product performance, such that end item performance testing is obviated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection / shall be required. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society of Quality Control (ASQC) ANSI/ASQC Z1.4 1993, Sampling Procedures and Tables for Inspection by Attributes.

4.2.4 For Visual and Dimensional inspections the level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 Percent Defective. The sample unit shall be one pointer. The supplier must provide objective evidence (test and inspection records) that the presented material meets the requirements of this Commercial Item Description.

5. Packaging:

5.1 Preservation, packing and marking shall be as specified in the contract or order.

6. Notes:

6.1 Reference Documents: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

6.1.2 Application for copies of (ANSI) Z1.1, Z1.2, Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

6.1.3 Federal Standards and Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at 490 L'Enfant Plaza, SW Washington DC 20407.

6.3 Ordering Information: Purchasers shall select the required options permitted herein, and include the following information in procurement documents:

A. Title, number, and date of this commercial item description
B. Purchasers shall specify the type and size required
C. Purchasers shall specify identification marking, if other than required
D. Purchasers shall specify arrangement for inspection and facilities if other than specified
E. Purchasers shall specify if bar code marking is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

6.4 National Stock Number Listing:

Pointer Wood

7520-00-271-8890
7520-00-271-8891

MILITARY INTERESTS:
None.
DoD has determined that no military activity has an official interest in this Commercial Item Description

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.