[Metric]
A-A-2991
May 22, 1996

COMMERCIAL ITEM DESCRIPTION
PRINTING SET, RUBBER TYPE

The General Services Administration has authorized the use of this commercial item description by all federal agencies and will be replaced by GG-P-655 which is canceled.

1. Scope: This Commercial Item Description covers a rubber type hand printing set.

2. **Salient Characteristics:**

2.1 Component Parts.

2.1.1 The rubber type printing set shall consist of a 5A & 6a letter font, 4 figure, commercial size 0 ink stamp pad, four figure font commercial size 0 ink stamp pad, a four line and a one line type holder block, a handle, and tweezer. The type shall be 12-point News Gothic face on a commercially acceptable body.

2.2 Materials.

2.2.1 Rubber. Rubber used shall be natural or synthetic or a combination of the two which is commercially accepted for this usage and shall be free from defects which may affect appearance or serviceability.

2.2.2 Stamp Pad. The stamp pad used shall be composed of materials in accordance with commercial item description A-A-1383A or a commercially acceptable type.

2.3 Design & Construction.

2.3.1 Type Holder Blocks. The type holder blocks shall be made of metal, wood, plastic or a commercially acceptable material with slots designed to receive the type. The top of the holder blocks shall have a centered hole to receive the handle. The holder blocks shall be 7.62 cm ± .317 cm (3 inches ± 1/8 inch long).

2.3.2 Handle. Each printing set shall be provided with a suitable handle designed to fit into the holder blocks or what is commercially acceptable. The handle shall have a flat face to indicate the front of the stamp, and handle size shall be in accordance with commercial practice.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Division, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4.2 Examination & Testing.

4.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC Techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

4.2.2 End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. While in process controls shall not be substituted for end item performance testing they may be used in evaluating visual and dimensional characteristics.

4.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. The sample unit for this item shall be one printing set. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

4.3.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual and dimensional testing shall be S-3 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

5. Packaging:

5.1 Preservation, packing, and marking shall be specified in the contract or order.

6. Notes:

6.1 Source of Documents. Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

6.1.2 Application for copies of (ANSI) Z1.1, Z1.2, Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control. PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

2.3.3 Type Compound for Letters, Numerals and Symbols. The type compound for producing impressions shall be molded from rubber as specified in paragraph 2.2.1. The type characters shall be raised in relief by a minimum of 0.794 mm (1/32 inch) from 1.588 mm (1/16 inch minimum) thickness sheet-rubber. The sheet-rubber type compound shall be glued on a rubber base which shall fit, by friction, into the metal slots of the holder block or of a design which is commercially acceptable. The type shall remain firmly in place and produce clear and distinct impressions.

2.3.4 Font Designation. The 5A & 6a font designation consists of the following:

Capital Letters:	A-5; B-4; C-5; D-4; E-5; F-4; G-5; H-5; I-5; J-3; K-2; L-6; M-4; N-5; O-5; P-4; Q-2; R-5, S-5; T-5; U-3; V-2; W-3; X-2; Y-2; Z-3.
Lower Case Letters:	a-6; b-5; c-6; d-5; e-6; f-6; g-5; h-5; I-6; j-4; k-3; l-6; m-5; n-6; o-6; p-4; q-3; r-6; s-6; t-6; u-5; v-3; w-4; x-4, y-4; z-3.

The 4 figure font consists of 4 of each numerical 1 through 9 and 0. In addition, each set has an assortment of marks and symbols.

2.3.5 Finish. The holders and handle shall be varnished, lacquered, or enameled. Metal components (if supplied) shall be plated or treated to a bright finish to resist corrosion.

2.3.6 Instructions. Each set shall be provided with an assembly instruction sheet.

2.4 Workmanship. Rubber type shall be sharply and cleanly cut. Handle and holder blocks shall be smoothly finished. The set shall be free from defects which may affect appearance or serviceability.

3. **Regulatory Requirements:** The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. **Quality Assurance Requirements:**

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the currentversion before use.

6.1.3 Federal Standards and Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at 490 L'Enfant Plaza, SW Washington DC 20407.

6.2 National Stock Number Listing (NSN's). The following is a list of Nsn's assigned which correspond to this CID. The list may not be indicative of all possible Nsn's associated with the CID.

7520-00-264-3718

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.