[Metric]
A-A-2996
August 15, 1996

COMMERCIAL ITEM DESCRIPTION
PAD, DESK, BLOTTER

The General Services Administration has authorized the use of this commercial item description by all federal agencies and replaces Federal Specification UU-P-16 which is canceled.

1. **Scope:** This Commercial Item Description covers linoleum back, desk pads designed to hold blotters.

2. **Salient Characteristics:**

2.1 **Materials.** The materials used shall conform to the requirements as specified herein. When materials are not specified, they shall be of the quality normally used for in commercial practice.

2.1.1 **Linoleum.** Linoleum shall conform to the requirements as specified in this commercial item description. The wearing surface of the linoleum shall consist of oxidized linseed oil, fossil or other resins / rosin equivalent completely oxidized oleoresins binder thoroughly mixed with ground cork or wood flour, mineral fillers and pigments. The exposed edges of the linoleum shall present a smooth and neat appearance, and corners shall be rounded. The linoleum shall have an average residual indentation of not more than 10 percent. The indenting load shall be 50 pounds applied for 15 minutes. After 60 minutes, the residual indentation shall be measured. The diameter of the indenting cylinder shall be 0.250 inch.

2.1.2 **Material Backing.**

2.1.2.1 **Organic Felt.** Organic fiber felt backing shall be treated with a resin or asphalt saturant. The backing material shall be securely bonded to the wearing surface. When an attempt is made to pull the wearing surface from the backing by hand the backing shall split or break before the bonding fails. The exposed side of the backing shall not mar the appearance of the wearing surface or cause sticking at points of contact.

2.1.3 **Surface Coating.** Unless otherwise specified, the wearing surface of the linoleum shall be factory-finished with a clear transparent coating.

2.1.4 **Thickness.** Except for embossed areas, the overall thickness shall be 2.032 mm ± .101 mm (0.080 inch ± .004 inch) with a wearing surface of 1.02 mm ± .005 mm (0.040 inch ± .002 inch).

2.1.5 **Artificial Leather.** The artificial leather shall conform to the requirements of federal specification CCC-A-700, class 1, 2 or 7. The color shall be that as specified in the contract/order

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

2.2 **Design and Construction:**

2.2.1 **Pads.** The pads shall consist of a linoleum back to which two panels extend the full width of the pad, one on each side, and each pad shall have a felt backing. The dimensions shall be as follows: 61.6 cm ± 1 cm (24.25 inches ± .392 inches) x 97.5 cm ± 1 cm (38.385 ± .392 inches).

2.2.3 **Panels.** Panels shall be artificial leather as specified in paragraph 2.1.5. The panels shall be 10.8 cm ± .635 cm (4.25 inches ± 0.25 inches) wide, and the panel length shall be the entire width of the pad. Panels shall be neatly and securely glued to the underside of the linoleum back for at least 1.27 cm (0.5 inch) along the outside edges and the entire width of the pad at the panel ends. Each panel shall be suitably reinforced and padded to give stiffness and a slight cushion effect to the upper surface of the panel. The pad shall be constructed so that a desk blotter can be inserted between the panels and linoleum back. Panels shall be securely glued so that they will not separate from the linoleum during normal usage.

2.3 **Workmanship.** The pad edges shall be straight and smooth. Except for rounded corners, edges of adjacent sides and ends shall be at 90 degree angles. Pads shall lay flat when placed on a flat surface. The felt used on the bottom of the pad shall protect the surfaces on which desk pads are normally used. Pads shall be free from defects which may affect appearance or which might impair serviceability.

3. **Regulatory Requirements:** The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. **Quality Assurance Requirements:**

4.1 **Product Conformance.** The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.2 **Examination & Testing:**

4.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

4.2.2 End item inspection/testing may be used by the offeror or the government representative, as a means to determine the effectiveness of the in process quality controls. While in process controls shall not be substituted for end item performance, the use of SPC techniques will be allowed for visual and dimensional sampling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. The sample unit shall be one pad. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

4.2.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual and dimensional examination shall be S-3 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

5. **Packaging:** Preservation, packing, and marking shall be specified in the contract or order.

6. **Notes:**

6.1 **Source of Documents.** Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

6.1.2 Application for copies of (ANSI) Z1.1, Z1.2, Z1.3 and (ASQC) B-1, B-2 and B-3 may be obtained from the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

6.1.3 Federal Standards and Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at 490 L'Enfant Plaza, SW, Washington DC 20407.

6.2 **National Stock Number Listing (NSN):** The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

7520-00-285-1801
7520-00-139-4635

MILITARY INTERESTS

NONE. DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.