[INCH-POUND]
A-A-3022
October 10, 1996

COMMERCIAL ITEM DESCRIPTION

EXTRACTOR, TAP

The General Services Administration has authorized the use of this Commercial Item Description for procurement of type II extractors specified in GGG-E-936C for all federal agencies.

1. SCOPE.

1.1 Scope. This Commercial Item Description covers hand-operated extractors for use in removing broken taps.

2. CLASSIFICATION.

2.1 Classification. Not applicable.

3. SALIENT CHARACTERISTICS.

3.1 Design. The tap extractor shall be of steel construction and consist of a body, sleeve, collar, and fingers. The bodies and fingers shall be heat treated and conform to a hardness of 50 to 58 on the Rockwell C scale for extractor sizes 9/16 through 1-1/2 and a hardness of 47 to 55 on the Rockwell C scale for extractor sizes 4 through 1/2. All parts having the same manufacturer's part number shall be so constructed to definite standards, tolerances, and clearances in order that such parts may be completely interchangeable, replaced, or adjusted without requiring modification. The extractors shall be similar to Figure 1 and conform to the dimensions specified in Table I. When required to be tested for hardness, sample extractors shall be tested in accordance with ASTM E 18.




Figure 1. Tap extractor.

3.1.1 Body. The body shall be grooved in such a manner as to provide a sliding fit for the fingers. The body diameter shall be of such size that it can be inserted in the applicable tapped hole with a minimum amount of looseness.

3.1.2 Fingers. The fingers shall be of high grade material and heat treated so as to satisfactorily back out taps which are broken during normal production operations. The fingers shall be shaped to fit both the grooves in the body and the flutes of the applicable tap.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Kansas City, MO 64131.

Distribution Statement A. Approved for public release; distribution is unlimited. FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

TABLE I. Tap extractor

For standard machine and handtaps			
Extractor 1/ size number	Nominal tap size (Inches)	Thread series	Number of flutes
4	0.112	---	3
5	0.125	---	3
6	0.138	---	3
8	0.164	---	4
10	0.190	---	4
12	0.216	---	4
1/4	0.250	---	4
5/16	0.3125	---	4
3/8	0.375	---	4
7/16	0.4375	---	4
1/2	0.500	---	4
9/16	0.5625	---	4
5/8	0.625	---	4
11/16	0.6875	---	4
3/4	0.750	---	4
7/8	0.875	---	4
1	1.000	---	4
1-1/8	1.125	NC	4
1-1/8	1.125	NF	6
1-1/4	1.250	NC	4
1-1/4	1.250	NF	6
1-3/8	1.375	NC	4
1-3/8	1.375	NF	6
1-1/2	1.500	NC	4
1-1/2	1.500	NF	6

For standard pipe taps only		
Specify "pipe tap extractor" size (Inch)	Specify number of flutes required	
1/8	4	5
1/4	4	5
3/8	4	5
1/2	4	5
3/4	---	5
1	---	5

1/ Extractors not listed in Table I may be ordered by specifying the tap size, threads per inch, number of flutes, and kind of tap the extractor is for (for example: 1/2-13, three-fluted, gun tap) (see 7.2).

3.1.3 Sleeve. The sleeve shall provide support for the fingers when removing broken taps and shall be a sliding fit over the entire length of the assembled extractor.

3.1.4 Collar. The collar shall be a sliding fit over the entire length of the extractor and designed for the fingers to be easily detached or attached thereto.

3.2 Extractor sets. When sets of extractors are specified (see 7.2), the parts of the sets shall conform to the requirements of the respective items covered by this commercial item description. The sets shall be provided in wraps or rolls of durable plastic or fabric with individual pockets for each extractor and its components, arranged to fold in a manner to enclose the extractor and its components, and shall be secured with durable snaps or ties.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

When boxes for sets are specified, the boxes shall be either of metal, plastic, or wood with partitions for holding the components and a cover, and have a positive- or friction-type catch. When wooden blocks are specified, the blocks shall have round drilled holes, to accommodate each extractor in the set. The interior and exterior surfaces of metal, wooden boxes, or wooden blocks shall have a suitable protective coating. When plastic wraps (pouches) are furnished, the plastic shall be of flexible vinyl film having a 1.58 maximum volatility rating, 1.30 maximum specific gravity, 13 gage (0.013 inch) minimum thickness, and shall have the capacity to pass a 0° to -5° Fahrenheit Maslan cold crack test.

3.3 Identification marking. The tool shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.4 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

ASTM E18: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) When extractors for machine and handtaps are ordered, specify the number of flutes required on size 1-1/8 inch and above (see Table I).
(d) When type II extractor, for pipe taps are ordered, specify "pipe tap extractor" and number of flutes required as applicable (see Table I).
(e) If bid samples are required, the number of samples required, and the subjective inspection requirements.
(f) If first article samples are required and the number of samples required.
(g) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample tool shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(h) What preservation, packing, packaging, and marking of packages are required.
(i) Whether sets are to be furnished and type of wrap or container; i.e., plastic or fabric, wraps or rolls, or metal, plastic, wooden boxes, or wooden blocks.

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the extractor specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	EXTRACTOR SIZE NUMBER
5120-00-293-3544	4
5120-00-293-3543	5
5120-00-293-3542	6

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the current version before use.

NSN	EXTRACTOR SIZE NUMBER
5120-00-180-0786	8
5120-00-203-9434	10
5120-00-293-3541	12
5120-00-288-9180	1/4 inch
5120-00-288-9181	5/16 inch
5120-00-288-9182	3/8 inch
5120-00-288-9183	7/16 inch
5120-00-288-9184	1/2 inch
5120-00-240-5225	9/16 inch
5120-00-288-9185	5/8 inch
5120-00-222-1442	3/4 inch
5120-00-222-1443	7/8 inch
5120-00-222-1444	1 inch

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.