A-A-58013
24 February 1993

COMMERCIAL ITEM DESCRIPTION

COMPACT LOADER/BACKHOE

This item description covers a self-propelled diesel-engine-driven pneumatic tired compact loader/backhoe.

Salient characteristics:

A. Design. The loader/backhoe shall be pneumatic tire mounted and water cooled, diesel engine driven.

B. Engine. The engine shall be heavy duty water cooled, diesel with a minimum of three cylinders. The engine shall be equipped with an efficient fuel injection mechanism, fuel filter system, air cleaner of the oil bath or dry type filter, and a lubricating oil filter. As a minimum, the engine shall produce 20 hp at 3000 rpm.

C. Transmission. The transmission shall be a heavy duty hydrostatic transmission rated at least at 35 hp.

D. Steering. Power steering with full size steering wheel.

E. Axles. The front axle shall have a minimum capacity of 4000 pounds. The rear axle shall have a minimum rating of 3300 ponnds with positraction and 5300 foot pounds (minimum) output torque.

F. Frame. One piece.

G. Loader/backhoe dimensions. Width - not to exceed 50 inches
Height - not to exceed 80 inches with ROPS
Wheel base - not less than 58 inches

H. Outriggers. Street pads shall be provided when rerquired, see NOTES.

I. Backhoe. The backhoe shall have a minimum reach of 135 inches and a minimum digging depth of 100 inches.

Beneifical comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: WR-ALC/LZMB Robins AFB, GA 31098-5609.

AMSC N/A FSC 3805

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

J. Backhoe bucket. The backhoe bucket shall be 16 inches wide and have a minimum capacity of 1.8 cubic feet, unless otherwise specified, see NOTES.

K. Front bucket. The front bucket shall have a minimum capacity of 6 cubic feet and a minimum roll back of 35 degrees. The cutting edge shall be of high carbon steel.

L. Hydraulic system for loader/backhoe. This system shall produce at least 2300 psi, have a 7 gallon tank and a flow of 7 gpm at 3600 rpm.

M. Rear tires. As specified for each location, see NOTES.

N. Front tires. 20.5 inches X 8 inches X 10 inches; 4 ply.

O. Controls. Standard controls unless otherwise specified, See NOTES.

P. Brakes. Hydrodynamic when hydrastatic drive is in neutral, otherwise independent disc brake with guard.

Q. Battery. Heavy duty 12 volt maintenance free.

R. Seat. High back, slide track, two position swivel lock with retractable seat belt.

S. Lights. The head lights shall be halogen, flood type, sealed beam and replaceable. The front and rear working lights shall be flood type, sealed beam and replaceable. An amber high output strobe light shall also be furnished.

T. Instrumentation. The following instruments, convenient to and in full view of the operator's normal operating position shall be furnished:

1. Voltmeter (or Ammeter)
2. Tachometer
3. Hourmeter
4. Fuel gauge
5. Oil pressure indicator
6. High coolant temperature indicator

U. Safety. The loader/backhoe shall conform to Federal Laws and Regulations governing noise, air pollution and other health and safety requirements which are in effect for this type of equipment at the time of contract award. Also the following safety features shall be provided:

(1) Neutral safety start switch.

(2) Backup alarm.

(3) ROPS conforming to SAE J1040.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

(4) Slow moving emblem on rear of loader/ backhoe.

V. Trailer. A flat bed trailer shall be provided with each loader/backhoe, unless otherwise specified, and shall be equipped with the necessary features to safely transport the machine from one site to another. The trailer shall have as a minimum the following features:

(1) F-78 X 14.5 tires and wheels.

(2) 7000 lbs GVW

(3) Safety chains.

(4) Two inch hard pine deck, 63 inches x 168 inches, minimum.

(5) 10,000 lb hydraulic surge coupler.

(6) Heavy duty ramps with ramp straps.

(7) Adjustable lunette eye coupler.

(8) Slipper springs.

(9) Heavy duty 10,000 lb top wind jack.

(10) DOT lighting.

(11) Primed and painted channel iron frame.

(12) D ring tie downs.

(13) Diamond plate fenders.

W. The vehicle furnished must be the latest model as of the date of award (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-39(f)(2)(ii)(A)) for at least three years immediately preceding the issuance date of the solicitation. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements.

NOTE TO OFFERORS: Offerors shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years immediately preceding the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

issuance date of the solicitation.

(2) Total sales of the item to the general public during the three years immediately preceding the issuance date of the solicitation.

(3) Length of time the item has been sold in the commercial market place.

(4) Points of contact and phone numbers of customers to which the item has been sold in the commercial market place.

(5) Other pertinent information necessary to determine that the item is an established commercial item.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, and as implemented by Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities, labeling, and marking shall be as specified in the contract and/or order. Identification marking and data plates shall be in accordance with MIL-STD-1223.

NOTES

a. Unless otherwise specified the loader/backhoes, and the transporting trailer when required, shall be painted dark green, 24052 of FED-STD-595.

b. Commercial manuals to include parts manual, and operation and maintenance manuals shall be supplied with each loader/backhoe. (Two copies of each shall be supplied).

c. Unless otherwise specified a trailer shall be provided with each loader/backhoe as required in this Commercial Item Description.

d. Backhoe bucket size, if different.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

e. Type rear tires required.

f. Wobblestick/joystick type controls, when required.

g. Hydraulic P.T.O., if required.

h. Street pads, if required.

Custodian:
AIR FORCE-99

Preparing Activity:
AIR FORCE-84

Project number 3805-0151

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.