NOT MEASUREMENT
SENSITIVE
A-A-59246
June 16, 1998
SUPERSEDING
OO-R-2783
March 9, 1992

COMMERCIAL ITEM DESCRIPTION

ROLLER, TOWED, OPEN-FACE TYPE, TWO DRUM

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE. This commercial item description (CID) covers a two drum, open-face (grid) type, towed roller.

2. SALIENT CHARACTERISTICS.

2.1 Description. The roller covered by this CID consists essentially of two open-face (grid) type drums mounted on a structural steel frame equipped with a tow bar and hitch. The roller is intended for use in:

a. Crushing, breaking, and pulverizing large pieces of salvaged asphaltic concrete, loose rocks, and stones.
b. Mixing the crushed rocks, stones, and asphaltic concrete with soil.
c. Compacting the soil-rock, stone, asphaltic concrete mixture.

2.2 Standard commercial product. The roller shall, as a minimum, be in accordance with the requirements of this CID and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this CID but which are a part of the manufacturer's standard commercial product, shall be included in the roller being furnished. A standard commercial product is a product which has been sold or is currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Officer In Charge (Code 15E2), Seabee Logistics Center, 4111 San Pedro St., Port Hueneme, CA 93043-4410, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3895

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

2.3 Maintainability. The roller shall be designed so that accessories and components are readily accessible for repair or replacement with minimum removal or disturbance of adjacent parts or components, using general purpose tools. Operating parts, accessories, and drain outlets shall be readily accessible for regular maintenance service. Drainage of all liquids shall be gravity onto the ground.

2.4 Interchangeability. All rollers of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, accessories, and spare parts.

2.5 Performance characteristics. The fully ballasted roller shall withstand the strains imposed without permanent deformation or damage while being towed at a speed of not less than 9 miles per hour (14.5 kilometre per hour) over rough and rocky ground. The roller shall be capable of breaking loose rocks and stones (see 6.3.1 and 6.3.2), having a minimum compressive strength of not less than 24,000 pound-force per square inch (psi) (165 474 kilopascal (kPa)) and crush, pulverize, mix, and compact large pieces of asphaltic concrete.

2.6 Frame. Frame shall be constructed of either structural steel sections or steel plate with members joined using one of the arc welding processes. To withstand the stresses imposed, and to prevent permanent deformation or damage to the roller, the frame shall be braced and reinforced wherever necessary. A clevis shall be affixed to the back of the frame to permit towing rollers in tandem. Clevis shall contain a hole to accommodate a 2-inch (in) (51 millimetre (mm)) pin.

2.7 Axles and bearings. Each drum shall be equipped with an independent axle extending entirely through the drum and mounted on heavy-duty bearings. Tapered roller or combination radial thrust-type ball bearings with dust-tight seals shall be used.

2.8 Drums. Drums shall be constructed with face strips forming square, rectangular, or hexagonal openings on the drums' surfaces.

2.9 Cleaners. Roller shall be equipped with adjustable drum cleaners. The cleaners shall be capable of cleaning the drums when roller travels in both the forward and reverse directions.

2.10 Drawbar. The drawbar shall be of such design and construction as to permit either pulling or pushing of the roller. The drawbar shall be equipped with an adjustable, universal type clevis which shall allow coupling to an SAE J749, size F tractor drawbar.

2.11 Jack leg. A jack leg shall be provided for supporting the roller frame in horizontal plane when detached from the tractor. Jack leg shall be retractable, and shall be equipped with a positive locking device to prevent accidental detachment while roller is being towed. No part of the jack leg or its components, while in the stowed position, shall interfere with normal operation of the roller.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

2.12 Ballast boxes. Roller shall be equipped with ballast boxes having sufficient volume for 14,000 pounds (lb) (6 350 kilogram (kg)) of weight when filled with wet sand. Volume calculations shall be determined using wet sand weighing 115 lbs per cubic foot (1 842 kilogram per cubic metre). Boxes shall be secured to the frame. Each box shall be furnished with lifting attachments to allow lifting of the loaded box (see 2.17).

2.13 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high-pressure lubricating equipment, 1,000 psi (6 895 kPa) or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

2.14 Identification plate. An identification plate will be furnished by the contracting officer for each roller. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each roller in a conspicuous place with nonferrous screws, rivets, or bolts not less than 0.125-inch (3.175 mm) in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

2.15 Instruction plates. The roller shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment. Plates shall be securely affixed to the equipment with nonferrous screws or bolts of not less than 0.125-inch (3.175 mm) diameter.

2.16 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to ensure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to ensure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current process and the total dry film thickness shall be not less than 2.5 mil (0.06 mm) over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

2.17 Lifting and tiedown attachments. When specified (see 6.2), the roller shall be equipped with lifting and tiedown attachments. A nonferrous transportation plate shall be provided and mechanically attached to the roller. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the sweeper on the carrier when shipped.

2.18 Workmanship.

2.18.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to ensure uniformity of size and shape.

2.18.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

2.18.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and uniform size the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

2.18.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

2.18.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the casting’s ability to perform its intended function.

3. REGULATORY REQUIREMENTS.

3.1 Dimensions and weight. The roller, unballasted and ready for operation, shall weigh not less than 12,400 lbs (5 625 kg). Fully ballasted, the roller shall weigh not less than 26,400 lbs (11 975 kg). The single drum roller width shall be not less than 32 in (813 mm) with a diameter of not less than 67 in (1 702 mm). The double drum roller width shall be not less than 70 in (1 778 mm) with a diameter of not less than 67 in (1 702 mm). The overall maximum width of either the single or double roller shall be not greater than 96 in (2 438 mm) with a length of not greater than 235 in (5 969 mm).

3.2 Materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this commercial item description are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

intended use. The term “recovered materials” means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description.

3.3 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest version of ASTM SI-10 (IEEE/ASTM SI-10), and all other requirements of this commercial item description including form, fit, and function are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer’s own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING. The preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 The Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

6.1.2 ASTM Standard is available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

6.1.3 IEEE Standard is available from the Institute of Electrical and Electronics Engineers, IEEE Service Center, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331.

6.1.4 SAE Standards and Recommended Practices are available from the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, date of this CID.
b. Means for lubrication, if other than manufacturer's standard practice (see 2.13).
c. Color of finish coat (see 2.16).
d. When lifting and tiedown attachments are required (see 2.17).

6.3 Definitions.

6.3.1 Loose rocks. Detached rocks greater than 1 cubic foot (0.03 cubic metre (m^3)) and less than 1 cubic yard (0.76 m^3) (see 2.5).

6.3.2 Stones. Rock fragments greater than 10 inches (254 mm) in diameter, if rounded, and greater than 15 inches (381 mm) along the greatest axis if flat (see 2.5).

6.4 Supersession data. This commercial item description replaces Federal Specification OO-R-2783, dated March 9, 1992.

6.5 Metric units. The values stated in either inch-pound units or SI units are to be regarded separately as standard. Within the text, the SI units are shown in brackets. The values stated in each system are not exact equivalents; therefore, each system should be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

6.6 Subject term (key word) listing.

Fully ballasted
Unballasted

MILITARY INTERESTS:

Custodians:
Navy - YD1
Air Force - 99

Review Activities:
Navy - MC
Air Force - 84

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity:
Navy - YD1

(Project 3895-0062)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** A-A-59246	**2. DOCUMENT DATE (YYMMDD)** 980616

3. DOCUMENT TITLE

ROLLER, TOWED, OPEN-FACE TYPE, TWO DRUM

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME BERNADETTE ROSE	b. TELEPHONE *Include Area Code)* (1) Commercial 805-982-5464 (2) AUTOVON 551-5464
c. ADDRESS *(Include Zip Code)* OFFICER IN CHARGE, SEABEE LOGISTICS CENTER CODE 15E2, 4111 SAN PEDRO ST. PORT HUENEME, CA 93043-4410	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil/Document Id: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.