MIL-B-23287(Wep)
Amendment 4
13 August 1965
Superseding
Amendment 3
21 July 1964

MILITARY SPECIFICATION

BATTERY SECTION ASSEMBLY

This amendment forms a part of Military Specification MIL-B-23287(Wep) dated 21 May 1962 and has been approved by the Bureau of Naval Weapons, Department of the Navy

Page 1: Change specification title to "BATTERY SECTION ASSEMBLY".

Page 1, paragraph 1.1. Delete and substitute:
"1.1 Scope. This specification establishes the requirements for the procurement and test of Torpedo Battery Sections, BUWEPS LD 419735 and LD 542958. The battery sections are for the water-activated, primary battery applicable to Torpedo Mk 45 Mods 0 and 1. When loaded with water-activated Battery Mk 67 Mod 1, the section provides necessary control and propulsion power for the torpedo."

Page 2, under "DRAWINGS". Insert the following:

"BUWEPS LD 419737	Battery Unit Water Activated Mk 67 Mod 1
BUWEPS LD 537879	Preserved (Packaging)Condition, Battery Section Assembly Water Activated
BUWEPS LD 537881	Shipping (Packing) Condition, Battery Section Assembly, Water Activated
BUWEPS LD 542958	Battery Section Assembly, Water Activated
BUWEPS Dwg 2005609	Battery Section Assembly, Water Activated, Electrical Schematic Diagram"

Page 2, under "PUBLICATIONS". Delete "OP 400" and associated title.

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:19Z
Check the source to verify that this is the current version before use.

Page 2, paragraph 2.2. After "Handbook H28" delete "and all supplements thereto".

Page 2, paragraph 3.1.1: Delete "battery compartment" and substitute "battery section".

Page 3, paragraphs 3.1.2, 3.1.3, and 3.1.4. Delete "battery compartment" and substitute "battery section"; after "LD 419735" add "and LD 542958".

Page 3, paragraph 3.1.5: After "LD 419735" add "and LD 542958".

Page 3, paragraph 3.1.8. Delete and substitute:
"3.1.8 Threads. Unless otherwise specified, all threads shall be in accordance with National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings."

Page 3, paragraph 3.1.9: Delete.

Page 4, paragraph 3.3: Delete "battery compartment" and substitute "battery section".

Page 4, paragraph 3.3.3, line 3: Delete "shall be less than 2.1 ohms" and substitute "shall be between 1.25 and 2.1 ohms".

Page 5, paragraphs 3.4, 3.4.1, 3.4.2, 3.4.3, 3.4.4, and 3.4.5: Delete "battery compartment" and substitute "battery section".

Page 6: In two notes and in paragraph 3.4.6 delete "battery compartment" and substitute "battery section".

Page 6, paragraph 4.1. Delete and substitute:
"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure that supplies and services conform to prescribed requirements."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:19Z
Check the source to verify that this is the current version before use.

Page 6, paragraph 4.1.2: Delete "battery compartment" and substitute "battery section".

Page 7, paragraph 4.1.4: Delete "battery compartment" and substitute "battery section".

Page 7, paragraph 4.2: Delete.

Page 7, paragraph 4.3: Delete "battery compartment" and substitute "battery section".

Page 7, paragraph 4.3.1. Delete and substitute:
"4.3.1 Acceptance tests. Acceptance tests are to be accomplished on each battery section being submitted for acceptance under contract. These tests, detailed in 4.5, shall be performed by the manufacturer."

Page 8, paragraph 4.3.2: Delete "battery compartment" and substitute "battery section".

Page 8, paragraph 4.3.3, line 4: Delete "Mod 0" and substitute "Mods 0 and 1"; in lines 3 and 4 delete "battery compartment" and substitute "battery section".

Page 8, paragraph 4.4.3: Delete paragraph title "Ohm-meter" and substitute "Ohmmeter or equivalent"; in line 3 delete "shall be less than 0.1 amp" and substitute "shall be between 0.025 and 0.075 ampere".

Page 9, paragraph 4.5.1: Delete "or Government inspector"; delete "battery compartment" and substitute "battery section".

Page 9, paragraph 4.5.2: Delete "battery compartment" and substitute "battery section".

Page 10, paragraphs 4.5.4.8.1 and 4.5.4.9.1: Delete "battery compartment" and substitute "battery section".

Page 10, paragraph 4.5.4.8.3: Delete and substitute:
"4.5.4.8.3 Close switch S-1 and listen for the pump to start. Open switch S-1 immediately when the sound of the pump running is heard. (Note: The pump shall start within 20 seconds maximum.) The pump shall start and continue to

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:19Z
Check the source to verify that this is the current version before use.

run during the period that the switch is closed, and shall stop when the switch is opened, to meet the requirements of 3.3.8. Do not allow the pump to run longer than 5 seconds."

Page 13, paragraphs 4.6.1, 4.6.2, 4.6.3, 4.6.4, and 4.6.4.1: Delete "battery compartment" and substitute "battery section".

Page 14, paragraphs 4.6.5, 4.6.6, 4.7, and 5.1.1.1: Delete "battery compartment" and substitute "battery section".

Page 14, paragraphs 5.1.1.1 and 5.2.2: After "LD 542932" add "and LD 537881".

Page 15, paragraph 6.1: Delete "battery compartment" and substitute "battery section"; delete "Mod O" and substitute "Mods O and 1".

Page 15, paragraph 6.3: Delete "battery compartment" and substitute "battery section".

Page 15: Delete "NOTICE" paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:19Z
Check the source to verify that this is the current version before use.