MILITARY SPECIFICATION

BOOSTER, GUIDED MISSILE, MARK 12
MOD 1 (LOADED ASSEMBLY)

This amendment forms a part of Military Specification MIL-B-23297B(OS) dated 5 March 1980, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, Below "MIL-STD-414" add: "DOD-STD-2101 Classification of Characteristics".

Beneficial comments block: delete "(501)" and substitute "(524)".

PAGE 2

* Delete "Sea" and substitute "Ordnance", two places.

* Below "DRAWINGS": delete "LD 487648" and "LD 487651" and associated titles and substitute:

"DL 1738571 Booster Mark 12 Mod 1 (Loaded Assembly)

DL 1738576 Propellant Grain MK 73 MOD 0"

* Below "PUBLICATIONS" delete: "WR43 Preparation of Quality Assurance Provisions".

PAGE 3

* Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence."

PAGE 4

* 3.2: Line 5: Delete "LD 487648 and LD 487651" and substitute "DL 1738571 and DL 1738576".

* 3.4: Add "(M101)" after "Ballistic performance".

* 3.5: Add "(C1)" after "2-Nitrodiphenylamine content".

FSC 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:21Z
Check the source to verify that this is the current version before use.

* 3.6: Add "(C2)" after "Stability and physical properties (propellant)".

* 3.7: Add "(M102)" after "Environmental".

PAGE 5

* 4.3: Delete and substitute:

"4.3 Classification of characteristics. The characteristics specified herein are classified as critical, major or minor in accordance with DOD-STD-2101. Critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). All other characteristics are classified minor. The number following the classification symbol is the serial number of the characteristic to be verified. The following exception to DOD-STD-2101 applies to classification of drawing characteristics:

When the classification applies to only a portion of a note or dimensional characteristics, or there are several classifications applicable, the applicable portions of the note shall be enclosed in brackets in lieu of parentheses, followed by the classification code and serial number."

PAGE 6

* TABLE I, in "THERMAL GRADIENT (4.7.4)" column:

Delete "49° to -12° C" and substitute "-12°C".

Delete "-12° to 49°C" and substitute "49°C".

PAGE 8

* 4.6.1.1, first line: Delete "(M101)".

* 4.6.2, first line: Delete "(M102)".

PAGE 9

* 4.7.1, first line: Delete "(M103)".

PAGE 10

4.7.2: Delete and substitute:

"4.7.2 Vibration. The motor shall be subjected to environmental vibration in accordance with Type I of MIL-STD-167-1."

TABLE II: Delete entire table.

PAGE 11

* 4.7.4, lines 2 and 3: Delete "...to the initial temperature, specified in Table I" and substitute "to an initial temperature of 27°C".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:21Z
Check the source to verify that this is the current version before use.

PAGE 12

6.2.1: line f: Delete "LD" and substitute "DL".

PAGE 13

6.4.2: Delete entire paragraph.

DD FORM 1426

Change "(5011)" in address to "(524)".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing Activity:
NAVY - OS

Project Number:
1336-N437

☆U.S. GOVERNMENT PRINTING OFFICE: 1993-605-034/170

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:21Z
Check the source to verify that this is the current version before use.