
MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, GLASS DIELECTRIC, (RADIAL WIRE-LEAD TERMINALS), ESTABLISHED RELIABILITY, STYLES CYR51, CYR52, AND CYR53

The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-C-23269.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.



STYLE CYR 51, SEE TABLE I

INCHES	MM
.002	.05
005	.13
.010	.25
.020	.51
.050	1.27
.115	2.92
.200	5.08
.300	7.62
1.25	31.75

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. See marking requirement.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:
Dimensions and configuration - See figures 1, 2, and 3 and tables I, II, and III.
Case material - Epoxy.
Terminals - Type D of MIL-STD-1276.
Capacitance (Cap.) (nom) - See tables I, II, and III.
Cap. tolerance - See tables I, II, and III.
Rated voltage - 300 volts, dc.
Failure rate level - L, M, P, R, or S.
Rated temperature - -55° to +125°C.
Temperature coefficient - 140 ±25 parts/million/°C.
Capacitance drift - 0.1% or 0.1 pF, whichever is greater.

Seal: Test II.

Insulation resistance: 10,000 megohms min (qualification inspection only at +125°C). 100,000 megohms min (at +25°C).


Dissipation factor (DF): 0.2% max (1.0 thru 100 pF) or 0.1% max (110 pF and up).

Thermal shock and moisture resistance:
DF - 0.3% max (1.0 thru 100 pF) or 0.1% max (110 pF and up).

Q: 500 min (1.0 thru 100 pF) or 1,000 min (110 pF and up).

Life:
ΔCap. (240 hr and 2,000 hr) - 0.5% or 0.5 pF, max.
DF (240 hr and 2,000 hr) - 0.45% max (1.0 thru 100 pF) or 0.25% max (110 pF and up).

Marking:



Substitutability data: See table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and physical characteristics and dash numbers.

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/10- FR level in %/1,000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
1	300	±0.25 pF	2001	3001	4001	5001	6001
1.5			2002	3002	4002	5002	6002
2.2			2003	3003	4003	5003	6003
2.7			2004	3004	4004	5004	6004
3.0			2005	3005	4005	5005	6005
3.3			2006	3006	4006	5006	6006
3.6			2007	3007	4007	5007	6007
3.9			2008	3008	4008	5008	6008
4.3			2009	3009	4009	5009	6009
4.7			2010	3010	4010	5010	6010
5.1		±0.25 pF	2011	3011	4011	5011	6011
5.1		±5%	2012	3012	4012	5012	6012
5.6		±0.25 pF	2013	3013	4013	5013	6013
5.6		±5%	2014	3014	4014	5014	6014
6.2		±0.25 pF	2015	3015	4015	5015	6015
6.2		±5%	2016	3016	4016	5016	6016
6.8		±0.25 pF	2017	3017	4017	5017	6017
6.8		±5%	2018	3018	4018	5018	6018
7.5		±0.25 pF	2019	3019	4019	5019	6019
7.5		±5%	2020	3020	4020	5020	6020
8.2		±0.25 pF	2021	3021	4021	5021	6021
8.2		±5%	2022	3022	4022	5022	6022
9.1		±0.25 pF	2023	3023	4023	5023	6023
9.1		±5%	2024	3024	4024	5024	6024
10		±0.25 pF	2025	3025	4025	5025	6025
10		±5%	2026	3026	4026	5026	6026
11		±0.25 pF	2027	3027	4027	5027	6027
11		±5%	2028	3028	4028	5028	6028
12		±0.25 pF	2029	3029	4029	5029	6029
12		±5%	2030	3030	4030	5030	6030
13		±0.25 pF	2031	3031	4031	5031	6031
13		±2%	2032	3032	4032	5032	6032
13		±5%	2033	3033	4033	5033	6033
15		±0.25 pF	2034	3034	4034	5034	6034
15		±2%	2035	3035	4035	5035	6035
15		±5%	2036	3036	4036	5036	6036
16		±0.25 pF	2037	3037	4037	5037	6037
16		±2%	2038	3038	4038	5038	6038
16		±5%	2039	3039	4039	5039	6039
18		±0.25 pF	2040	3040	4040	5040	6040
18		±2%	2041	3041	4041	5041	6041
18		±5%	2042	3042	4042	5042	6042
20		±0.25 pF	2043	3043	4043	5043	6043
20		±2%	2044	3044	4044	5044	6044
20		±5%	2045	3045	4045	5045	6045
22		±0.25 pF	2046	3046	4046	5046	6046
22		±2%	2047	3047	4047	5047	6047
22		±5%	2048	3048	4048	5048	6048
24		±0.25 pF	2049	3049	4049	5049	6049
24		±2%	2050	3050	4050	5050	6050
24	300	±5%	2051	3051	4051	5051	6051

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and physical characteristics and dash numbers. - Continued


Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/10- FR level in %/1, 000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
27	300	±1%	2052	3052	4052	5052	6052
27	↑	±2%	2053	3053	4053	5053	6053
27		±5%	2054	3054	4054	5054	6054
30		±1%	2055	3055	4055	5055	6055
30		±2%	2056	3056	4056	5056	6056
30		±5%	2057	3057	4057	5057	6057
33		±1%	2058	3058	4058	5058	6058
33		±2%	2059	3059	4059	5059	6059
33		±5%	2060	3060	4060	5060	6060
36		±1%	2061	3061	4061	5061	6061
36		±2%	2062	3062	4062	5062	6062
36		±5%	2063	3063	4063	5063	6063
39		±1%	2064	3064	4064	5064	6064
39		±2%	2065	3065	4065	5065	6065
39		±5%	2066	3066	4066	5066	6066
43		±1%	2067	3067	4067	5067	6067
43		±2%	2068	3068	4068	5068	6068
43		±5%	2069	3069	4069	5069	6069
47		±1%	2070	3070	4070	5070	6070
47		±2%	2071	3071	4071	5071	6071
47		±5%	2072	3072	4072	5072	6072
51		±1%	2073	3073	4073	5073	6073
51		±2%	2074	3074	4074	5074	6074
51		±5%	2075	3075	4075	5075	6075
56		±1%	2076	3076	4076	5076	6076
56		±2%	2077	3077	4077	5077	6077
56		±5%	2078	3078	4078	5078	6078
62		±1%	2079	3079	4079	5079	6079
62		±2%	2080	3080	4080	5080	6080
62		±5%	2081	3081	4081	5081	6081
68		±1%	2082	3082	4082	5082	6082
68		±2%	2083	3083	4083	5083	6083
68		±5%	2084	3084	4084	5084	6084
75		±1%	2085	3085	4085	5085	5085
75		±2%	2086	3086	4086	5086	6086
75		±5%	2087	3087	4087	5087	6087
82		±1%	2088	3088	4088	5088	6088
82		±2%	2089	3089	4089	5089	6089
82		±5%	2090	3090	4090	5090	6090
91		±1%	2091	3091	4091	5091	6091
91		±2%	2092	3092	4092	5092	6092
91		±5%	2093	3093	4093	5093	6093
100		±1%	2094	3094	4094	5094	6094
100		±2%	2095	3095	4095	5095	6095
100		±5%	2096	3096	4096	5096	6096
110		±1%	2097	3097	4097	5097	6097
110		±2%	2098	3098	4098	5098	6098
110		±5%	2099	3099	4099	5099	6099
120		±1%	2100	3100	4100	5100	6100
120		±2%	2101	3101	4101	5101	6101
120	300	±5%	2102	3102	4102	5102	6102

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and physical characteristics and dash numbers. - Continued

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/10- FR level in %/1,000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
130	300	±1%	2103	3103	4103	5103	6103
130	↑	±2%	2104	3104	4104	5104	6104
130		±5%	2105	3105	4105	5105	6105
150		±1%	2106	3106	4106	5106	6106
150		±2%	2107	3107	4107	5107	6107
150		±5%	2108	3108	4108	5108	6108
160		±1%	2109	3109	4109	5109	6109
160		±2%	2110	3110	4110	5110	6110
160		±5%	2111	3111	4111	5111	6111
180		±1%	2112	3112	4112	5112	6112
180		±2%	2113	3113	4113	5113	6113
180		±5%	2114	3114	4114	5114	6114
200		±1%	2115	3115	4115	5115	6115
200		±2%	2116	3116	4116	5116	6116
200		±5%	2117	3117	4117	5117	6117
220		±1%	2118	3118	4118	5118	6118
220		±2%	2119	3119	4119	5119	6119
220		±5%	2120	3120	4120	5120	6120
240		±1%	2121	3121	4121	5121	6121
240		±2%	2122	3122	4122	5122	6122
240		±5%	2123	3123	4123	5123	6123
270		±1%	2124	3124	4124	5124	6124
270		±2%	2125	3125	4125	5125	6125
270		±5%	2126	3126	4126	5126	6126
300		±1%	2127	3127	4127	5127	6127
300		±2%	2128	3128	4128	5128	6128
300		±5%	2129	3129	4129	5129	6129
330		±1%	2130	3130	4130	5130	6130
330		±2%	2131	3131	4131	5131	6131
330		±5%	2132	3132	4132	5132	6132
360		±1%	2133	3133	4133	5133	6133
360		±2%	2134	3134	4134	5134	6134
360		±5%	2135	3135	4135	5135	6135
390		±1%	2136	3136	4136	5136	6136
390		±2%	2137	3137	4137	5137	6137
390		±5%	2138	3138	4138	5138	6138
430		±1%	2139	3139	4139	5139	6139
430		±2%	2140	3140	4140	5140	6140
430		±5%	2141	3141	4141	5141	6141
470		±1%	2142	3142	4142	5142	6142
470		±2%	2143	3143	4143	5143	6143
470		±5%	2144	3144	4144	5144	6144
510		±1%	2145	3145	4145	5145	6145
510		±2%	2146	3146	4146	5146	6146
510		±5%	2147	3147	4147	5147	6147
560		±1%	2148	3148	4148	5148	6148
560		±2%	2149	3149	4149	5149	6149
560	300	±5%	2150	3150	4150	5150	6150

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.



STYLE CYR52, SEE TABLE II

INCHES	MM
.002	.05
.005	.13
.010	.25
.020	.51
.050	1.27
.115	2.92
.200	5.08
.300	7.62
1.25	31.75


NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. See marking requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical and physical characteristics and dash numbers.

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/10- FR level in %/1, 000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
620	300	±1%	2201	3201	4201	5201	6201
620	↑	±2%	2202	3202	4202	5202	6202
620		±5%	2203	3203	4203	5203	6203
680		±1%	2204	3204	4204	5204	6204
680		±2%	2205	3205	4205	5205	6205
680		±5%	2206	3206	4206	5206	6206
750		±1%	2207	3207	4207	5207	6207
750		±2%	2208	3208	4208	5208	6208
750		±5%	2209	3209	4209	5209	6209
820		±1%	2210	3210	4210	5210	6210
820		±2%	2211	3211	4211	5211	6211
820		±5%	2212	3212	4212	5212	6212
910		±1%	2213	3213	4213	5213	6213
910		±2%	2214	3214	4214	5214	6214
910		±5%	2215	3215	4215	5215	6215
1, 000		±1%	2216	3216	4216	5216	6216
1, 000	↓	±2%	2217	3217	4217	5217	6217
1, 000	300	±5%	2218	3218	4218	5218	6218

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.



STYLE CYR53, SEE TABLE III

INCHES	MM
.002	.05
.005	.13
.010	.25
.020	.51
.050	1.27
.115	2.92
.300	7.62
.400	10.16
.500	12.70
1.25	31.75

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. See marking requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE III. Electrical and physical characteristics and dash numbers.

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/10- FR level in %/1, 000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
1, 100	300	±1%	2301	3301	4301	5301	6301
1, 100	▲	±2%	2302	3302	4302	5302	6302
1, 100	▲	±5%	2303	3303	4303	5303	6303
1, 200	▲	±1%	2304	3304	4304	5304	6304
1, 200	▲	±2%	2305	3305	4305	5305	6305
1, 200	▲	±5%	2306	3306	4306	5306	6306
1, 300	▲	±1%	2307	3307	4307	5307	6307
1, 300	▲	±2%	2308	3308	4308	5308	6308
1, 300	▲	±5%	2309	3309	4309	5309	6309
1, 500	▲	±1%	2310	3310	4310	5310	6310
1, 500	▲	±2%	2311	3311	4311	5311	6311
1, 500	▲	±5%	2312	3312	4312	5312	6312
1, 600	▲	±1%	2313	3313	4313	5313	6313
1, 600	▲	±2%	2314	3314	4314	5314	6314
1, 600	▲	±5%	2315	3315	4315	5315	6315
1, 800	▲	±1%	2316	3316	4316	5316	6316
1, 800	▲	±2%	2317	3317	4317	5317	6317
1, 800	▲	±5%	2318	3318	4318	5318	6318
2, 000	▲	±1%	2319	3319	4319	5319	6319
2, 000	▲	±2%	2320	3320	4320	5320	6320
2, 000	▲	±5%	2321	3321	4321	5321	6321
2, 200	▲	±1%	2333	3322	4322	5322	6322
2, 200	▲	±2%	2323	3323	4323	5323	6323
2, 200	▲	±5%	2324	3324	4324	5324	6324
2, 400	▲	±1%	2325	3325	4325	5325	6325
2, 400	▲	±2%	2326	3326	4326	5326	6326
2, 400	300	±5%	2327	3327	4327	5327	6327

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE IV. Substitutability data.

Superseded type designation in MIL-C-23269/10	Use dash number M23269/10- in MIL-C-23269/10A FR level in %/1, 000 hrs		Superseded type designation in MIL-C-23269/10	Use dash number M23269/10- in MIL-C-23269/10A FR level in %/1, 000 hrs	
	L (2.0)	M (1.0)		L (2.0)	M (1.0)
CYR51C1R0C	2001	3001	CYR51C270F	2052	3052
CYR51C1R5C	2002	3002	CYR51C270G	2053	3053
CYR51C2R2C	2003	3003	CYR51C270J	2054	3054
CYR51C2R7C	2004	3004	CYR51C300F	2055	3055
CYR51C3R0C	2005	3005	CYR51C300G	2056	3056
CYR51C3R3C	2006	3006	CYR51C300J	2057	3057
CYR51C3R6C	2007	3007	CYR51C330F	2058	3058
CYR51C3R9C	2008	3008	CYR51C330G	2059	3059
CYR51C4R3C	2009	3009	CYR51C330J	2060	3060
CYR51C4R7C	2010	3010	CYR51C360F	2061	3061
CYR51C5R1C	2011	3011	CYR51C360G	2062	3062
CYR51C5R1J	2012	3012	CYR51C360J	2063	3063
CYR51C5R6C	2013	3013	CYR51C390F	2064	3064
CYR51C5R6J	2014	3014	CYR51C390G	2065	3065
CYR51C6R2C	2015	3015	CYR51C390J	2066	3066
CYR51C6R2J	2016	3016	CYR51C430F	2067	3067
CYR51C6R8C	2017	3017	CYR51C430G	2068	3068
CYR51C6R8J	2018	3018	CYR51C430J	2069	3069
CYR51C7R5C	2019	3019	CYR51C470F	2070	3070
CYR51C7R5J	2020	3020	CYR51C470G	2071	3071
CYR51C8R2C	2021	3021	CYR51C470J	2072	3072
CYR51C8R2J	2022	3022	CYR51C510F	2073	3073
CYR51C9R1C	2023	3023	CYR51C510G	2074	3074
CYR51C9R1J	2024	3024	CYR51C510J	2075	3075
CYR51C100C	2025	3025	CYR51C560F	2076	3076
CYR51C100J	2026	3026	CYR51C560G	2077	3077
CYR51C110C	2027	3027	CYR51C560J	2078	3078
CYR51C110J	2028	3028	CYR51C620F	2079	3079
CYR51C120C	2029	3029	CYR51C620G	2080	3080
CYR51C120J	2030	3030	CYR51C620J	2081	3081
CYR51C130C	2031	3031	CYR51C680F	2082	3082
CYR51C130G	2032	3032	CYR51C680G	2083	3083
CYR51C130J	2033	3033	CYR51C680J	2084	3084
CYR51C150C	2034	3034	CYR51C750F	2085	3085
CYR51C150G	2035	3035	CYR51C750G	2086	3086
CYR51C150J	2036	3036	CYR51C750J	2087	3087
CYR51C160C	2037	3037	CYR51C820F	2088	3088
CYR51C160G	2038	3038	CYR51C820G	2089	3089
CYR51C160J	2039	3039	CYR51C820J	2090	3090
CYR51C180C	2040	3040	CYR51C910F	2091	3091
CYR51C180G	2041	3041	CYR51C910G	2092	3092
CYR51C180J	2042	3042	CYR51C910J	2093	3093
CYR51C200C	2043	3043	CYR51C101F	2094	3094
CYR51C200G	2044	3044	CYR51C101G	2095	3095
CYR51C200J	2045	3045	CYR51C101J	2096	3096
CYR51C220C	2046	3046	CYR51C111F	2097	3097
CYR51C220G	2047	3047	CYR51C111G	2098	3098
CYR51C220J	2048	3048	CYR51C111J	2099	3099
CYR51C240C	2049	3049	CYR51C121F	2100	3100
CYR51C240G	2050	3050	CYR51C121G	2101	3101
CYR51C240J	2051	3051	CYR51C121J	2102	3102

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

TABLE IV. Substitutability data. - Continued

Superseded type designation in MIL-C-23269/10	Use dash number M23269/10- in MIL-C-23269/10A FR level in %/1, 000 hrs		Superseded type designation in MIL-C-23269/10	Use dash number M23269/10- in MIL-C-23269/10A FR level in %/1, 000 hrs	
	L (2.0)	M (1.0)		L (2.0)	M (1.0)
CYR51C131F	2103	3103	CYR52C681F	2204	3204
CYR51C131G	2104	3104	CYR52C681G	2205	3205
CYR51C131J	2105	3105	CYR52C681J	2206	3206
CYR51C151F	2106	3106	CYR52C751F	2207	3207
CYR51C151G	2107	3107	CYR52C751G	2208	3208
CYR51C151J	2108	3108	CYR52C751J	2209	3209
CYR51C161F	2109	3109	CYR52C821F	2210	3210
CYR51C161G	2110	3110	CYR52C821G	2211	3211
CYR51C161J	2111	3111	CYR52C821J	2212	3212
CYR51C181F	2112	3112	CYR52C911F	2213	3213
CYR51C181G	2113	3113	CYR52C911G	2214	3214
CYR51C181J	2114	3114	CYR52C911J	2215	3215
CYR51C201F	2115	3115	CYR52C102F	2216	3216
CYR51C201G	2116	3116	CYR52C102G	2217	3217
CYR51C201J	2117	3117	CYR52C102J	2218	3218
CYR51C221F	2118	3118			
CYR51C221G	2119	3119	CYR53C112F	2301	3301
CYR51C221J	2120	3120	CYR53C112G	2302	3302
CYR51C241F	2121	3121	CYR53C112J	2303	3303
CYR51C241G	2122	3122	CYR53C122F	2304	3304
CYR51C241J	2123	3123	CYR53C122G	2305	3305
CYR51C271F	2124	3124	CYR53C122J	2306	3306
CYR51C271G	2125	3125	CYR53C132F	2307	3307
CYR51C271J	2126	3126	CYR53C132G	2308	3308
CYR51C301F	2127	3127	CYR53C132J	2309	3309
CYR51C301G	2128	3128	CYR53C152F	2310	3310
CYR51C301J	2129	3129	CYR53C152G	2311	3311
CYR51C331F	2130	3130	CYR53C152J	2312	3312
CYR51C331G	2131	3131	CYR53C162F	2313	3313
CYR51C331J	2132	3132	CYR53C162G	2314	3314
CYR51C361F	2133	3133	CYR53C162J	2315	3315
CYR51C361G	2134	3134	CYR53C182F	2316	3316
CYR51C361J	2135	3135	CYR53C182G	2317	3317
CYR51C391F	2136	3136	CYR53C182J	2318	3318
CYR51C391G	2137	3137	CYR53C202F	2319	3319
CYR51C391J	2138	3138	CYR53C202G	2320	3320
CYR51C431F	2139	3139	CYR53C202J	2321	3321
CYR51C431G	2140	3140	CYR53C222F	2322	3322
CYR51C431J	2141	3141	CYR53C222G	2323	3323
CYR51C471F	2142	3142	CYR53C222J	2324	3324
CYR51C471G	2143	3143	CYR53C242F	2325	3325
CYR51C471J	2144	3144	CYR53C242G	2326	3326
CYR51C511F	2145	3145	CYR53C242J	2327	3327
CYR51C511G	2146	3146			
CYR51C511J	2147	3147			
CYR51C561F	2148	3148			
CYR51C561G	2149	3149			
CYR51C561J	2150	3150			
CYR52C621F	2201	3201			
CYR52C621G	2202	3202			
CYR52C621J	2203	3203			

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 17

Review activities:
Army - EL
Navy -
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - None
Navy - MC, CG, AS, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5910-1008-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commander
Naval Electronic Systems Command
Defense Standardization Program Branch
Department of the Navy
Washington DC 20360

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.