MIL-C-23269/10A
AMENDMENT 5
10 April 1984
SUPERSEDING
AMENDMENT 4
4 October 1983

MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, GLASS DIELECTRIC,
(RADIAL WIRE-LEAD TERMINALS), ESTABLISHED RELIABILITY,
STYLES CYR51, CYR52, AND CYR53

This amendment forms a part of Military Specification Sheet MIL-C-23269/10A, dated 30 September 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following title, insert: "FAILURE RATE LEVEL 'L' IS INACTIVE FOR DESIGN AFTER 20 JULY 1983"

PAGE 2

After case material: Delete "Terminal - Type D of MIL-STD-1276" and substitute "Terminals - Type D2 (gold plated copper clad iron-nickel alloy) of MIL-STD-1276. Type D5 (Hot solder dip copper clad iron-nickel alloy) of MIL-STD-1276 may be furnished when specified in the contract or purchase order."

* Thermal shock and moisture resistance, delete and substitute:

"Thermal shock and moisture resistance, Qualification and group C inspection:

DF - 0.3% maximum (1 thru 100 pF) or 0.1% maximum (110 pF and up).

Thermal shock, Group A inspection: Capacitance shall be within the tolerance specified (see table I).
DF shall be within the initial limits".

NOTE: The margin of this amendment is marked with an asterisk to indicate where a change (addition) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 11
NASA - NA

Review activities:
Air Force - 17, 85
DLA - ES

User activities:
Navy - AS, CG, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1491)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:16Z
Check the source to verify that this is the current version before use.