MIL-R-23285B
AMENDMENT 5
5 August 1975
SUPERSEDING
AMENDMENT 4
17 November 1971

MILITARY SPECIFICATION

RESISTORS, VARIABLE, NONWIRE-WOUND

GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-R-23285B, dated 13 September 1967, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3

2.1, list of FEDERAL SPECIFICATIONS: Delete "PPP-B-566, PPP-B-676, PPP-B-636, PPP-T-60, and PPP-T-76", and all corresponding titles. List of MILITARY SPECIFICATIONS: Delete "MIL-P-116 - Preservation, Methods of", and substitute "MIL-F-39032 - Resistors, Preparation for Delivery of." List of MILITARY STANDARDS: Delete "MIL-STD-129 - Marking for Shipment and Storage."

Page 4

* 3.2, at end of paragraph add: "Not applicable for style covered by MIL-R-23285/2."

* Following 3.2, add new subparagraph 3.2.1:

"3.2.1 Production testing. Resistors furnished under MIL-R-23285/2 shall pass the production tests as specified."

Page 9

3.14, line 3: Delete "±5 percent", and substitute "±2 percent."

Page 10

3.20, in title: Delete "Shock, medium impact", and substitute "Shock (specified pulse)."

Page 12

TABLE VI, Group VII, column 1: Delete "Shock, medium impact", and substitute "Shock (specified pulse)."

Page 13

4.5.1, delete and substitute:

"4.5.1 Inspection of product for delivery. Inspection of product for delivery shall consist of groups A and B inspection. Except as specified in 4.5.1.4.3, delivery of products which have passed the groups A and B inspection shall not be delayed pending the results of the group C inspection."

Page 14

4.5.1.4, lines 1 and 2. Delete "weekly, monthly, and quarterly", and substitute "monthly, quarterly, and semiannually".

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:18Z
Check the source to verify that this is the current version before use.

Page 14 - Continued

TABLE IX, column 1, line 1: Delete "Weekly", and substitute "Monthly".
Line 9: Delete "Monthly" and substitute "Quarterly".
Line 14: Delete "Quarterly", and substitute "Semiannually".

TABLE IX, Semiannually, Subgroup 1: Delete "Shock, medium impact", and substitute "Shock (specified pulse)."

Page 15

4.5.1.4.1, line 4: Delete "weekly and monthly", and substitute "monthly and quarterly". Line 5: Delete "quarterly", and substitute "semiannually". Line 7: Delete "quarterly", and substitute "semiannually".

4.5.2, delete and substitute:

"4.5.2 Inspection of preparation for delivery. Sample packages and packs and the inspection of the preservation, packaging, packing and marking for shipment and storage shall be in accordance with the requirements of MIL-R-39032."

Page 21

4.6.9.2, under column "Bushings L and T": Delete "0 cycle". Under column "Bushings S and N": Delete "0 cycle", and substitute "1,000 cycles".

Page 24

4.6.17: Delete "Shock, medium impact (see 3.20. Resistors shall be tested in accordance with method 205 of MIL-STD-202.", and substitute "Shock (specified pulse) (see 3.20). Resistors shall be tested in accordance with method 213, test condition I, MIL-STD-202 (100G, 6 ms)."

Page 27

SECTION 5, "PREPARATION FOR DELIVERY", delete in its entirety and substitute:

"5. PREPARATION FOR DELIVERY

5.1 Preparation. Resistors shall be prepared for delivery in accordance with MIL-R-39032."

Page 29

6.1.1: Delete in its entirety.

Page 30

6.8.4 Add new paragraph:

"6.8.4 Shaft length substitution data. Shaft length symbols "C" and "A" of MIL-R-23285A(NAVY) are replaced as follows under revision B of this specification:

Shaft length symbol of MIL-R-23285A(NAVY)	Revision B shaft length symbol
C (5/8 inch)	A (5/8 inch)
A (3/8 inch)	L (3/8 inch)"

Source: https://assist.dla.mil -- Downloaded: 202610-19T16:18Z
Check the source to verify that this is the current version before use.

Page 30 - Continued

6.10, in title: Delete "Shock, medium impact", and substitute "Shock (specified pulse)".

6.12, delete and substitute:

"6.12 Copies of Provisions Governing Qualification SD-6 may be obtained upon application to Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120."

Page 34

30.2, line 6, delete and substitute:

"Bushing types:
N or S will qualify L or T when lot 5 of TABLE XII is submitted with an N or S (lots 1 through 4) submission. Qualification of resistors with standard (N) type bushing shall qualify resistors with sealed (S) type bushing. Conversely, qualification of resistors with sealed (S) type bushing shall qualify resistors with standard (N) type bushing. Qualification of resistors with locking (L) type bushing shall qualify resistors with sealed (T) type bushing. Conversely, qualification of resistors with sealed (T) type bushing shall qualify resistors with locking (L) type bushings."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - MI, MU
Navy - AS, OS
Air Force - 17, 80
DSA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5905-0884)

Source: https://assist.dla.mil -- Downloaded: 202610-19T16:18Z
Check the source to verify that this is the current version before use.