MIL-R-23285B
SUPPLEMENT 1B
13 August 1970
SUPERSEDING
SUPPLEMENT 1A
11 July 1968

MILITARY SPECIFICATION

RESISTORS, VARIABLE, NONWIRE-WOUND

GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-R-23285B, dated 13 September 1967, and is mandatory for use by all Departments and Agencies of the Department of Defense.

MIL-R-23285/2 - Resistors, Variable, Nonwire-Wound. Style RVC5.
MIL-R-23285/3 - Resistors, Variable, Nonwire-Wound. Style RVC6.

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5905-0728-1)

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:18Z
Check the source to verify that this is the current version before use.

TABLE I. Performance characteristics.

Style	RVC5	RVC6
Maximum resistance-temperature coefficient in ppm/°C (referred to 25°C)	±250	±250
Maximum ambient temperature at rated wattage (see figure 2)	125°C	125°C
Maximum ambient temperature at zero wattage derating (see figure 2)	175°C	175°C
Power rating (in watts) (see 3.1)	1 watt taper-A 1/2 watt taper-C	1/2 watt taper-A 1/4 watt taper-C
Minimum resistance value (ohms)	100	100
Maximum resistance value (megohms)	2.5	2.5
Resistance tolerance percent ±	10	10
Maximum percent change in resistance as follows:		
Contact resistance variation (see 3.8)	±3%	±3%
Resistance to soldering heat (see 3.11)	±1%	±1%
Rotational life (see 3.12)		
1,000 cycles	±2%	±2%
25,000 cycles	±4%	±4%
50,000 cycles	±5%	±5%
Life (see 3.13)	±3%	±3%
Moisture-resistance (see 3.14)	±2%	±2%
Low-temperature operation (see 3.17)	±1%	±1%
Temperature cycling (see 3.18)	±1%	±1%
High-temperature exposure (see 3.19)	±4%	±4%
Shock (specified pulse) (see 3.20)	±2%	±2%
Vibration, high frequency (see 3.21)	±2%	±2%
Insulation resistance (wet)	100 megohms (minimum)	100 megohms (minimum)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:18Z
Check the source to verify that this is the current version before use.