INCH-POUND
MIL-C-48890B(AR)
AMENDMENT 2
4 October 1996
SUPERSEDING
AMENDMENT 1
29 March 1991

MILITARY SPECIFICATION

CONTROL PANEL ASSEMBLY FOR
M130 DISPENSER SYSTEM

This amendment forms a part of MIL-C-48890B(AR), dated 14 January 1985, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Issue of documents. Add the following specification:

"MIL-L-85762 - Lighting, Aircraft, Interior, AN/ANS-6 Aviator's Night Vision Imaging System (ANVIS) Compatible"

PAGE 2

2.1.2: Delete from list of drawings:

"9321931 - Packing and Marking for Box, Exterior for Panel Dispenser Control: M130"

PAGE 3

* 3.3.1 Power up: Delete "22.5" and substitute "24.0".

* 3.3.2 Safe/arm: Delete "22.5" and substitute "24.0".

* 3.3.4 Flare ripple fire: Delete "22.5" and substitute "24.0".


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

PAGE 5

* Figure 1 Count signal: Delete “20.0” and substitute “24.0”.

PAGE 7

TABLE I - Panel, Edge, Lighting. Delete “Dwg. 9272532” and substitute “12597636”.

PAGE 14

4.4.2.5 Panel, Edge, Lighting. Delete “Dwg. 9272532” and substitute “12597636”.

Add the following:

“105 Lighting, ANVIS Compatible (1/)

a. Luminance and illumination 0.40% 3.2 4.8.12 of MIL-L-85762

b. Chromaticity 0.40% 3.2 4.8.13 of MIL-L-85762

c. Spectral radiance 0.40 3.2 2/
or
Spectral radiance 100% 3.2 3/”

Add note:

“1/ Sampling plans shall be in accordance with MIL-STD-105, Inspection Level II.

2/ Inspect in accordance with 4.8.14 of MIL-L-85762, Spectral radiance measurements except that the radiance limit shall be as specified on Dwg. 12597636.

3/ Alternate Method to be pre-approved by the Government (see 6.3). An edge light panel, which has been inspected and accepted to the requirements of 4.8.14 of MIL-L-85762 may be used in production (5 or more) as an IR calibration source.”

PAGE 17

4.4.2.8 Delete in its entirety.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

PAGE 18

4.4.2.9 Delete in its entirety.

PAGE 22

5.1.1: Delete “... drawing 9321931 ...” and substitute “... Special Packaging Instructions P9272533 ...”.

5.2.1: Delete “... drawing 9321931 ...” and substitute “... Special Packaging Instructions P9272533 ...”.

5.3.1: Delete “... drawing 9321931 ...” and substitute “... Special Packaging Instructions P9272533 ...”.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-0026)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.