INCH-POUND
MIL-C-48890B(AR)
AMENDMENT 3
10 July 1998
SUPERSEDING
AMENDMENT 2
4 October 1996

MILITARY SPECIFICATION

CONTROL PANEL ASSEMBLY FOR
M130 DISPENSER SYSTEM

MIL-C-48890 was inactivated after 13 August 1997 for new design.

This amendment forms a part of MIL-C-48890B(AR), dated 14 January 1985, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Issue of documents. Add the following specification:

"MIL-L-85762 - Lighting, Aircraft, Interior, AN/ANS-6 Aviator's Night Vision Imaging System (ANVIS) Compatible"

PAGE 2

2.1.2: Delete from list of drawings:

"9321931 - Packing and Marking for Box, Exterior for Panel Dispenser Control: M130"

PAGE 3

3.3.1 Power up: Delete "22.5" and substitute "24.0".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

3.3.2 Safe/arm: Delete "22.5" and substitute "24.0".

3.3.4 Flare ripple fire: Delete "22.5" and substitute "24.0".

* 3.4.1 Helicopter vibration. Delete "... MIL-STD-810C, Test Method 514.2, Procedure I, Part 1, Category 6 using curve C of Figure 514.5-2 and curve M of Figure 514.2-3." and substitute "... MIL-STD-810, Test Method 514.4, Category 6."

* 3.4.2 Transportation vibration. Delete "... MIL-STD-810C, Test Method 514.2, Procedure X, using curve AW of Figure 514.2-7 (change curve to 0.8" displacement (double amplitude) between 5 and 6 Hz)". and substitute "... MIL-STD-810, Test Method 514.4, Basic Transportation, Category I."

* 3.4.3 Shock. Delete "... MIL-STD-810C, Test Method 516.2, Procedure I, using peak value (a) and nominal duration (c) in Figure 516.2-1." and substitute "... MIL-STD-810, Test Method 516.4, Procedure I. Three sawtooth pulses shall be applied in each direction along three (3) mutually perpendicular axes for a total of eighteen (18) shocks at peak value of 20g's and a nominal duration of 11 ms."

* 3.4.4 Low temperature. Delete paragraph in its entirety and substitute "3.4.4 Low temperature. The control panel shall perform all functions satisfactorily at -51°C for 24 hours according to MIL-STD-810, Test Method 502.3, Procedure II, Severe Cold."

PAGE 4

* 3.4.5 High temperature. Delete "... MIL-STD-810C, Test Method 501.1 ..." and substitute "... MIL-STD-810, Test Method 501.3, Procedure II, Hot, induced for 72 hours."

PAGE 5

Figure 1 Count signal: Delete "20.0" and substitute "24.0".

PAGE 7

TABLE I - Panel, Edge, Lighting. Delete "Dwg. 9272532" and substitute "12597636".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

PAGE 14

4.4.2.5 Panel, Edge, Lighting. Delete "Dwg. 9272532" and substitute "12597636".

Add the following:

"105 Lighting, ANVIS Compatible (1/)

a. Luminance and illumination 0.40% 3.2 4.8.12 of MIL-L-85762

b. Chromaticity 0.40% 3.2 4.8.13 of MIL-L-85762

c. Spectral radiance 0.40 3.2 2/
or
Spectral radiance 100% 3.2 3/"

Add note:

"1/ Sampling plans shall be in accordance with MIL-STD-105, Inspection Level II.

2/ Inspect in accordance with 4.8.14 of MIL-L-85762, Spectral radiance measurements except that the radiance limit shall be as specified on Dwg. 12597636.

3/ Alternate Method to be pre-approved by the Government (see 6.3). An edge light panel, which has been inspected and accepted to the requirements of 4.8.14 of MIL-L-85762 may be used in production (5 or more) as an IR calibration source."

PAGE 17

4.4.2.8 Delete in its entirety.

PAGE 18

4.4.2.9 Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

* 4.5.2 Low temperature. Delete "... -54 ± 2°C according to MIL-STD-810C, Test Method 502.1 ..." and substitute "... -51 ± 2° for 24 hours according to MIL-STD-810, Test Method 502.3, Procedure II, Severe Cold, ...".

* 4.5.3 High temperature. Delete "... according to MIL-STD-810C, Test Method 501.1 ..." and substitute "... for 72 hours according to MIL-STD-810, Test Method 501.3, Procedure II, Hot, ...".

* 4.5.4 Transportation vibration. Delete "... MIL-STD-810C, Method 514.2, Procedure X using curve AW of Figure 514.2-7 (change curve to 0.8" Displacement (double amplitude) between 5 and 6 Hz)." and substitute "... MIL-STD-810, Method 514.4, Basic Transportation, Category I."

* 4.5.5 Helicopter vibration. Delete "... MIL-STD-810C, Test Method 514.2, Procedure I, Part 2. One DCP should be tested to curve C of Figure 514.2-2 and the other DCP should be tested to curve M of Figure 514.2-3." and substitute "... MIL-STD-810, Method 514.4, Category 6."

* 4.5.6 Shock. Delete "... MIL-STD-810C, Test Method 516.2, Procedure I, using peak value (a) and nominal duration (c) in Figure 516.2.1." and substitute "... MIL-STD-810, Test Method 516.4, Procedure I, applying three (3) sawtooth pulses in each direction along three (3) mutually +perpendicular axes for a total of eighteen (18) shocks at a peak value of 20g's and a nominal duration of 11 ms."

5.1.1: Delete "... drawing 9321931 ..." and substitute "... Special Packaging Instructions P9272533 ...".

5.2.1: Delete "... drawing 9321931 ..." and substitute "... Special Packaging Instructions P9272533 ...".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.

5.3.1: Delete "... drawing 9321931 ..." and substitute "... Special Packaging Instructions P9272533 ...".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-0046)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:43Z
Check the source to verify that this is the current version before use.