MILITARY STANDARD

UNIT LOADS OF AMMUNITION AND EXPLOSIVES FOR DOMESTIC AND OVERSEAS SHIPMENT

TO ALL HOLDERS OF MIL-STD-1323 (NAVY)

Make the following pen and ink changes to Appendix B, pgs 18 and 19.

a. Para 40.3.2.1a. Add the following, "Samples for testing may also be made on a dummy unit load set up for this purpose and tested in accordance with para. 40.6.

b. Delete para. 40.3.2.2a.

c. Change para. 40.3.2.2d to read "quarterly" instead of "monthly".

d. Redesignate sub-paragraph 40.3.2.2b, c and d as 40.3.2.2a, b, and c respectively.

e. Change para. 40.5 to read "at least 12 inches overall and at least 8 inches between --------".

f. Change para. 40.6.1 as follows. Delete the second and third sentences and substitute the following: "Activate the tensile tester and apply the load to the test specimen until it reaches 500 lbs. above the minimum value required or fails. Record the results as follows:

(1) ☐ failed below 1900 lbs for 3/4 in. or 3000 lbs for 1 1/4 in.

(2) ☐ failed beyond (1) above but before the test limit, i.e. 2400 lbs. for 3/4 in. and 3500 lbs. for 1 1/4 in.

(3) ☐ failed beyond test limit, see (2) above.

"A tensile tester pull rate of approximately 0.2 inches/minute should be used."

Activity:
Review Activity
Navy - OS, AS

Preparing Activity
NAVY - OS
(Project No. 8140-N631)
FSC 8140

DISTRIBUTION STATEMENT A
Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:51Z
Check the source to verify that this is the current version before use.