MILITARY SPECIFICATION SHEET

CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-50288(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-50288(MU) - Cable Assemblies for War Reserve Atomic Demolition Charges, General Specification for

STANDARDS

MILITARY

AN960-C4 - Washer
MS35233-14 - Screw
MS35649-44 - Nut

DRAWINGS

ORDNANCE CORPS

8800545 - Bag, Packing, Ammunition, for Cable Assembly
8808362 - Packing and Marking for Storage and Shipments
8825655 - Cable Clip
8836605 - Cable Assembly
8854368 - Fixture, Pull Test
8864110 - Connector
9214694 - Cover, Electrical
EL-8836605 - Equipment List

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-50288(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 8836605)

From Connector	To other Connector	Ohms Max
Pin	Pin	15.00
Shell	Shell	0.75

3.3 Pull. The cable assembly shall withstand a pull of 5 pounds, minimum without evidence of slippage or loosening of parts. After test, the cable assembly shall comply with circuit resistance and insulation resistance, section 3, MIL-C-50288(MU) when tested as specified in 4.6.1.

3.4 Dielectric strength. The cable assembly shall be subjected to a voltage of 1500 ± 100 volts alternating current (vac), 60 ± 3 cycles per second and shall not indicate a leakage current to exceed 200 micro-amperes. There shall be no indication of insulation breakdown. Testing shall be conducted in accordance with 4.6.3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.2 Inspection and testing to be performed in first article testing (see Table I, MIL-C-50288(MU)). Add the following tests:

Examination	Contractor's inspection permissable before submission	Non-Dest.	Assembly
Pull (see 3.3)	X	X	X
Dielectric strength (see 3.4)	X	X	X

4.3 Classification of characteristics.

4.3.1 Cable clip (see dwg 8825655); connector (see dwg 8864110); cover, electrical (see dwg 9214694); washer (see AN960-C4); screw (see MS35233-14); nut (see MS35649-44) covering details of dwg 8836605.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see Objective evidence, section 6, MIL-C-50788(MU) available for part in accordance with applicable drawing or standard.....Visual

Minor: None defined.

4.3.2 Cable assembly (see dwg 8836605).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length.....*Measure
102. Large diameter of connector mold.....*Measure
103. Length from end of mold to end of mold taper.....*Measure
104. Length of mold taper.....*Measure
105. Small diameter of connector mold.....*Measure
106. Taper of mold present adjacent to connector.....Visual
107. Adhesive applied to collet clamp, no voids between cable and connector filled with adhesive.....Visual

* Measure with suitable scale.

Minor: None defined.

4.4 Testing. Testing shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.4.1 Pull (see 3.3). Each connector on the cable assembly shall be tested as specified in 4.6.1. If any connector fails to comply with 3.3, the cable assembly shall be rejected and removed from the lot.

4.4.2 Dielectric strength (see 3.4). Each cable assembly shall be tested as specified in 4.6.3. If any cable assembly fails to comply with 3.4, the cable assembly shall be rejected and removed from the lot.

4.5 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-50288(MU) and EL-8836605.

4.6 Test methods. Test methods shall be in accordance with MIL-C-50288(MU) and as specified herein.

4.6.1 Pull (see 3.3). The pull test shall be performed by utilizing test fixture dwg 8854368. In addition, the cable shall be gripped not closer than 12 inches from the connector in such a manner that there

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

will be no damage to the cable by gripping nor slippage during the test. The pull shall be applied to the cable for a minimum of 30 seconds and after the test the cable assembly shall comply with Circuit and Insulation resistance, section 3, MIL-C-50288(MU).

4.6.2 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg 8836605)

Positive potential applied to connector Pin	Minus potential to other connector shell

4.6.3 Dielectric strength (see 3.4). The dielectric strength shall be measured with an approved insulation leakage tester in accordance with Table III for a period of one minute minimum.

Table III

Dielectric strength test voltage (see dwg 8836605)

From connector	To connector
Pin	Shell

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-50288(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-50288(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800545 and 8808362 and as specified in MIL-C-50288(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-50288(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8800545 and 8808362 and MIL-C-50288(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800545 and 8808362 and MIL-C-50288(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-50288(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU

Project No. - 1125-A040

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-C-50288/2(MU) Cable Assembly

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.